

## SAINTS DIAMOND DRILLING UNDERWAY

### Highlights

- Major diamond drill programme has commenced at the Saints Nickel Project to update and potentially increase the current high-grade Mineral Resources of **1.02Mt @ 2.0% Ni for 21,400kt of contained nickel<sup>1</sup>**
- 3,000m of infill drilling to be completed across the Saint Patricks and Saint Andrews prospects, with an additional 2,000m planned to test for down-plunge extensions to the known high-grade nickel sulphide mineralisation
- Bulk composite samples will be taken from some of the drill core to be used for metallurgical testwork
- The drill programme will take approximately 6 weeks to complete and the results will be used in the Saints Scoping Study due for completion at the end of March

Auroch Minerals Limited (**ASX:AOU**) (**Auroch** or the **Company**) is pleased to announce it has commenced a major diamond drill programme at its 100%-owned Saints Nickel Project (**Saints**) in Western Australia.

The programme comprises approximately 3,000m of infill drilling across the Saint Patricks and Saint Andrews prospects (Figure 1), with the aim to update **the current JORC(2012)-compliant Saints Mineral Resource Estimate (MRE) of 1.02Mt @ 2.0% Ni for 21,400kt of contained nickel<sup>1</sup>** and increase the confidence level from the Inferred Resource category to predominantly Indicated Resources. Also included in this programme are two drill-holes specifically designed to collect large bulk composite samples for metallurgical testwork.

A further 2,000m of drilling has been planned to test for possible strike and down-plunge extensions to the known high-grade nickel sulphide mineralisation at Saints, particularly below the Saint Andrews Prospect to test for extensions of the mineralised lava channel, where previous drill hole geochemistry indicates hotter ultramafic rocks (i.e. >42% MgO) at depth. A review of historic down-hole electromagnetic (DHEM) data in this zone is also being completed.

#### **Auroch Managing Director Aidan Platel commented:**


*"We are very pleased to have kicked off a major diamond drill programme at Saints. The infill drilling is critical to increasing the confidence in the MRE to a predominantly Indicated Resource category so that it can underpin the current Saints Scoping Study due to be completed at the end of March. It will also provide necessary bulk samples to initiate the metallurgical testwork that is also critical information for the completion of the study.*

*The planned concurrent exploration drilling will test down-plunge from the known high-grade nickel sulphide mineralisation at the Saint Patricks and Saint Andrews prospects as the search continues for the "feeder" lava channel to this nickel-rich system and of course, the nickel sulphide mineralisation that is associated with such channels in Kambalda-style nickel deposits such as the Saints!"*

Both the new MRE and the metallurgical testwork results will provide important inputs for the ongoing Scoping Study at the Saints Nickel Project. To date the Scoping Study is progressing well with site flora

<sup>1</sup> JORC (2012) Inferred Resources, above a 1.0% Ni cut-off grade. Refer to ASX Announcement - AUROCH TO ACQUIRE HIGH-GRADE WESTERN AUSTRALIAN NICKEL PROJECTS <https://www.asx.com.au/asxpdf/20190528/pdf/445dz31g15d0kx.pdf>.

and fauna surveys completed, miscellaneous licence applications for the future haul road location submitted, and mine design and optimisation well underway.



**Figure 1** – Long section of the Saints Nickel Project showing the current nickel sulphide resource (1%Ni cut-off) and the planned pierce points from the major diamond drill programme now underway

This announcement has been authorised by the Board of Directors of the Company.

-END-

For further information visit [www.aurochminerals.com](http://www.aurochminerals.com) or contact:

Aidan Platel

**Managing Director**

E: [aplattel@aurochminerals.com](mailto:aplattel@aurochminerals.com)


**Competent Persons Statement**

*The information in this report that relates to Exploration Results is based on information compiled by Mr Matthew McCarthy and represents an accurate representation of the available data. Mr McCarthy (Member of the Australian Institute of Mining and Metallurgy) is the Company's Senior Geological Officer and has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves' ("JORC Code 2012"). Mr McCarthy consents to the disclosure of this information in this report in the form and context in which it appears.*

**Forward-Looking Statements**

*This document may include forward-looking statements. Forward-looking statements include, but are not limited to, statements concerning Auroch Minerals Limited's planned exploration programmes and other statements that are not historical facts. When used in this document, the words such as "could," "plan," "estimate," "expect," "intend," "may", "potential", "should," and similar expressions are forward-looking statements. Although Auroch Minerals Limited believes that its expectations reflected in these forward-looking statements are reasonable, such statements involve risks and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements.*

For personal use only



**Figure 2 – Location and geology map of the Saints Nickel Project**

For personal use only

JORC Code, 2012 Edition, Table 1  
Section 1: Sampling Techniques and Data

CRITERIA	EXPLANATION	COMMENTARY
<b>Sampling techniques</b>	<ul style="list-style-type: none"> <li>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</li> <li>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</li> <li>Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1m samples from which 3kg was pulverised to produce a 30g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</li> </ul>	<p>Drilling Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>Nickel mineralisation at Saints has been sampled from the following drilling techniques:</li> <li>Diamond Core - half core samples with a maximum of 1.2m and minimum 0.2m length.</li> <li>RC drilling - 1m samples of pulverised chips, approximately 3kg's is collected in individual calico bags</li> <li>Air Core drilling creates single metre sample of drill chips, however samples are composited every 3 metres, with the end of hole sample consisting of a 1m sample.</li> </ul> <p><b>DHEM Parameters:</b></p> <p>Contractor: SGC Niche Acquisition            Configuration: Down-hole EM (DHEM)            Tx Loop size: 300x300m to 350x450m, single turn            Transmitter: TTX2            Receiver: Smartem24            Sensor: DigiAtlantis            Station spacing: 2m to 10 m            Tx Freq: 0.5 Hz            Duty cycle: 50%            Current: ~68-75 Amp            Stacks: 64            Readings: 2-3 repeatable readings per station</p>
<b>Drilling techniques</b>	<ul style="list-style-type: none"> <li>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc).</li> </ul>	<ul style="list-style-type: none"> <li>Diamond Core (DD) drilling is referenced in this report. Core is oriented and retrieved via double or triple tube methods.</li> </ul>
<b>Drill sample recovery</b>	<ul style="list-style-type: none"> <li>Method of recording and assessing core and chip sample recoveries and results assessed.</li> <li>Measures taken to maximise sample recovery and ensure representative nature of the samples.</li> <li>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</li> </ul>	<ul style="list-style-type: none"> <li>DD core recovery is measured and recorded by Auroch staff and contractors.</li> <li>No relationship between sample recovery and grade has been yet observed and no sample bias is believed to have occurred.</li> </ul>

For personal use only

CRITERIA	EXPLANATION	COMMENTARY
<b>Logging</b>	<ul style="list-style-type: none"> <li>• Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>• Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>• The total length and percentage of the relevant intersections logged.</li> </ul>	<p>Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>• Drill core is lithologically and structurally logged by Geologists in the field.</li> <li>• Drill chips are lithologically logged by Geologists in the field</li> <li>• Logging is qualitative, recording rock type and mineral abundance</li> <li>• Logging of RC &amp; AC chips is conducted on a 1 metre sample size.</li> <li>• Logging of DD core is conducted on lithological boundaries.</li> </ul> <p>Historic:</p> <ul style="list-style-type: none"> <li>• Geological logging data collected to date is sufficiently detailed. At this stage detailed geotechnical logging is not required.</li> <li>• Geological logging is intrinsically qualitative.</li> <li>• Historic drill holes were geologically logged by previous operators and these data are available to Auroch Minerals.</li> </ul>
<b>Sub-sampling techniques and sample preparation</b>	<ul style="list-style-type: none"> <li>• If core, whether cut or sawn and whether quarter, half or all core taken.</li> <li>• If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</li> <li>• For all sample types, the nature, quality and appropriateness of the sample preparation technique.</li> <li>• Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>• Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>• Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<p>Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>• Diamond core is sawn in half with half used for sampling and the other half retained for future reference.</li> <li>• 1m RC percussion, sample is split via a cyclone and cone splitter attached to the drill rig to produce a bagged 3kg sample.</li> <li>• Certified reference material and blank material are inserted every 20 samples as per company QAQC procedure for both DD &amp; RC.</li> <li>• Field duplicates collected from the Cyclone and cone splitter are inserted every 60 samples</li> <li>• No further sub sampling has been conducted</li> <li>• 3m AC sample composites are scooped from sample piles to create a 3kg bagged sample.</li> <li>• Certified reference material are inserted every 30 samples as per the company Air Core QAQC procedure.</li> </ul> <p>Historic:</p> <ul style="list-style-type: none"> <li>• 1m RC percussion, maximum 1m length core samples, or as close as reasonable within geological boundaries, are considered appropriate for the style of mineralisation being targeted.</li> <li>• Historic drill holes were logged at level of detail to ensure sufficient geological understanding to allow representative selection of sample intervals.</li> <li>• Sampling QAQC measures taken by previous operators not fully documented.</li> </ul>

For personal use only

CRITERIA	EXPLANATION	COMMENTARY
<b>Quality of assay data and laboratory tests</b>	<ul style="list-style-type: none"> <li>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</li> <li>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</li> <li>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</li> </ul>	<p>Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>ALS Minerals, multi element analysis method ME-ICP61 utilised for all samples, consisting of multi acid digestion with HF and ICP-AES analysis. Over limit method Ni-OG62H for ore grade Ni consisting of four acid digestion with ICP-AES analysis. PGM-ICP23 fire assay ICP-AES finish method used selectively for samples considered to contain Pt, Pd &amp; Au. All methods are considered suitable for the style of mineralisation targeted.</li> <li>Certified Reference Material (CRM's) and quartz blank (Blanks) samples are inserted 1:20 for DD &amp; RC and 1:30 for AC as part of Auroch's QAQC procedure. Accuracy and performance of CRM's and Blanks are considered after results are received.</li> <li>Field duplicates collected from the Cyclone and cone splitter are inserted every 60 samples</li> </ul>
<b>Verification of sampling and assaying</b>	<ul style="list-style-type: none"> <li>The verification of significant intersections by either independent or alternative company personnel.</li> <li>The use of twinned holes.</li> <li>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</li> <li>Discuss any adjustment to assay data.</li> </ul>	<p>Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>No third party verification has been completed to date</li> <li>Drill holes have not been twinned</li> <li>All primary paper data is held on site, digitised data is held in a managed database off site.</li> <li>No adjustments to assays have occurred.</li> </ul> <p>Historic:</p> <ul style="list-style-type: none"> <li>All historic drilling data including collar coordinates, hole orientation surveys, total depth, sampling intervals and lithological logging were collated from statutory annual reports and historic digital data files and verified by Auroch's Geologists.</li> <li>No indication of drill holes being twinned by previous workers has been observed or documented.</li> <li>It is assumed that industry best practice was used for collection, verification and storage of historic data.</li> <li>No adjustments to assay data were undertaken.</li> </ul>
<b>Location of data points</b>	<ul style="list-style-type: none"> <li>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</li> <li>Specification of the grid system used.</li> <li>Quality and adequacy of topographic control.</li> </ul>	<p>Auroch Minerals Limited:</p> <ul style="list-style-type: none"> <li>Drill collars were surveyed in GDA94/MGA Zone 51 datum for Saints by handheld GPS +5m accuracy</li> <li>At completion of programme drill collars will be surveyed using a Differential GPS +- 0.1m accuracy.</li> </ul>

For personal use only

CRITERIA	EXPLANATION	COMMENTARY
<b>Data spacing and distribution</b>	<ul style="list-style-type: none"> <li>Data spacing for reporting of Exploration Results.</li> <li>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</li> <li>Whether sample compositing has been applied.</li> </ul>	Auroch Minerals Limited: <ul style="list-style-type: none"> <li>Drill data spacing of historic drill data is sufficient to establish the degree of geological and grade continuity appropriate for estimating an Inferred Ni Resource.</li> </ul>
<b>Orientation of data in relation to geological structure</b>	<ul style="list-style-type: none"> <li>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</li> <li>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</li> </ul>	Auroch Minerals Limited: <ul style="list-style-type: none"> <li>Drill holes azimuth is nominally planned perpendicular to stratigraphic strike</li> <li>Drill hole dip is regarded suitable for subvertical stratigraphy and provides a near true width intersection to minimise orientation bias.</li> </ul> Historic: <ul style="list-style-type: none"> <li>Historical drill holes were oriented, as far as reasonably practical, to intersect the centre of the targeted mineralised zone perpendicular to the interpreted strike orientation of the mineralised zone.</li> <li>The geometry of drill holes relative to the mineralised zones achieves unbiased sampling of this deposit type.</li> <li>No orientation-based sampling bias has been identified.</li> </ul>
<b>Sample security</b>	<ul style="list-style-type: none"> <li>The measures taken to ensure sample security.</li> </ul>	Auroch Minerals Limited: <ul style="list-style-type: none"> <li>Diamond core samples are dispatched once all cutting and sampling of drill core is complete. Drill core is maintained in a secure core yard or onsite facility.</li> </ul> Historic: <ul style="list-style-type: none"> <li>It is assumed that due care was taken historically with security of samples during field collection, transport and laboratory analysis.</li> </ul>
<b>Audits or reviews</b>	<ul style="list-style-type: none"> <li>The results of any audits or reviews of sampling techniques and data.</li> </ul>	<ul style="list-style-type: none"> <li>No independent audit or review has been undertaken.</li> </ul>

## Section 2: Reporting of Exploration Results

CRITERIA	EXPLANATION	COMMENTARY
<b>Mineral tenement and land tenure status</b>	<ul style="list-style-type: none"> <li>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</li> <li>The security of the tenure held at the time of reporting along with any known</li> </ul>	<ul style="list-style-type: none"> <li>The Saints Nickel Project consists of two Mining Leases M29/245 and M29/246</li> <li>No known royalties exist on the leases.</li> <li>There are no material issues with regard to access.</li> <li>The tenements are in good standing and no known impediments exist.</li> </ul>

CRITERIA	EXPLANATION	COMMENTARY
	impediments to obtaining a licence to operate in the area.	
<b>Exploration done by other parties</b>	<ul style="list-style-type: none"> <li>Acknowledgment and appraisal of exploration by other parties.</li> </ul>	<ul style="list-style-type: none"> <li>At Saints previous work has been conducted by WMC Resources, Scotia Nickel Ltd, Breakaway Resources and Minotaur Gold Solutions</li> <li>Data collected by these entities has been reviewed in detail by Auroch.</li> </ul>
<b>Geology</b>	<ul style="list-style-type: none"> <li>Deposit type, geological setting and style of mineralisation.</li> </ul>	<ul style="list-style-type: none"> <li>The Saints Nickel Project is regarded as an Archaean komatiite-hosted nickel sulphide deposit.</li> </ul>
<b>Drill hole Information</b>	<ul style="list-style-type: none"> <li>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: <ul style="list-style-type: none"> <li>easting and northing of the drill hole collar</li> <li>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</li> <li>dip and azimuth of the hole</li> <li>down hole length and interception depth</li> <li>hole length.</li> </ul> </li> <li>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</li> </ul>	<ul style="list-style-type: none"> <li>Relevant drillhole information is included in this announcement.</li> </ul>
<b>Data aggregation methods</b>	<ul style="list-style-type: none"> <li>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</li> <li>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</li> <li>The assumptions used for any reporting of metal equivalent values should be clearly stated.</li> </ul>	<ul style="list-style-type: none"> <li>Exploration Results have been reported by using the weighted average of each sample result by its corresponding interval length, as is industry standard practice.</li> <li>Grades &gt;0.3% Ni are used to identify nickel sulphide mineralisation in fresh rock samples.</li> <li>Top-cuts were deemed not applicable considering the style of Ni mineralisation</li> <li>Metal equivalent values have not been used.</li> </ul>
<b>Relationship between mineralisation widths and intercept lengths</b>	<ul style="list-style-type: none"> <li>These relationships are particularly important in the reporting of Exploration Results.</li> <li>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</li> <li>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. ‘down hole length, true width not known’).</li> </ul>	<ul style="list-style-type: none"> <li>Most drill holes are orthogonal to the orientation of stratigraphy and mineralisation.</li> </ul>
<b>Diagrams</b>	<ul style="list-style-type: none"> <li>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being</li> </ul>	<ul style="list-style-type: none"> <li>Relevant diagrams have been included within the announcement.</li> </ul>

For personal use only



CRITERIA	EXPLANATION	COMMENTARY
	reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.	
<b>Balanced reporting</b>	<ul style="list-style-type: none"> <li>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</li> </ul>	<ul style="list-style-type: none"> <li>All results related to relevant mineralisation at Saints have been previously reported</li> </ul>
<b>Other substantive exploration data</b>	<ul style="list-style-type: none"> <li>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</li> </ul>	<ul style="list-style-type: none"> <li>No other substantive data exists.</li> </ul>
<b>Further work</b>	<ul style="list-style-type: none"> <li>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).</li> <li>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</li> </ul>	<ul style="list-style-type: none"> <li>Once the drill program is complete and assay results received and reviewed, the results will be used to remodel the Saints nickel sulphide resource, largely into Indicated category. If it is determined that additional drilling is required, the Company will announce such plans in due course.</li> <li>Refer to diagrams in the main body of text.</li> </ul>

For personal use only