



ASX ANNOUNCEMENT  
21 November 2022

## OUTSTANDING HIGH GRADE COPPER MINERALISATION AT CHATSWORTH PROSPECT, TOLLU COPPER PROJECT

### HIGHLIGHTS

- Four (4) reverse circulation (RC) drill holes, TLC188, TLC189, TLC190 and TLC192, for a total of 756m were drilled at the end of 2021 at the Chatsworth Prospect (**Chatsworth**) at the Tollu Copper Vein deposit (**Tollu**) to test for continuity of volume between and beyond historical drilling.
- Geochemical assays have confirmed previously reported hand-held portable XRF analyses that showed these drill holes intersected thick high grade copper mineralisation between and beyond the limits of the relative historical drilling; the significant intersections include:
  - **10m at 2.51% Cu** from 174m downhole (TLC188) including:
    - **3m at 4.71% Cu** from 175m downhole;
  - **26m at 1.46% Cu** from 61m downhole (TLC189) including:
    - **1m at 5.1% Cu** from 84m downhole;
  - **16m at 2.88% Cu** from 74m downhole (TLC190) including:
    - **9m at 4.6% Cu** from 76m downhole, which includes
    - **2m at 7.62% Cu** from 76m downhole;
  - **22m at 1.26% Cu** from 104m downhole (TLC190) including:
    - **3m at 3.67% Cu** from 122m downhole; and
  - **25m at 1.10% Cu** from 53m downhole (TLC192) including:
    - **7m at 2.64% Cu** from 60m downhole.
- Drillholes TLC188 and TLC189 have extended the vertical continuity of the copper mineralisation in some of the historical drillholes to double that previous with at least some 100m of vertical extent and open at depth and towards the surface.
- The shallow extension of mineralisation by TLC192 extends the high grade mineralisation in this location to some 120m vertically and is open towards the surface.
- The success of the limited RC drilling at Chatsworth suggests that there may be opportunities in the Tollu resource<sup>1</sup> yet to be realised.
- Assay results from the Company's most recent drilling campaign completed in September 2022 remain pending.
- The Tollu Cu Vein deposit is 40km east of the Nebo-Babel Ni-Cu-PGE deposit (Figure 1). The West Musgrave Project, which includes the Tollu Cu Vein deposit, has the ideal geological and structural setting for large magmatic Ni-Cu sulphide deposits.



Redstone Resources Limited (ASX Code: **RDS**) ('Redstone' or the 'Company') is pleased to announce that geochemical assays have confirmed the previously reported hh-pXRF analyses (refer to ASX announcement of 23 November 2021) and show that the reverse circulation (**RC**) drilling completed at the end of 2021 has successfully proved that thick high-grade lenses of copper mineralisation intersected in historical drilling at the Chatsworth Prospect (**Chatsworth**), Tollar, have significant volume vertically and extend to shallower depths. Chatsworth is part of the Tollar Copper Vein deposit on the Company's 100% owned West Musgrave Project (the **Project**) in Western Australia.

The West Musgrave Project, which includes the Tollar Cu Vein deposit, is located 40 kilometres east of the world-class Nebo- Babel nickel-copper-PGE sulphide deposit now owned by OZ Minerals and has the ideal geological and structural setting for large magmatic Ni-Cu sulphide deposits.



Figure 1 – Location of the West Musgrave Project in relation to the Nebo-Babel Ni-Cu-PGE deposit.

### TOLLU COPPER VEIN DEPOSIT - CHATSWORTH PROSPECT

At the end of 2021 four reverse circulation (RC) drill holes, TLC188, TLC189, TLC190 and TLC192, for a total of 756m were drilled at the Chatsworth Prospect, Tollar. The aim of the drilling was to test for continuity of mineralisation vertically through the hosting sub-vertical vein system, and in doing so, test if the thick high grade copper mineralisation previously intersected in early drilling held volume between and beyond the historical drill holes, particularly at shallower depths than previously intersected.


Preliminary results of the drilling using hh-pXRF analyses were announced in the ASX announcement of 23 November 2021. Geochemical assays have successfully confirmed these preliminary results, with generally higher Cu grades than the hh-pXRF analyses but with slightly varying thicknesses.

As shown in **Figure 2**, drill holes TLC188 and TLC189, targeted approximately 15-20m vertically above a high grade copper intersection in historical drill hole TLC033, drilled in 2010 and 25-30m vertically below another high grade intersection in historical drill hole TLC034, also drilled in 2010 (refer ASX Announcement 21 February 2011 for further information on the historical drilling referenced). The historical drill holes suggest the mineralisation extends vertically between them but the vertical distance between the intersections is some 35m, a considerable distance for vein hosted mineralisation. The geochemical assays from TLC188 and TLC189 have confirmed that the thick high grade copper mineralisation continues vertically, being maintained




in the deeper intersection with **10m at 2.51% Cu from 174m downhole, including 3m at 4.71% Cu from 175m downhole (in TLC188)** and swelling in the shallower intersection with **26m at 1.46% copper from only 61m downhole, inclusive of 1m at 5.1% Cu from 67m downhole (in TLC189).**

**Figure 2** shows that TLC188 and TLC189 have extended the vertical continuity of the copper mineralisation to double previous with at least some 100m of vertical extent, seemingly continuous and still open at depth and towards the surface. What previously seemed a contraction of mineralisation towards the surface in TLC033, is most likely a 'pinch' in a pinch and swell morphology.



**Figure 2 – E-W Cross-section of recent RC drill holes TLC188 and TLC189 along with the historical drilling at Chatsworth, Tollar, looking north. Grades on historical drill holes are both hh-pXRF and laboratory based geochemistry and they are labelled accordingly. See text for further details.**

As shown in **Figure 3** drill hole TLC192, positioned some 90m to the south of TLC188 and TLC189 above, has successfully extended the high grade copper mineralisation intersected in historical drill holes TLC024, TLC031 and TLC030 vertically towards the surface. Geochemical assays confirm the intersection of copper mineralisation in **TLC192 is 25m thick grading 1.1% Cu from 53m downhole, which includes 7m at 2.64% Cu from 60m downhole.** The shallow extension of mineralisation by TLC192 extends the high grade mineralisation in this location to some 120m vertically and is open towards the surface (see **Figure 3**).




**Figure 3 – E-W Cross-section of recent RC drill hole TLC192 along with the historical drilling at Chatsworth, Tollar, looking north. Grades on historical drill holes are both hh-pXRF and laboratory based geochemistry and they are labelled accordingly. See text for further details.**

**Figure 4** shows that geochemical assays have also confirmed the two thick high grade copper mineralisation intersections in TLC190 previously suggested by hh-pXRF analyses at the time of drilling (refer to ASX announcement of 23 November 2021). Geochemistry confirms TLC190 intersected **16m at 2.88% Cu from 74m downhole, which included 9m at 4.6% Cu from 76m downhole and 2m at 7.62% from 76m downhole.** Then a little deeper, TLC190 also intersected **22m at 1.26% Cu from 104m downhole, which included 3m at 3.67% Cu from 122m downhole.**





TLC190 was located some 40m to the north of TLC192 and 50m to the south of TLC188 and TLC189. It was aimed at testing for an extension of mineralisation in historical drill hole TLC035 because the historical drilling (TLC032) was prematurely terminated before testing the position. **Figure 4** shows that TLC190 did not intersect the thick high grade mineralisation intersected in historical drill hole TLC135 but rather that it is more likely related to the mineralisation intersected further up-hole in TLC190 in a pinch and swell or lensing morphology.



The 2021 RC drilling has shown that whilst there is some complexity in the mineralisation at Chatsworth, as may be expected in a vein hosted system, the thick high-grade copper mineralisation intersected in the drilling holds volume between historical drill holes and extends beyond that which has been intersected by drilling to date.



The drilling has also highlighted that there may be opportunities in the Tollu resource<sup>1</sup> not yet realised and which may need to be investigated.

*This Announcement has been approved for release by the Board of Redstone Resources Limited.*

For further information please contact:

Richard Homsany  
Chairman  
Redstone Resources Limited  
+61 8 9328 2552  
[contact@redstone.com.au](mailto:contact@redstone.com.au)

Miranda Conti  
Company Secretary  
Redstone Resources Limited  
+61 8 9328 2552  
[contact@redstone.com.au](mailto:contact@redstone.com.au)

1. Initial JORC 2012 resource of 3.8 million tonnes at 1% Cu, containing 38,000 tonnes of copper at the Tollu Copper Vein Project, West Musgrave (ASX Announcement 15 July 2016).

#### REDSTONE RESOURCES

Redstone Resources Limited (ASX: RDS) is a base and precious metals developer exploring the 100% owned prospective West Musgrave Project, which includes the Tollu Copper deposit, in Western Australia. The West Musgrave Project is located between OZ Minerals' Nebo Babel prospect and Nico Resources' Wingellina Ni-Co project. Redstone is also evaluating the HanTails Gold Project at Kalgoorlie, Western Australia for potential development in the future.

#### Competent Persons Statement

The information in this document that relates to Redstone exploration results from 2017 to date was authorised by Dr Greg Shirliff, who is employed as a Consultant to the company through Zephyr Professional Pty Ltd. Dr Shirliff is a Member of the Australian Institute of Mining and Metallurgy and has sufficient experience of relevance to the tasks with which he was employed to qualify as a Competent Person as defined in the 2012 Edition of the Joint Ore reserves Committee (JORC) Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Dr Shirliff consents to the inclusion in the report of matters based on information in the form and context in which it appears.

The information in this report that relates to Mineral Resource for Tollu, West Musgrave Project was authorised by Mr Darryl Mapleson, a Principal Geologist and full time employee of BM Geological Services, who were engaged as consultant geologists to Redstone Resources Limited. Mr Mapleson is a Fellow of the Australian Institute of Mining and Metallurgy. Mr Mapleson has sufficient experience which is relevant to the style of mineralisation and type of deposit under consideration to act as a competent person as defined in the 2012 Edition of the 'Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Mapleson consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

#### ASX Listing Rule Information

The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcements, and in the case of estimates of Mineral Resources, that all material assumptions and technical parameters underpinning the estimates in the original market announcements continue to apply and have not materially changed. The Company confirms that the form and context in which the competent persons findings have not been materially modified from the original announcement referred to in the release.



### Forward-Looking Statements

This document may include forward-looking statements. Forward-looking statements include, but are not limited to statements concerning Redstone Resources Limited's (**Redstone**) planned exploration program and other statements that are not historical facts. When used in this document, the words such as "could", "plan", "estimate", "expect", "intend", "may", "potential", "should", and similar expressions are forward-looking statements. Although Redstone believes that its expectations reflected in these forward-looking statements are reasonable, such statements involve risks and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements.

### Appendix 1: Table of significant intervals discussed in this ASX announcement

Hole ID	From Depth (m)	To Depth (m)	Interval thickness (downhole m)	Average Grade %Cu	Cut-off %Cu	Dilution (m)
TLC188	31	47	16	0.21	0.05	1
TLC188	174	184	10	2.51	0.1	None
TLC188	175	178	3	4.71	3	None
TLC189	61	87	26	1.46	0.1	None
TLC189	84	85	1	5.1	5	None
TLC190	74	90	16	2.88	0.1	None
TLC190	76	85	9	4.61	1	None
TLC190	76	78	2	7.6	7	None
TLC190	104	126	22	1.26	0.1	3
TLC190	122	125	3	3.67	3	None
TLC190	154	155	1	1.66	1	None
TLC190	194	195	1	1.52	1	None
TLC192	53	78	25	1.1	0.05	4
TLC192	60	67	7	2.64	1	1
TLC192	92	97	5	0.32	0.05	None



## Appendix 2: Summary Table of drill hole details for drill holes referenced in this ASX announcement.

Hole ID	Easting	Northing	Method	Azimuth (degrees)	Azimuth Method	Dip (degrees)	Final Depth (m)
TLC188	438096	7108603	hhGPS	270	magnetic	-60	216
TLC189	438051	7108600	hhGPS	270	magnetic	-60	150
TLC190	438079	7108548	hhGPS	270	magnetic	-60	240
TLC192	438061	7108510	hhGPS	270	magnetic	-60	150
TLC020 (historical)	438109	7108556	RTK_GPS0.1	266	magnetic	-60	235
TLC021 (historical)	438132	7108555	RTK_GPS0.1	266	magnetic	-60	271
TLC024 (historical)	438120	7108515	RTK_GPS0.1	260	magnetic	-60	247
TLC025 (historical)	438150	7108518	RTK_GPS0.1	260	magnetic	-60	286
TLC030 (historical)	438070	7108510	RTK_GPS0.1	266	magnetic	-60	127
TLC031 (historical)	438090	7108510	RTK_GPS0.1	266	magnetic	-60	157
TLC032 (historical)	438075	7108550	RTK_GPS0.1	260	magnetic	-60	121
TLC033 (historical)	438060	7108600	RTK_GPS0.1	266	magnetic	-60	139
TLC034 (historical)	438080	7108600	RTK_GPS0.1	266	magnetic	-60	175
TLD035 (historical)	438090	7108470	RTK_GPS0.1	266	magnetic	-60	139

The collar location references are using the GDA94 Zone 52 datum system.

## Appendix 3:

# JORC Code, 2012 Edition – Table 1 report Tollu Project

## Section 1 Sampling Techniques & Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> <li><i>Nature &amp; quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc.). These examples should not be taken as limiting the broad meaning of sampling.</i></li> <li><i>Include reference to measures taken to ensure sample representivity &amp; the appropriate calibration of any measurement tools or systems used.</i></li> <li><i>Aspects of the determination of mineralisation that are Material to the Public Report.</i></li> </ul>	<ul style="list-style-type: none"> <li>Geochemical samples were taken from drill chips produced by a reverse circulation (RC) drill rig. Samples were split from the sample stream every metre as governed by metre marks on the drill string, by a cone splitter approximating between 7-13% of the full metre of sample. The dust box was used to control the flow of chips to the cone splitter.</li> <li>Duplicates were taken every metre from the alternate sample opening on the cone splitter. This gave flexibility to where field duplicates were introduced into the geochemical sampling stream to the lab and allowed for compositing at any depth or interval.</li> <li>On a regular basis both sample and duplicate were weighed with a simple hook based hand held scale to check for representivity of both the metre sampled and the duplicate. This weight was not recorded,</li> </ul>





Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> <li><i>In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.</i></li> </ul>	<ul style="list-style-type: none"> <li>rather used as an in-filed measure to alert drillers of issues with the cone splitter and drilling.</li> <li>Samples were collected in calico bags – each bag weighed approximately 1-3kg.</li> <li>In areas of targeted copper veins 1m RC chip samples were selected for laboratory analysis using a calibrated (using calibration discs and standardised compressed powders) hand-held XRF to discriminate anomalous copper (Cu) values. In some drill holes the entire holes was sampled; where so outside the mineralised zones were composited into 4m composites.</li> <li>A small (1-2 teaspoon sized) representative sample was kept of each metre for record purposes.</li> </ul>
Drilling techniques	<ul style="list-style-type: none"> <li><i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc.) &amp; details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented &amp; if so, by what method, etc.).</i></li> </ul>	<ul style="list-style-type: none"> <li>Reverse Circulation drilling was used to obtain 1m samples for the purpose of geological logging and geochemistry. Compositing was performed for some geochemical samples (see elsewhere in this table)</li> <li>RC sampling completed using a 5.5" diameter drill bit with a face sampling hammer. RC drilling rigs were equipped with a booster compressor.</li> </ul>
Drill sample recovery	<ul style="list-style-type: none"> <li><i>Method of recording &amp; assessing core &amp; chip sample recoveries &amp; results assessed.</i></li> <li><i>Measures taken to maximise sample recovery &amp; ensure representative nature of the samples.</i></li> <li><i>Whether a relationship exists between sample recovery &amp; grade &amp; whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i></li> </ul>	<ul style="list-style-type: none"> <li>RC Drillers were advised by geologists of the ground conditions expected for each hole and instructed to adopt an RC drilling strategy to maximize sample recovery, minimize contamination and maintain required spatial position.</li> <li>Sample recovery is approximated by assuming volume and rock densities for each metre of the drill hole and back referencing to this for individual metres coming from the cone splitter.</li> <li>Actual metal grades are not detailed in the ASX release. No correlation was observed between the amount of sample passing through the cone splitter and the geology or amount of sulphides observed.</li> </ul>
Logging	<ul style="list-style-type: none"> <li><i>Whether core &amp; chip samples have been geologically &amp; geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies &amp; metallurgical studies.</i></li> <li><i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.</i></li> <li><i>The total length &amp; percentage of the relevant intersections logged.</i></li> </ul>	<ul style="list-style-type: none"> <li>All drilling in this ASX release is by reverse circulation (RC). RC holes are geologically logged on a 1m interval basis. Where no sample is returned due to voids or lost sample, it is logged and recorded as such. The weathering profile is logged with no washing/sieving as well as washed/sieving to identify the transition into fresh rock and to identify unweathered quartz veins. In fresh rock all RC chips are logged by washing/sieving.</li> <li>Geological logging is qualitative and quantitative in nature.</li> <li>When visual estimations of sulphides have been presented then those estimations and the related geological interpretations have been based on examination of drill chips from a reverse circulation (RC) drill rig using a hand lens during drilling</li> </ul>



Criteria	JORC Code explanation	Commentary
		<p>operations. Chips are washed and sieved prior to logging.</p> <ul style="list-style-type: none"> <li>It should be noted that whilst % mineral proportions are based on standards as set out by JORC, they are estimation only and can be subjective to individual geologists to some degree.</li> <li>Details of the sulphides, type, nature of occurrence and general % proportion estimation are found within the text of the relevant ASX release.</li> </ul>
<ul style="list-style-type: none"> <li>Sub-sampling techniques &amp; sample preparation</li> </ul>	<ul style="list-style-type: none"> <li>If core, whether cut or sawn &amp; whether quarter, half or all core taken.</li> <li>If non-core, whether riffled, tube sampled, rotary split, etc. &amp; whether sampled wet or dry.</li> <li>For all sample types, the nature, quality &amp; appropriateness of the sample preparation technique.</li> <li>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</li> <li>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</li> <li>Whether sample sizes are appropriate to the grain size of the material being sampled.</li> </ul>	<ul style="list-style-type: none"> <li>Geochemical samples were taken from drill chips produced by a reverse circulation (RC) drill rig. All sampling techniques are described above. The nature and quality of the sampling technique was considered appropriate for the drilling technique applied and for the geochemical analysis sought.</li> <li>As described above a cone splitter was used to split samples from the RC sample stream. The cone splitter was levelled prior to drilling and this level was checked at regular intervals throughout the drilling of each drill hole to ensure representivity of sample.</li> <li>A field duplicate was taken for every metre sampled and both duplicate and original sample were weighed in the field using a hook based hand held scale to check for sample representivity.</li> <li>Filed duplicates were introduced into the geochemical sample submission at approximately 1 in 20 samples or 5% of the sample stream.</li> <li>Quartz sand blanks were introduced into the sample stream at 1 in 20 or 5%.</li> <li>The laboratory introduced copper standards for samples from the area of copper veins (TLC holes) at the rate of 1 in 20 or 5% or at smaller intervals.</li> <li>At the lab, samples were crushed to a nominal 2mm using a jaw crusher before being split using a rotary splitter into 400-700g samples for pulverising.</li> <li>Samples were pulverised to a nominal &gt;90% passing 75 micron for which a 100g sample was then selected for analysis. A spatula was used to sample from the pulverised sample for digestion.</li> <li>Bureau Veritas Laboratories in Perth use their own internal standards and blanks as well as flushing and cleaning methods accredited by international standards.</li> <li>Sample sizes and splits are considered appropriate to the grain size of the material being sampled as according to the Gi standard formulas.</li> </ul>
<p><i>Quality of assay data &amp; laboratory tests</i></p>	<ul style="list-style-type: none"> <li>The nature, quality &amp; appropriateness of the assaying &amp; laboratory procedures used &amp; whether the technique is considered partial or total.</li> </ul>	<ul style="list-style-type: none"> <li>Geochemical analyses performed consisted of a four acid digestion and/or peroxide fusion before Inductively Coupled Plasma Mass Spectrometer (ICPMS) or Inductively Coupled Plasma Atomic</li> </ul>



Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> <li>For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis including instrument make &amp; model, reading times, calibrations factors applied &amp; their derivation, etc.</li> <li>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) &amp; whether acceptable levels of accuracy (i.e. lack of bias) &amp; precision have been established.</li> </ul>	<p>Emission Spectrometer (ICPAES). This technique is considered a total analysis.</p> <ul style="list-style-type: none"> <li>As described above the HHXRF used to determine which samples were selected for analysis in the area of the copper veins was calibrated using calibration discs and standardised compressed powders at the start of every day and approximately every hour when analysing.</li> <li>All standards, blanks and filed duplicates are described above.</li> <li>The total error for copper (Cu) concentrations as measured by field duplicates for the samples represented by this ASX release passed the average mean difference of <math>\pm 20\%</math>. This is considered within expectations for geochemical sampling of RC drilling and shows no significant bias towards the positive or negative.</li> <li>In some instances, hand-held portable XRF method has been used to ascertain very approximate ranges of transition element concentrations and if so, this method has been explained in Appendix 1 if relevant to this ASX announcement.</li> </ul>
Verification of sampling & assaying	<ul style="list-style-type: none"> <li><i>The verification of significant intersections by either independent or alternative company personnel.</i></li> <li><i>The use of twinned holes.</i></li> <li><i>Documentation of primary data, data entry procedures, data verification, data storage (physical &amp; electronic) protocols.</i></li> <li><i>Discuss any adjustment to assay data.</i></li> </ul>	<ul style="list-style-type: none"> <li>Verification of significant intersections as shown by the results of geochemical analyses has been made via Zephyr Professional Pty Ltd employees and Redstone employees internally.</li> <li>There has been no dedicated twinned holes in this drilling program.</li> <li>All geological and geochemical data has been checked by Zephyr personnel. All geological and drilling data has been entered into a Redstone Access database. The geochemistry is currently being analysed but will also eventually be included in the Access database.</li> </ul>
Location of data points	<ul style="list-style-type: none"> <li><i>Accuracy &amp; quality of surveys used to locate drill holes (collar &amp; down-hole surveys), trenches, mine workings &amp; other locations used in Mineral Resource estimation.</i></li> <li><i>Specification of the grid system used.</i></li> <li><i>Quality &amp; adequacy of topographic control.</i></li> </ul>	<ul style="list-style-type: none"> <li>All drill hole collars referenced in this ASX release have been surveyed for easting, northing &amp; elevation using an RTK GPS system which was left to calibrate for 1.5 hours prior to recording survey data for each project location. The accuracy according to the GPS unit averaged approximately 10cm for all recordings (north, south and elevations). Data was collected in MGA94 Zone 52 &amp; AHD.</li> </ul>
Data spacing & distribution	<ul style="list-style-type: none"> <li><i>Data spacing for reporting of Exploration Results.</i></li> <li><i>Whether the data spacing &amp; distribution is sufficient to establish the degree of geological &amp; grade continuity appropriate for the Mineral</i></li> </ul>	<ul style="list-style-type: none"> <li>Drilling has been for exploration only, spacing varies between targets.</li> </ul>



Criteria	JORC Code explanation	Commentary
	<p><i>Resource &amp; Ore Reserve estimation procedure(s) &amp; classifications applied.</i></p> <ul style="list-style-type: none"> <li>• <i>Whether sample compositing has been applied.</i></li> </ul>	
<i>Orientation of data in relation to geological structure</i>	<ul style="list-style-type: none"> <li>• <i>Whether the orientation of sampling achieves unbiased sampling of possible structures &amp; the extent to which this is known, considering the deposit type.</i></li> <li>• <i>If the relationship between the drilling orientation &amp; the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed &amp; reported if material.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Drill angle details are given in the text of the release and in the table in the release. Orientation is according to the exploration target (see text of release for further details).</li> </ul>
<i>Sample security</i>	<ul style="list-style-type: none"> <li>• <i>The measures taken to ensure sample security.</i></li> </ul>	<ul style="list-style-type: none"> <li>• All geochemical samples were selected by geologists in the field and sent directly to the laboratory from the field in a single vehicle, packaged in bulk bags. Results of geochemical analysis were sent directly to the designated geologist entering into the central database and for analysis.</li> </ul>
<i>Audits or reviews</i>	<ul style="list-style-type: none"> <li>• <i>The results of any audits or reviews of sampling techniques &amp; data.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Not applicable</li> </ul>

## Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
<i>Mineral tenement &amp; land tenure status</i>	<ul style="list-style-type: none"> <li>• <i>Type, reference name/number, location &amp; ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park &amp; environmental settings.</i></li> <li>• <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></li> </ul>	<ul style="list-style-type: none"> <li>• The West Musgrave Project is located within E69/2450 and E69/3456 (Western Australia). These exploration license are held by Redstone Resources. The Tollu Cu Vein deposit is located within E69/2450.</li> <li>• The tenements are in good standing &amp; no known impediments exist.</li> </ul>
<i>Exploration done by other parties</i>	<ul style="list-style-type: none"> <li>• <i>Acknowledgment &amp; appraisal of exploration by other parties.</i></li> </ul>	<ul style="list-style-type: none"> <li>• There has been limited recent exploration undertaken by other parties at the West Musgrave Project, including the Tollu Cu Vein deposit.</li> </ul>
<i>Geology</i>	<ul style="list-style-type: none"> <li>• <i>Deposit type, geological setting &amp; style of mineralisation.</i></li> </ul>	<ul style="list-style-type: none"> <li>• The genetic origin is currently under review and part of a research project.</li> </ul>
<i>Drill hole Information</i>	<ul style="list-style-type: none"> <li>• <i>A summary of all information material to the understanding of the exploration results including a</i></li> </ul>	<ul style="list-style-type: none"> <li>• See the table in the release.</li> </ul>



Criteria	JORC Code explanation	Commentary
	<p><i>tabulation of the following information for all Material drill holes:</i></p> <ul style="list-style-type: none"> <li>○ <i>Easting &amp; northing of the drill hole collar</i></li> <li>○ <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i></li> <li>○ <i>dip &amp; azimuth of the hole</i></li> <li>○ <i>down hole length &amp; interception depth</i></li> <li>○ <i>hole length.</i></li> <li>• <i>If the exclusion of this information is justified on the basis that the information is not Material &amp; this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></li> </ul>	
<i>Data aggregation methods</i>	<ul style="list-style-type: none"> <li>• <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) &amp; cut-off grades are usually Material &amp; should be stated.</i></li> <li>• <i>Where aggregate intercepts incorporate short lengths of high grade results &amp; longer lengths of low grade results, the procedure used for such aggregation should be stated &amp; some typical examples of such aggregations should be shown in detail.</i></li> <li>• <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Compositing has been described above. The technique for compositing used entailed the lab crushing every metre to a nominal 2mm crushed grain size before splitting off a 400-700g, sample using a rotary splitter, of each metre for compositing. The lab then proceeded to composite the 400-700g samples.</li> </ul>
<i>Relationship between mineralisation widths &amp; intercept lengths</i>	<ul style="list-style-type: none"> <li>• <i>These relationships are particularly important in the reporting of Exploration Results.</i></li> <li>• <i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i></li> <li>• <i>If it is not known &amp; only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</i></li> </ul>	<ul style="list-style-type: none"> <li>• No true widths have been stated in this ASX release, just downhole intercept lengths.</li> </ul>
<i>Diagrams</i>	<ul style="list-style-type: none"> <li>• <i>Appropriate maps &amp; sections (with scales) &amp; tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole</i></li> </ul>	<ul style="list-style-type: none"> <li>• See ASX release</li> </ul>





Criteria	JORC Code explanation	Commentary
	<i>collar locations &amp; appropriate sectional views.</i>	
<i>Balanced reporting</i>	<ul style="list-style-type: none"> <li><i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low &amp; high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i></li> </ul>	<ul style="list-style-type: none"> <li>Only observations are reported, see data details above for further information</li> </ul>
<i>Other substantive exploration data</i>	<ul style="list-style-type: none"> <li><i>Other exploration data, if meaningful &amp; material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size &amp; method of treatment; metallurgical test results; bulk density, groundwater, geotechnical &amp; rock characteristics; potential deleterious or contaminating substances.</i></li> </ul>	<ul style="list-style-type: none"> <li>No other exploration data collected is considered material to this announcement.</li> </ul>
<i>Further work</i>	<ul style="list-style-type: none"> <li><i>The nature &amp; scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).</i></li> <li><i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations &amp; future drilling areas, provided this information is not commercially sensitive.</i></li> </ul>	<ul style="list-style-type: none"> <li>The details of the nature of future work are currently being assessed.</li> </ul>