

ROX RESOURCES LIMITED

ASX: RXL

Rox Resources Limited (ASX: RXL) is an Australian listed company with advanced gold assets in Western Australia: the Youanmi Gold Project and the Mt Fisher Gold project.

DIRECTORS

Mr Stephen Dennis
Chairman

Mr Robert Ryan
Managing Director

Dr John Mair
Non-Executive Director

Shares on Issue	217.2m
Share Price	\$0.15
Market Cap.	\$32.6m
Cash	\$10.5m

(as at 31 Dec 22)

Level 2, 87 Colin Street,
West Perth WA 6005

+61 8 9226 0044

admin@roxresources.com.au

www.roxresources.com.au

Follow Rox:



Midway Emerging as a New High-Grade Gold Discovery

Highlights:

- **New drilling at the emerging Midway discovery hits thick high-grade intercepts including:**
 - **6.76m @ 15.40g/t Au from 169.13m**
 - **3.73m @ 10.25g/t Au from 405.80m**
 - **2.86m @ 22.03g/t Au from 356.39m**
- **The new drilling at Midway confirms the continuity of this developing high-grade discovery, located adjacent to the Youanmi mine**
- **Exploration and resource drilling at the Youanmi project is proceeding ahead of schedule with 6,434m completed of the planned 23,000m drilling program**

West Australian gold exploration and development company, Rox Resources Limited ("**Rox**" or "**the Company**") (ASX: RXL), in conjunction with its joint venture partner Venus Metals Corporation (ASX: VMC), is pleased to report initial drilling results from the substantial reverse circulation (RC) and diamond drilling (DD) programs at the Youanmi Gold Project (OYG JV).

Exploration drilling has initially targeted the exciting, high-grade '**Midway**' discovery made by the OYG JV in 2021 (ASX announcement 8 June 2022). This high-grade, multi-lode system is located just 300m from the hanging-wall of the Youanmi Main Lode and presents an excellent near mine exploration target which is open in all directions. The exceptional drilling results, coupled with the detailed structural information, will provide valuable information to expand the emerging discovery.

4,726 RC meters and 1,708 diamond meters have been completed to date from the planned 16,000 metre RC and 7,000 metre DD drill programs. Drilling is ongoing and is expected to be completed in April.

Management Comments

Rox Resources Managing Director, Mr Robert Ryan, said the Midway discovery has vast potential to grow with follow-up work underway:

“From the initial drilling campaign last year, excitement has been building for the latest drilling results at Midway and they have not disappointed, with thick, high-grade gold intercepts proving the exploration concept. Follow-up drilling is currently being planned and will commence in the coming weeks.

“The results from Midway to date have shown that this discovery has the potential to grow substantially in all directions in a corridor previously untested with drilling. The high-grade tenor of the results to date show Midway has the potential to be higher grade than the Youanmi main lode and has the potential to significantly contribute to the gold resource.

“2023 is evolving into an exciting year for the company as we continue our three pronged approach for building value for shareholders through adding ounces through exploration, increasing resource confidence through in-fill drilling and de-risking the project through feasibility work.”

Midway Exploration Drilling

Gold mineralisation at Midway is shear-zone hosted within highly altered tholeiitic and komatiitic basaltic rocks. The alteration assemblage consists of sericite, quartz, carbonate, and biotite. Gold occurs in association with pyrite and lesser arsenopyrite (Figure 1).




Figure 1: Core photos and sampling intervals of RXDD048 6.76m @ 15.40 g/t Au from 169.13m

The results to date define at least two gold lodes striking WNW and dipping towards the SW. Structural analysis of the mineralised zone (shear fabric and stretching mineral lineation) indicates that the lodes are dipping steeply towards the southwest and show a high-grade component plunging at 50 degrees to the WNW. The orientation of the new lodes is different to previously identified lodes at Youanmi which strike NW to NNW. This new orientation of mineralised structures is apparent in high resolution drone magnetic imagery and has generated several new exploration targets which will be tested by RC and DD drilling. So far the multi-lode structure has been intersected over approximately 100m strike and 300m down plunge.

Exceptional drill intersection results received from the first two of five planned drill holes at Midway:

- **2.86m @ 22.03 g/t Au** from 356.39m in RXDD047 and;
- **3.73m @ 10.25 g/t Au** from 405.80m in RXDD047
- **6.76m @ 15.40 g/t Au** from 169.13m in RXDD048

These results from the first two drill holes confirm the exciting discovery of the Midway Lode with exceptional gold grades. This potential linking cross structure is developing as a higher-grade lode as compared to the existing NW to NNW Youanmi lodes. The extent of this new mineralised structure is at its infancy with huge potential along strike, and at depth.




Figure 2: Midway Long Section

The Company looks forward to providing further drilling results from the current drill program in due course.

For personal use only




Figure 3: Plan view of proposed resource and exploration drilling at the Youanmi Gold Project



Authorised for release to the ASX by the Board of Rox Resources Limited.

*** ENDS ***

For more information:

Rob Ryan
Managing Director
Rox Resources Limited
Tel: +61 8 9226 0044
E: admin@roxresources.com.au

Matthew Hogan
Managing Director
Venus Metals Corporation Limited
Tel: +61 8 9321 7541
E: info@venusmetals.com.au

For personal use only

Table 1 – Collar Locations and Drilling Details

Hole ID	Prospect	Drill Type	East	North	RL	Depth	Dip	Azi	Comments
RXDD047	Midway	RC Pre-collar	679511.00	6833250.00	458.30	287.40	-61.49	25.22	Assays received
		Diamond Tail				493.00			Assays received
RXDD048	Midway	RC Pre-collar	679628.39	6833230.52	457.90	100.70	-61.99	31.83	Assays received
		Diamond Tail				362.00			Assays received
RXDD049	Link	RC	679122.27	6834414.10	461.70	342.00	-60.68	62.62	Assays pending
RXDD050	Link	RC Pre-collar	679069.89	6834467.27	461.07	240.00	-61.16	62.91	Assays pending
		Diamond Tail				414.80			Assays pending
RXDD051	Link	RC Pre-collar	679097.51	6834434.00	461.63	208.00	-69.87	61.32	Assays pending
		Diamond Tail				390.40			Assays pending
RXDD052	Link	RC Pre-collar	679101.96	6834406.74	461.64	280.00	-63.04	64.25	Assays pending
		Diamond Tail				410.90			Assays pending
RXDD053	Link	RC Pre-collar	679164.32	6834361.98	461.06	250.00	-59.91	64.26	Assays pending
		Diamond Tail				370.00			Assays pending
RXDD054	Link	RC Pre-collar	679111.09	6834457.00	461.21	210.00	-60.09	63.46	Assays pending
		Diamond Tail				336.10			Assays pending
RXDD056	Midway	RC Pre-collar	679577.79	6833278.73	458.07	208.00	-60.20	30.40	Assays pending
		Diamond Tail				322.80			Assays pending
RXDD057	Link	RC Pre-collar	679241.21	6834175.73	461.45	253.00	-70.82	62.82	Assays pending
		Diamond Tail				410.10			Assays pending
RXDD058	Link	RC Pre-collar	679133.87	6834314.94	461.41	210.00	-71.80	62.50	Assays pending
		Diamond Tail				445.00			Assays pending
RXDD059	Link	RC Pre-collar	679102.44	6834564.12	463.61	233.00	-60.64	63.13	Assays pending
		Diamond Tail				N/A			Yet to be drilled
RXDD061	Link	RC Pre-collar	679199.84	6834117.24	460.39	240.00	-70.83	65.25	Assays pending
		Diamond Tail				N/A			Yet to be drilled
RXDD062	Link	RC Pre-collar	679169.66	6834257.24	460.69	133.00	-63.56	60.73	Assays pending
		Diamond Tail				N/A			Yet to be drilled
RXRC454	Kathleen	RC	679062.90	6834893.18	465.24	180.00	-59.15	54.83	Assays pending
RXRC455	Kathleen	RC	679091.19	6834808.44	464.70	200.00	-60.30	54.60	Assays pending
RXRC456	Kathleen	RC	679044.16	6834784.73	465.39	220.00	-60.10	54.90	Assays pending
RXRC457	Link	RC	679158.10	6834480.16	462.17	300.00	-60.30	64.40	Assays pending
RXRC458	Youanmi Sth	RC	680469.02	6833112.86	454.15	300.00	-59.60	315.80	Assays pending
YMDD003_OY	Bunker	DD	679454.00	6833045.00	458.52	330.40	-50.00	90.00	Assays pending

*Grid MGA94_Zone50S with RL in Australian Height Datum.

RC = Reverse Circulation, DD = Diamond & RCD = RC pre-collar with diamond tail.

For personal use only

Table 2 – Significant Intersections

Hole ID	Prospect	Drill type	From	to	Interval	Au g/t	Au g.m
RXDD047	Midway	DD	356.39	359.25	2.86	22.03	62.99
RXDD047	Midway	DD	364	364.8	0.80	6.76	5.41
RXDD047	Midway	DD	405.8	409.53	3.73	10.25	38.25
RXDD047	Midway	DD	453.81	454.32	0.51	4.04	2.06
RXDD048	Midway	DD	155.88	157	1.12	2.30	2.57
RXDD048	Midway	DD	169.13	175.89	6.76	15.40	104.10

Minimum significant intercept is 1m @ 0.5g/t Au, maximum 1m contiguous internal dilution.

NSI = No significant Intercept

* Indicates a RC pre-collar result, with a diamond tail to follow intersecting the target lode.

** Indicates preliminary 4 meter composite samples. Final 1 meter samples to follow.

For personal use only

Competent Person Statement

Exploration Results

The information in this report that relates to Data and Exploration Results is based on information compiled and reviewed by Mr Travis Craig a Competent Person who is a Member of the Australasian Institute of Geologists (AIG) and Exploration Manager at Rox Resources. Mr Craig has sufficient experience relevant to the style of mineralisation and type of deposit under consideration and to the activity which he has undertaken to qualify as a Competent Person as defined in the 2012 Edition of the 'Australasian Code for the Reporting of Exploration Results, Mineral Resources and Ore Reserves'. Mr Craig consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

Where reference is made to previous releases of exploration results in this announcement, the Company confirms that it is not aware of any new information or data that materially affects the information included in those announcements and all material assumptions and technical parameters underpinning the exploration results included in those announcements continue to apply and have not materially changed.

The information in this report that relates to previous Exploration Results was prepared and first disclosed under the JORC Code 2012 and has been properly and extensively cross-referenced in the text to the date of the original announcement to the ASX.

Resource Statements

The Statement of Estimates of Mineral Resources for the Youanmi Near Surface Resource was reported by Rox in accordance with ASX Listing Rule 5.8 in the announcement released to the ASX on 20th April 2022. Rox confirms it is not aware of any new information or data that materially affects the information included in the previous announcements and that all material assumptions and technical parameters underpinning the estimates in the previous announcements continue to apply and have not materially changed.

The Statement of Estimates of Mineral Resources for the Youanmi Underground Resource was reported by Rox in accordance with ASX Listing Rule 5.8 in the announcement released to the ASX on 20th January 2022. Rox confirms it is not aware of any new information or data that materially affects the information included in the previous announcements and that all material assumptions and technical parameters underpinning the estimates in the previous announcements continue to apply and have not materially changed.

The Statement of Estimates of Mineral Resources that relates to gold Mineral Resources for the Mt Fisher project was reported by Rox in accordance with ASX Listing Rule 5.8 in the announcement released to the ASX on 11th July 2018. Rox confirms it is not aware of any new information or data that materially affects the information included in the previous announcements and that all material assumptions and technical parameters underpinning the estimates in the previous announcements continue to apply and have not materially changed.

Forward-Looking Statements

This document may include forward-looking statements. Forward-looking statements include, but are not limited to, statements concerning Rox Resources Limited planned exploration program(s) and other statements that are not historical facts. When used in this document, the words such as "could," "plan," "estimate," "expect," "intend," "may," "potential," "should," and similar expressions are forward looking statements.

About Rox Resources

Rox Resources (ASX:RXL) is a West Australian focused gold exploration and development company. It is 70 per cent owner and operator of the historic Youanmi Gold Project near Mt Magnet, approximately 480 kilometres northeast of Perth, and wholly-owns the Mt Fisher Gold project approximately 140 kilometres southeast of Wiluna. Youanmi has a Total Mineral Resource of 3,199 koz of contained gold, with potential for further expansion with the integration of existing prospects into the Resource and further drilling. Youanmi was a high-grade gold mine and produced 667,000oz of gold (at 5.47 g/t Au) before it closed in 1997. Youanmi is classified as a disturbed site and is on existing mining leases which has significant existing infrastructure to support a return to mining operations.

JORC Table 1 - Section 1 Data and Sampling Techniques

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i>	<p>RC hole diameter was 5.5" (140 mm) reverse circulation percussion (RC). Sampling of RC holes was undertaken by collecting 1m cone split samples at intervals.</p> <p>Diamond drill hole core size is NQ2 size diameter through the mineralisation. Sampling of diamond holes was by cut half core as described further below.</p> <p>Drill holes were generally angled at -60° towards grid northeast (but see Table for individual hole dips and azimuths) to intersect geology as close to perpendicular as possible.</p>
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used</i>	Drillhole locations were picked up by differential GPS. Logging of drill samples included lithology, weathering, texture, moisture and contamination (as applicable). Sampling protocols and QAQC are as per industry best practice procedures.
	<i>Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information</i>	<p>RC drillholes were sampled on 1m intervals using a cone splitter. A nominal 3-4kg sample is taken and analysed for gold by Fire Assay 50g (FA50).</p> <p>Diamond core is dominantly NQ2 size, sampled on geological intervals, with a minimum of 0.3 m up to a maximum of 1.2 m. The diamond core was cut in half, with one half sent to the lab and one half retained. The sample was analysed for gold by Fire Assay 50g (FA50).</p>
Drilling techniques	<i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i>	Drilling technique was Reverse Circulation (RC) and diamond core (DD). The RC hole diameter was 140mm face sampling hammer.
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed</i>	RC drill recoveries were high (>90%).
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples</i>	Samples were visually checked for recovery, moisture and contamination and notes made in the logs.
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	There is no observable relationship between recovery and grade, and therefore no sample bias.

For personal use only

Criteria	JORC Code explanation	Commentary
Logging		Detailed geological logs have been carried out on all RC, but no geotechnical data have been recorded (or is possible to be recorded due to the nature of the sample). Detailed geological and geotechnical logs were carried out on all diamond drill holes for recovery, RQD, structures etc. which included structure type, dip, dip direction, alpha angle, beta angle, texture, shape, roughness, fill material, and this data is stored in the database. The geological data would be suitable for inclusion in a Mineral Resource estimate.
	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	Logging of diamond core and RC chips recorded lithology, mineralogy, mineralisation, weathering, colour, and other sample features. RC chips are stored in plastic RC chip trays.
	<i>The total length and percentage of the relevant intersections logged</i>	All holes were logged in full.
Sub-sampling techniques and sample preparation		Drill core was cut in half on site using a core saw. All samples were collected from the same side of the core, preserving the orientation mark in the kept core half.
	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	RC samples were collected on the drill rig using a cone splitter. If any mineralised samples were collected wet these were noted in the drill logs and database.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	The sample preparation followed industry best practice. Fire Assay samples were dried, coarse crushing to ~10mm, followed by pulverisation of the entire sample in an LM5 or equivalent pulverising mill to a grind size of 85% passing 75 micron.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Field QC procedures involve the use of Certified Reference Materials (CRM's) as assay standards, along with duplicates and blank samples. The insertion rate of these was approximately 1:20.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	For RC drilling field duplicates were taken on a routine basis at an approximate 1:20 ratio using the same sampling techniques (i.e. cone splitter) and inserted into the sample run. No diamond core field duplicates were taken.
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	The sample sizes are considered more than adequate to ensure that there are no particle size effects relating to the grain size of the mineralisation which lies in the percentage range.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	The analytical technique involved Fire Assay 50g.

Criteria	JORC Code explanation	Commentary
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	No geophysical or portable analysis tools were used to determine assay values stored in the database.
	<i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (i.e. lack of bias) and precision have been established.</i>	Internal laboratory control procedures involve duplicate assaying of randomly selected assay pulps as well as internal laboratory standards. All of these data are reported to the Company and analysed for consistency and any discrepancies.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Senior personnel from the Company have visually inspected mineralisation within significant intersections.
	<i>The use of twinned holes.</i>	Two twin RC holes have been completed at the Grace Prospect and confirm reliability of previous results.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Primary data was collected using a standard set of Excel templates on Toughbook laptop computers in the field. These data are transferred to Geobase Pty Ltd for data verification and loading into the database.
	<i>Discuss any adjustment to assay data.</i>	No adjustments or calibrations have been made to any assay data.
Location of data points	<i>Accuracy and quality of surveys used to locate drillholes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Drill hole locations have been established using a differential GPS with an accuracy of +/- 0.3m.
	<i>Specification of the grid system used.</i>	The grid system is MGA_GDA94, zone 50 for easting, northing and RL.
	<i>Quality and adequacy of topographic control.</i>	The topography of the mined open pits is well defined by historic monthly survey pickups
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	RC and diamond drill hole spacing varies 40-200 metres between drill sections, with some areas at 40 metre drill section spacing. Down dip step-out distance varies 20-100 metres.
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	Data spacing and distribution are sufficient to establish the degree of geological and grade continuity appropriate for JORC(2012) classifications applied.
	<i>Whether sample compositing has been applied.</i>	No sample compositing has occurred for diamond core drilling. Sample intervals are based on geological boundaries with even one metre samples between. For RC samples, 1m samples through target zones were sent to the laboratory for analysis. The remainder of the hole was sampled using 4m composite samples. For 4m composite samples >0.2g/t Au, 1m samples were collected and sent to the laboratory for analysis.

For personal use only

Criteria	JORC Code explanation	Commentary
Orientation of data in relation to geological structure	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	The mineralisation strikes generally WNW and dips to the SW at approximately -60 degrees. The drill orientation was 065 and -60 dip. Drilling is believed to be generally perpendicular to strike.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	No sampling bias is believed to have been introduced.
Sample security	<i>The measures taken to ensure sample security.</i>	Sample security is managed by the Company. After preparation in the field samples are packed into polyweave bags and despatched to the laboratory. For a large number of samples these bags were transported by the Company directly to the assay laboratory. In some cases the sample were delivered by a transport contractor the assay laboratory. The assay laboratory audits the samples on arrival and reports any discrepancies back to the Company. No such discrepancies occurred.
Audits or reviews	<i>The results of any audits or reviews of sampling techniques and data.</i>	No audits have yet been completed.

For personal use only

JORC Table 1 - Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	<p><i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></p> <hr/> <p><i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></p>	<p>Rox Resources Ltd is in a Joint Venture Agreement with Venus Metals Corporation Ltd under which it has a 70% interest in the Youanmi Gold Mine Joint Venture (OYG Joint Venture). Tenements in the JV consist of the following mining leases: M 57s /10, 51,76,97,109, 135, 160A, 164, 165, 166 and 167.</p> <hr/> <p>The tenement is in good standing and no known impediments exist.</p>
Exploration done by other parties	<p><i>Acknowledgment and appraisal of exploration by other parties.</i></p>	<p>Significant previous exploration has been carried out throughout the project by various companies, including AC/RAB, RC drilling and diamond drilling 1971-1973 WMC: RAB, RC and surface diamond drilling 1976 Newmont: 10 surface diamond drillholes (predominantly targeting base metals). 1980-1986 BHP: RAB, RC and surface diamond drilling (predominantly targeting base metals). 1986-1993 Eastmet: RAB, RC and surface diamond drilling. 1993-1997 Goldmines of Australia: RAB, RC and surface diamond drilling. Underground mining and associated underground diamond drilling. 2000-2003 Aquila Resources Ltd: Shallow RAB and RC drilling 2004-2005 Goldcrest Resources Ltd: Shallow RAB and RC drilling; data validation. 2007- 2013 Apex Minerals NL: 9 diamond holes targeting extensions to the Youanmi deeps resource.</p>

For personal use only

For personal use only

Criteria	JORC Code explanation	Commentary
<p>Geology</p> <p><i>Deposit type, geological setting and style of mineralisation.</i></p>		<p>The Youanmi Project straddles a 40km strike length of the Youanmi Greenstone Belt, lying within the Southern Cross Province of the Archaean Yilgarn Craton in Western Australia. The greenstone belt is approximately 80km long and 25km wide, and incorporates an arcuate, north-trending major crustal structure termed the Youanmi Fault Zone. This structure separates two discordant greenstone terrains, with the stratigraphy to the west characterised by a series of weakly deformed, layered mafic complexes (Windimurra, Black Range, Youanmi and Barrambie) enveloped by strongly deformed, north-northeast trending greenstones.</p> <p>Gold mineralisation is developed semi-continuously in shear zones over a strike length of 2,300m along the western margin of the Youanmi granite.</p> <p>Gold is intimately associated with sulphide minerals and silicates in zones of strong hydrothermal alteration and structural deformation. Typical Youanmi lode material consists of a sericite-carbonate- quartz- pyrite- arsenopyrite schist or mylonite which frequently contains significant concentrations of gold, commonly as fine, free gold particles in the silicates, occluded in sulphide minerals and in solid solution in arsenopyrite. The lodes contain between 10% and 25% sulphide, the principal species being pyrite (10% to 20%) and arsenopyrite (1% to 5%).</p> <p>There are a series of major fault systems cutting through the Youanmi trend mineralisation that have generated some significant off-sets.</p> <p>The Youanmi Deeps project area is subdivided into three main areas or fault blocks by cross-cutting steep south-east trending faults; and these are named Pollard, Main, and Hill End from south to north respectively.</p> <p>Granite hosted gold mineralisation occurs at several sites, most notably Grace and the Plant Zone Prospects. Gold mineralization occurs as free particles within quartz-sericite altered granite shear zones.</p> <p>The Commonwealth-Connemarra mineralised trend is centred 4km northwest of the Youanmi plant. The geology comprises a sequence of folded mafic and felsic volcanic rocks intercalated with BIF and intruded by granite along the eastern margin. Gold mineralisation is developed over a 600m strike length, associated with a north trending and steeply west dipping shear zone that traverses the northwest trending succession.</p>

Criteria	JORC Code explanation	Commentary
Drill hole Information	<p>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</p> <ul style="list-style-type: none"> • easting and northing of the drill hole collar • elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar • dip and azimuth of the hole • down hole length and interception depth • hole length. 	Refer to drill results Table/s and the Notes attached thereto.
Data aggregation methods	<p>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</p> <p>Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</p> <p>The assumptions used for any reporting of metal equivalent values should be clearly stated.</p>	<p>All reported assay intervals have been length weighted. No top cuts have been applied. A lower cut-off of 0.5g/t Au was applied for RC and diamond core.</p> <p>Mineralisation over 0.5g/t Au has been included in aggregation of intervals for RC and diamond core.</p> <p>No metal equivalent values have been used or reported.</p>
Relationship between mineralisation widths and intercept lengths	<p>These relationships are particularly important in the reporting of Exploration Results.</p> <p>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</p> <p>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</p>	The mineralisation strikes generally WNW and dips to the west at approximately -60 degrees. Drill orientations are usually 060 degrees and -60 dip. Drilling is believed to be generally perpendicular to strike. Given the angle of the drill holes and the interpreted dip of the host rocks and mineralisation (see Figures in the text), reported intercepts approximate true width.
Diagrams	<p>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</p>	Refer to Figures and Table in the text.
Balanced reporting	<p>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</p>	Representative reporting of both low and high grades and widths is practiced.
Other substantive exploration data	<p>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</p>	All meaningful and material information has been included in the body of the announcement.

For personal use only

Criteria	JORC Code explanation	Commentary
Further work	<p><i>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).</i></p> <p><i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive</i></p>	<p>Further work (RC and diamond drilling) is justified to locate extensions to mineralisation both at depth and along strike.</p>

For personal use only