

22 May 2023

ASX: AHK

Corporate Directory

Directors

Executive Chairman

Roger Jackson

Executive Director

Ben Emery

Non-Executive Director

Ian Mitchell

Projects

- Gunnawarra Nickel-Cobalt
- Mt Jesse Iron – Copper
- Sandy Mitchell – Rare Earths and HM
- Pluton Gold



Contact Details

T: +61 82 80660601

E: info@arkmines.com.au

W: www.arkmines.com.au

Suite 9.04a, Level 9, MLC Centre,
19-29 Martin Place, SYDNEY
NSW 2000

DRILLING UNDERWAY AT SANDY MITCHELL RARE EARTHS PROJECT

HIGHLIGHTS

- Drilling has formally commenced at ‘Sandy Mitchell’, Ark Mines’ fully owned advanced Rare Earths project in North Queensland
- Phase 1 drill program has commenced on schedule, and will be carried out by specialist Queensland-based contractor Saxon Drilling
- Unique features of the deposit, with Rare Earths hosted in sands, will also facilitate on-site metallurgical test work and gravity separation, allowing the Company to further fast-track exploration efforts
- Assay results and ongoing test work will form the basis of a Maiden Mineral Resource Estimate (MRE) under the 2012 JORC code

Ark Mines Ltd (ASX: AHK, “Ark” or the “Company”) is pleased to confirm that Air Core drilling has commenced at ‘Sandy Mitchell’, the Company’s fully-owned advanced Rare Earths and Heavy Minerals project contained in sands that hosts both light and heavy rare earths and heavy minerals.

The Phase 1 drill program will comprise infill and extension drilling of historic auger drill-holes in a 120m-by-120m grid, spanning an area of 2.0 km², along with 30 reconnaissance holes testing the broader anomaly (*refer ASX Announcement 27 April 2023*). However, it may be varied depending on geological feedback.

Confirmation of the drill start date is in alignment with the group’s previously announced timeline, after it signed an agreement with Queensland-based specialist contractor Saxon Drilling in April (*refer ASX Announcement 3 April 2023*).

The infill and extension drilling of historic auger drill holes has been designed to maximise mineralisation depths, and data obtained from the program will form the basis of a maiden JORC-2012 compliant Mineral Resource Estimate (MRE).

The commencement of drilling follows an extensive planning and review process, which highlighted the scale of anomalous REE and Heavy Metals at the Sandy Mitchell project. The Company looks forward to updating investors with initial drill results in the coming weeks and months as exploration gets underway.

Executive Chairman Roger Jackson said: “Confirmation that the Phase 1 drill program is underway marks another exciting step forward for Ark and our investor base. Since acquiring the Sandy Mitchell rare earths project, management have executed well on a targeted exploration strategy which included extensive drill planning, the commissioning of highly-rated contractors and ongoing test work of REE sands on-site. We look forward to reporting first assays from this Phase 1 drill program, which will also form the basis for further metallurgical test work ahead of an updated MRE which is scheduled for Q4 CY2020.”

For personal use only



Image 1: Air Core Drill rig in Action, Directors overseeing the commencement of the program




Figure 2 Ark Directors accessing drill samples with the Scintillometer



Figure 3 Ark Geologists logging and accessing samples from the air core rig.

Figure 4. Proposed drill program for Sandy Mitchell. Focussed area in red:



For personal use only




Figure 2 Location of historical Pan concentrate samples

For further information please contact:

Roger Jackson
Executive Chairman
info@arkmines.com.au

Ben Emery
Executive Director
info@arkmines.com.au

Released through: Ben Jarvis, Six Degrees Investor Relations, +61 413 150 448

Or visit our website and social media www.arkmines.com | www.twitter.com/arkmineslimited
www.linkedin.com/company/ark-mines-limited/

About Ark Mines Limited

Ark Mines is an ASX listed Australian mineral exploration company focused on developing its 100% owned projects located in the prolific Mt Garnet and Greenvale mineral fields of Northern Queensland. The Company's exploration portfolio consists of three high quality projects covering 200km² of tenure that are prospective for copper, iron ore, nickel-cobalt and porphyry gold:

Gunnawarra Nickel-Cobalt Project

- Comprised of 11 sub-blocks covering 36km²
- Borders Australian Mines Limited Sconi project - most advanced Co-Ni-Sc project in Australia
- Potential synergies with local processing facilities with export DSO Nickel/Cobalt partnership options

Mt Jesse Copper-Iron Project

- Project covers a tenure area of 12.4km² located ~25km west of Mt Garnet
- Centered on a copper rich magnetite skarn associated with porphyry style mineralization
- Three exposed historic iron formations
- Potential for near term production via toll treat and potential to direct ship

Pluton Porphyry Gold Project

- Located ~90km SW of Cairns near Mareeba, QLD covering 18km²
- Prospective for gold and associated base metals (Ag, Cu, Mo)
- Porphyry outcrop discovered during initial field inspection coincides with regional scale geophysical interpretation

Sandy Mitchell Rare Earth and heavy Mineral Project

- Ark has recently Acquired the 147km² EPM 28013 'Sandy Mitchell' – an advanced Rare Earths Project in North Queensland with additional 138km² of sub blocks under application
- Very high historical TREO grades* including high grade pan concentrates of:
 - 18.4% TREO
 - 17.4% TREO
 - 15.8% TREO
 - 15.3% TREO
 - 12.3% TREO
 - 9.4% TREO
 - 4.7% TREO
 - 3.3% TREO

*Historical data, Not to JORC 2012 code standards

- Project contains all critical Light Rare Earths as well as Heavy Rare Earths including dysprosium (Dy), terbium (Tb), holmium (Ho), erbium (Er), thulium (Tm) ytterbium (Yb), yttrium (Y) and excluding only Lutetium
- Up to 25% of the TREO is Nd and Pr (magnet metals)
- Rare Earths at 'Sandy Mitchell' are amenable to panning a concentrate ; Planned low-cost, fast start up, straightforward beneficiation by gravity processing

Reliance on historic data

All sample data reported in this release, as disclosed in the body of the release, in the tables in the Appendix and in the JORC table is based on data compiled by the Competent Person from other sources and quoted in their original context. These sources have been referenced in the text and the original Competent Persons statements may be found with the relevant documents. Some of this information is publicly available but has not been reported in accordance with the provisions of the JORC Code and a completed Table 1 of the JORC Code and Competent Persons statement is attached to this Release. Whilst every effort has been made to validate and check the data, these results should be considered in the context in which they appear and are subject to field verification by the Company.

Cautionary Statement

The panned concentration samples were taken by Stuart Foster. And the reported assay results supplied to MKY Resources Ltd and Delminco Pty Ltd (2007 to 2009). Stuart Foster, the present owner of the tenement has supplied a hard copy of the panned concentrate results to Ark. Mr Foster has also supplied a statement pertaining to the sampling procedures undertaken. There is however some information which is not available, and cannot be included in the Table 1. Sample results were sent to SGS Townsville for assaying the assay technique is yet to be determined and the assay receipts have not been sited. It is possible that following further evaluation and/or exploration work that the confidence in the prior exploration results may be reduced when reported under the JORC Code 2012. However, nothing has come to the attention of Ark that causes it to question the accuracy or reliability of S Fosters exploration results. The Company however has not independently validated the former explorers exploration results and therefore is not to be regarded as reporting, adopting or endorsing those results.

Competent Persons Statement

The Information in this report that relates to exploration results, mineral resources or ore reserves is based on information compiled by Mr Roger Jackson, who is a Fellow of the Australian Institute of Mining and Metallurgy and a Fellow of the Australasian Institute of Geoscientists. Mr Jackson is a shareholder and director of the Company. Mr Jackson has sufficient experience which is relevant to the style of mineralisation and type of deposits under consideration and to the activity that he is undertaking to qualify as a Competent Person as defined in the 2012 edition of the 'Australian Code for Reporting Exploration Results, Mineral Resources and Ore Reserves' (the JORC Code). Mr Jackson consents to the inclusion of this information in the form and context in which it appears in this report. Mr Jackson confirms information in this market announcement is an accurate representation of the available data for the exploration areas being acquired.

Forward Looking Statements and Important Notice

This report contains forecasts, projections and forward-looking information. Although the Company believes that its expectations, estimates and forecast outcomes are based on reasonable assumptions it can give no assurance that these will be achieved. Expectations and estimates and projections and information provided by the Company are not a guarantee of future performance and involve unknown risks and uncertainties, many of which are out of Vertex Minerals' control.

Actual results and developments will almost certainly differ materially from those expressed or implied. Vertex Minerals has not audited or investigated the accuracy or completeness of the information, statements and opinions contained in this announcement. To the maximum extent permitted by applicable laws, Ark Mines makes no representation and can give no assurance, guarantee or warranty, express or implied, as to, and takes no responsibility and assumes no liability for the authenticity, validity, accuracy, suitability or completeness of, or any errors in or omission from, any information, statement or opinion contained in this report and without prejudice, to the generality of the foregoing, the achievement or accuracy of any forecasts, projections or other forward looking information contained or referred to in this report.

Investors should make and rely upon their own enquiries before deciding to acquire or deal in the Company's securities.

Appendix A: JORC Code, 2012 Edition – Table 1

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> • <i>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i> • <i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i> • <i>Aspects of the determination of mineralisation that are Material to the Public Report.</i> • <i>In cases where ‘industry standard’ work has been done this would be relatively simple (eg ‘reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay’). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</i> 	<p>Data taken from W. Scott and Partners EPM18308 2014 Annual Report CR075376</p> <p>Augur Sampling</p> <ul style="list-style-type: none"> • Auger programme, using 6m auger • Total soils were collected by hand from the collar to give a composite sample of 5m or depth of refusal, • Sample was split by 25/75 riffle splitter to yield a 3 to 4 kg aliquot per hole <p>Data provided by Stuart Foster and pertaining to the panned concentration samples.</p> <ul style="list-style-type: none"> • Stream and soil samples were panned to yield a heavy mineral concentrate. The panned residual material was placed in calico sample bags and sent to SGS for assaying.
Drilling techniques	<ul style="list-style-type: none"> • <i>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if</i> 	<p>Augur Samples</p> <ul style="list-style-type: none"> • Augur Drilling • 6 inch diameter • 5m depth • Vertical hole <p>Panned Concentrates</p>

	<p><i>so, by what method, etc).</i></p>	<ul style="list-style-type: none"> • No drilling undertaken
<p>Drill sample recovery</p>	<ul style="list-style-type: none"> • <i>Method of recording and assessing core and chip sample recoveries and results assessed.</i> • <i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i> • <i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i> 	<p>Augur Samples</p> <ul style="list-style-type: none"> • Recoveries were not recorded. • Relationships between sample recovery and grade could not be determined without original sample weight data, however the CP does not believe a material relationship exists given it was Augur sampling. Short hole auger soil sampling is not known to cause significant material fractionation as might be expected with RAB or RC techniques. <p>Panned Concentrates</p> <ul style="list-style-type: none"> • No drilling undertaken
<p>Logging</p>	<ul style="list-style-type: none"> • <i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i> • <i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i> • <i>The total length and percentage of the relevant intersections logged.</i> 	<p>Augur Samples</p> <ul style="list-style-type: none"> • Samples were not logged • Total Counts per second were taken <p>Panned Concentrates</p> <ul style="list-style-type: none"> • Not logged
<p>Sub-sampling techniques and sample preparation</p>	<ul style="list-style-type: none"> • <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i> • <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i> • <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i> • <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i> • <i>Measures taken to ensure that the sampling is representative of the in situ material collected,</i> 	<p>Augur Samples</p> <ul style="list-style-type: none"> • Samples were composited over the full length of the Augur depth. • Total soils were collected progressively by hand from the collar to give a composite sample of 5m or depth of refusal, • Sample was split by 25/75 riffle splitter to yield a 3 to 4 kg aliquot per hole. • The samples size are appropriate to the grain size of the material sampled: Sand to very fine sand. <p>Panned Concentrates</p> <ul style="list-style-type: none"> • No compositing undertaken • The sample size would be appropriate to the grain size of the material sampled. Sand to very fine sand.

including for instance results for field duplicate/second-half sampling.

- Whether sample sizes are appropriate to the grain size of the material being sampled.

Quality of assay data and laboratory tests

- The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.
- For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.
- Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.

Augur Samples

- Drill samples were sent to SGS Laboratories Townsville.
- Aliquots were collected from the splitter in calico sample bags and submitted to SGS Townsville for assay by ICP-OES
- Duplicate samples were produced at a rate of 1 in 13 and assayed.
- Twin auger holes were drilled at a rate of 1 in 100 with sample and assay as per other holes.
- The laboratory procedure was SGS ICP95A for major elements and IMS41Q for REE.

Panned Concentrates

- The samples were sent to SGS Laboratories Townsville.
- The laboratory procedure was SGS ICP95A for major elements and IMS41Q for REE.
- Duplicate samples were taken Refer to the panned concentrate table.

Verification of sampling and assaying

- The verification of significant intersections by either independent or alternative company personnel.
- The use of twinned holes.
- Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.
- Discuss any adjustment to assay data.

Augur Samples

- The work was undertaken by others.
- There is no way of verifying the sampling or the data other than observation of its spatial relationships and internal consistency.
- Assay data yielding elemental concentrations for rare earths (REE) within the sample are converted to their stoichiometric oxides (REO) in a calculation performed within the database using the conversion factors in the table below.
- Rare Earth oxide is the industry accepted form for reporting rare earths. The following calculations have been used for reporting throughout this report;

TREO = La2O3 + CeO2 = Pr6O11 + Nd2O3 +

Sm2O3 + Eu2O3 + Gd2O3 + Tb4O7 + Dy2O3 + Ho2O3 + Er2O3 + Tm2O3 + Yb2O3 + Lu2O3 + Y2O3

CREO = Nd2O3 + Eu2O3 + Tb4O7 + Dy2O3 + Yb2O3

LREO = La2O3 + CeO2 = Pr6O11

HREO = Sm2O3 + Eu2O3 + Gd2O3 + Tb4O7 + Dy2O3 + Ho2O3 + Er2O3 + Tm2O3 + Yb2O3 + Lu2O3 + Y2O3

ND/Pr = Nd2O3 + Pr6O11

TREO – Ce = TREO – CeO2

- %NdPr + NdPr/TREO

Element Name	Element Oxide	Oxide Factor
Ce	CeO2	1.2284
Dy	Dy2O3	1.1477
Er	Er2O3	1.1435
Eu	Eu2O3	1.1579
Gd	Gd2O3	1.1526
Ho	Ho2O3	1.1455
La	La2O3	1.1728
Lu	Lu2O3	1.1371
Nd	Nd2O3	1.1664
Pr	Pr6O11	1.2081
Sc	Sc2O3	1.5338
Sm	Sm2O3	1.1596
Tb	Tb4O7	1.1762
Th	ThO2	1.1379
Tm	Tm2O3	1.1421
U	U3O8	1.1793
Y	Y2O3	1.2699
Yb	Yb2O3	1.1387

Panned Concentrates

- The work was undertaken by others.
- There is no way of verifying the sampling or the data other than observation of its spatial relationships and internal consistency.

Location of data points

- Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral

Augur Samples

- All collar coordinates were located with hand held GPS with an accuracy of ±5m.
- All coordinates were converted from WGS84 UTM z 54, to MGA94 z 54 by the GPS.

For personal use only

Resource estimation.

- *Specification of the grid system used.*
- *Quality and adequacy of topographic control.*

- Current topographic control is by AGSO DEM derived 10m contours which are of greater accuracy than the $\pm 50m$ available from hand held GPS. This is sufficient for the current stage of pre-resource exploration.

Panned Concentrates

- All collar coordinates were located with hand held GPS with an accuracy of $\pm 5m$.
- All coordinates were converted from WGS84 UTM z 54, to MGA94 z 54 by the GPS.
- Current topographic control is by AGSO DEM derived 10m contours which are of greater accuracy than the $\pm 50m$ available from hand held GPS. This is sufficient for the current stage of pre-resource exploration.

Data spacing and distribution

- *Data spacing for reporting of Exploration Results.*
- *Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.*
- *Whether sample compositing has been applied.*

Augur Samples

- Augur drilling was undertaken over three E-W fences of auger holes approximately each 9 km long
- Hole spacings at approximately 250 metres.
- Samples were composited at the sampling stage.
- These factors result in some data gaps that require infill.
- Variography to determine appropriateness of grade continuity for resource estimation has not yet been carried out but the current spacing is not expected to support resource estimation.
- No resource or reserve is reported.

Panned Concentrates

- Samples were taken randomly in areas with a high radiometric reading.
- No resource or reserve is reported.

Orientation of data in relation to

- *Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is*

Augur Samples

- Drill holes were drilled vertically which is appropriate for horizontal regolith

<p>geological structure</p>	<p><i>known, considering the deposit type.</i></p> <ul style="list-style-type: none"> <i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i> 	<p>profile.</p> <ul style="list-style-type: none"> Any sampling bias resultant from the orientation of drilling and possible structural offsets of mineralisation is considered to be minimal. The fence of augur holes running east west cross the North south alluvial patterns. The orientation of the drilling is considered appropriate for testing the lateral and vertical extent of mineralisation without any bias. <p>Panned Concentrates</p> <ul style="list-style-type: none"> The sampling is random There is no relationship of sampling to mineralisation orientation
<p>Sample security</p>	<ul style="list-style-type: none"> <i>The measures taken to ensure sample security.</i> 	<ul style="list-style-type: none"> Samples were farmed on the remote site with batches transported and delivered to SGS by company personnel.
<p>Audits or reviews</p>	<ul style="list-style-type: none"> <i>The results of any audits or reviews of sampling techniques and data.</i> 	<ul style="list-style-type: none"> Data was audited in mid Feb 2023 by independent geologists of Empirical Earth Science. The data was found to be acceptable for the current stage of exploration with recommendation that the original assay returns and laboratory QAQC be sourced from the previous owner or SGS Townsville.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
<p>Mineral tenement and land tenure status</p>	<ul style="list-style-type: none"> <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i> <i>The security of the tenure held at the time of reporting along with</i> 	<ul style="list-style-type: none"> EPM 28013 Sandy Mitchell is 100% owned by Ark Mines Limited. It was purchased on the 23rd of February 2023. This tenement was formally EPM18308 There are no third party agreements No known issues impeding on the security of the tenure of Ark Mines ability to operate in the area exist.

Criteria	JORC Code explanation	Commentary
<p>Exploration done by other parties</p>	<p><i>any known impediments to obtaining a licence to operate in the area.</i></p> <ul style="list-style-type: none"> • <i>Acknowledgment and appraisal of exploration by other parties.</i> 	<p>A number of companies and individuals have explored the area for gold and base metals and for heavy minerals. The summaries presented below are from the IRTM source:</p> <ul style="list-style-type: none"> • ATP 597M was granted to Laskan Minerals Pty Ltd in 1969 over the Reid Creek area, north of the Mitchell River. From assays of rock chip and stream sediment samples, it was concluded that there was little chance of economic mineralisation occurring in the Authority. Although good monazite grades were obtained, the samples were from creeks with little available wash. Good concentrations of monazite and ilmenite were present in large areas of sandy, alluvial sheet wash in the Reid's Creek area. It was believed that there was a potential for economic exploitation if the monazite concentrations occurred in a large enough volume of sandy material. No further work was reported. • In 1970, Altarama Search Pty Ltd was granted ATP 833M over the Mitchell River in the Reid Creek, Sandy Creek and Mount Mulgrave Homestead area. Four hundred stream sediment samples, at an average density of 1.25 samples/km², were collected for assay. Copper and lead contents were low. Half of the zinc results were considered to be possibly anomalous. A two population distribution was obtained for zinc, with a standard threshold of about 15 ppm. It was suggested that the two population distributions represented normal background ranges present in different strata. No other work was carried out. • ATP 2580M was granted to Tacam Pty Ltd over Sandy Creek and its tributaries. Stream sediment samples averaged 0.18% monazite (0.01 to 0.45%), 0.07% rutile (0.15% in terraces), and 0.06% zircon (0.14% in terraces). The area had low economic potential and the Authority was abandoned in August 1981. • The principals involved in Tacam Pty Ltd combined with Metcalfe Holdings Pty Ltd in 1986 to take up 4 Authorities to Prospect - 4400,4401,4402 and 4403 centred on Mt Mulgrave, Arkara Creek, Sandy Creek and the Kennedy River respectively. The investigations were for the possibility of locating large-scale heavy minerals in association with major drainages and lower slope eluvial

For personal use only

For personal use only

Criteria	JORC Code explanation	Commentary
		<p>deposits associated with Cretaceous weathering as indicated in previous investigations. EPM 4400, 4401, 4402 and 4403</p> <ul style="list-style-type: none"> Barron and O’Toole focused on Mt Mulgrave for Ilmenite, rutile, REE, Monzonite, Zircon, and Gold. Tenement EPM 4400 consisted of 96 sub-blocks centred on Mount Mulgrave (7665, 7765), EPM 4401 consisted of 97 sub-blocks centred on Arkara Creek (7665), EPM 4402 consisted of 100 sub-blocks centred on Sandy Creek (7665) and EPM 4403 consisted of 86 sub-blocks centred on Kennedy River (7666, 7766) were granted to P.T.C. Barron, A. O’Toole and Metcalfe Holdings Pty Ltd on 22 September 1986 to explore for heavy minerals and precious metals. After three years of exploration the EPMs were surrendered on 22 August 1989. Tenement EPM 10185 consisted of 157 sub-blocks was granted to Palmer Gold Pty Ltd on 25 October 1994 for an initial 2 year period. The exploration permit was renewed for a further 3 years on 25 October 1996 and surrendered on 3 October 2001. The tenement was situated 200km west of Cooktown. <p>Rationale</p> <p>Significant gold-silver, tin and base metal deposits are known from the Georgetown and southern Dargalong Inliers to the south of EPM 10185 (e.g. Etheridge, Croydon and Oaks goldfields), from the Hodgkinson Province to the east (e.g. Palmer, Hodgkinson, Russell River, Starcke, Jordon Ck, Mareeba and Mount Peter goldfields, and Herberton-Mt Garnet tinfield), and the Coen Inlier to the north (e.g. Alice River & Potallah goldfields). However, other than brief reference to sub-economic alluvial gold occurrences near the junction of the Palmer and Mitchell Rivers, and in the Staaten, Lynd and Walsh Rivers (Culpeper 1993), no precious or base metal deposits are known to occur within rocks of the Yambo Inlier.</p> <p>Application for the area was made after structural interpretation of the region showed prospectivity for gold occurrence. Base metal anomalies delineated from previous exploration were also targeted for follow-up work.</p> <ul style="list-style-type: none"> In 2007 exploration activity was carried out by BHP Billiton Minerals Pty Ltd under an extremely large area (2,850 sub-blocks) of the Coen Yambo area from 2005 to 2007. EPM’s 14438 and 14445 covered the majority of the Yambo Inlier. BHP targeted Ni sulphide and PGM and carried out AEM surveying, field mapping and sampling and drilling. The AEM targets were found to be related to sedimentary lithological units or obvious shear zones.

For personal use only

Criteria	JORC Code explanation	Commentary
		<ul style="list-style-type: none"> In 2007 - 2009 - MTY Resources Ltd undertook bulk sampling program along with a Panned Concentrate sampling program as reported in this report. In 2012 Waverley Nominees undertook an Augur sampling program as set out in this report
Geology	<ul style="list-style-type: none"> <i>Deposit type, geological setting and style of mineralisation.</i> 	<p>The tenement covers portion of the southern extent of the Yambo Inlier, one of the several Proterozoic inliers to the west of the Palmerville Fault System. Rocks of the Yambo Inlier covered by the tenement comprise those of the middle Proterozoic Yambo Metamorphic Group of mainly amphibolites and gneisses ranging in age from ~1690 Ma to ~1585 Ma. These rocks have been intruded by Silurian-Devonian granites of the Lukinville Suite which form an integral part of the Cape York Batholith. Within the tenement they form a belt roughly 10 km wide trending NNW. Extensive intrusions of Carboniferous-Permian dolerites occur throughout the Inlier, with only a few occurrences within the tenement.</p> <p>The tenement is largely gold deficient except for the gold reporting to sediments within the Palmer River. Recent Governmental radiometric surveys have highlighted areas of anomalous radiometric emission within the Yambo Inlier. The project tenements cover the majority of the anomalous radiometric areas.</p> <p>There are many stream systems within the Mulgrave/Sandy Mitchell tenements and they contain concentrations of rare earth minerals. These minerals have been derived from the now denuded remnant Jurassic-Cretaceous sandstone-pebble conglomerates and quartz sandstones, with the greater volumes being associated with the breakdown of the Mesoproterozoic basement rocks. Isolated areas of high garnet concentrations are derived from irregular zones of highly garnetiferous dolerites and schists.</p>
Drill hole Information	<ul style="list-style-type: none"> <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> <i>easting and northing of the drill hole collar</i> <i>elevation or RL (Reduced Level</i> 	<p>Augur Samples</p> <ul style="list-style-type: none"> Refer to Table in Appendices C <p>Panned Concentrate</p> <ul style="list-style-type: none"> Refer to Table in Appendices B

For personal use only

Criteria	JORC Code explanation	Commentary
	<ul style="list-style-type: none"> – elevation above sea level in metres) of the drill hole collar ○ dip and azimuth of the hole ○ down hole length and interception depth ○ hole length. ● If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	
<p>Data aggregation methods</p>	<ul style="list-style-type: none"> ● In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. ● Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. ● The assumptions used for any reporting of metal equivalent values should be clearly stated. 	<ul style="list-style-type: none"> ● No high or Low-grade top/bottom-cut has been applied. ● The total data set is reported in Appendix C ● REE Equivalent TREO (total REE oxides) is reported as this is the industry standard for presentation of REE data. Stoichiometric calculation of REE oxide equivalents were performed in units of ppm, with TREO, LREO (light REE oxides), HREO (heavy REE Oxides), CREO (critical REE oxides) and Mag REO (magnet production REE oxides), as per Table 1 page 2 and 3, yielding these factors as concentrations and percentages of TREO concentration. <p>Panned Concentrates</p> <ul style="list-style-type: none"> ● The total data set is reported in Appendix X
<p>Relationship between mineralisation widths and intercept lengths</p>	<ul style="list-style-type: none"> ● These relationships are particularly important in the reporting of Exploration Results. ● If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. ● If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg ‘down hole length, true width not known’). 	<p>Augur Samples</p> <ul style="list-style-type: none"> ● All holes sample assays are based on sampling of the whole hole length. ● The mineralisation is interpreted to be flat lying and drilling is vertical perpendicular to mineralisation. Any internal variations to REE distribution within the horizontal layering was not defined, therefore the true width is considered not known at the current stage of development. <p>Panned Concentrates</p> <ul style="list-style-type: none"> ● Not relevant to soil samples

Criteria	JORC Code explanation	Commentary
Diagrams	<ul style="list-style-type: none"> • <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i> 	<ul style="list-style-type: none"> • See plan image 2 and 3.
Balanced reporting	<ul style="list-style-type: none"> • <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i> 	<ul style="list-style-type: none"> • Results reported include all recovered assay, both low and high grade, for all holes. • See Appendix B and C for full data.
Other substantive exploration data	<ul style="list-style-type: none"> • <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i> 	<ul style="list-style-type: none"> • All data material to this report that has been collected to date has been reported textually, graphically or both. • Absent material data includes, Drill collar RLs, bulk density, the nature, quality and appropriateness of the assaying and laboratory procedures , water table height and geotechnical characteristics is absent from the historical data record recovered so far, and current data is still undergoing analysis. These data are not relevant to the current pre-resource drill data release.
Further Work	<ul style="list-style-type: none"> • <i>The nature and scale of planned further work.</i> 	<ul style="list-style-type: none"> • Ark plans to undertake further infill Augur drilling, further beneficiation test work, pilot plant test work. Resourcing and reserve studies.

Appendix B: Panned Concentrate Table

Sample ID	E MGA94z54	N MGA94z54	Samp Type	TREO ppm	LREO %	HREO %	CREO %	Mag Reo %	Sc ₂ O ₃ ppm	La ₂ O ₃ %	CeO ₂ %	Pr ₆ O ₁₁ ppm	Nd ₂ O ₃ %	Sm ₂ O ₃ ppm	Eu ₂ O ₃ ppm	Gd ₂ O ₃ ppm	Y ₂ O ₃ ppm	Tb ₄ O ₇ ppm	Dy ₂ O ₃ ppm	Ho ₂ O ₃ ppm	Er ₂ O ₃ ppm	Tm ₂ O ₃ ppm	Yb ₂ O ₃ ppm	Lu ₂ O ₃ ppm	Note			
430A	813624	8195067	Pan Con	153,969	95.4	4.6	23.7	25.9	225.5	3.26	7.10	8,288	2,9976	4,650	120.4		4,749	349.3	1,285	174.1	354.5	29.7	160.56					
443A	808124	8196989	Pan Con	94,180	95.5	4.5	23.1	25.3	220.9	2.05	4.34	5,014	1,7846	2,876	88.5		2,806	197.6	797	103.8	215.0	19.6	109.77			twin		
443B	808125	8196989	Pan Con	17,554	91.1	8.9	25.5	24.3	309.8	0.35	0.76	887	0.3126	513	25.5		1,062	46.6	211	37.1	99.0	13.6	90.185			twin		
447A	807601	8195835	Pan Con	47,376	95.0	5.0	23.7	25.6	123.0	1.02	2.16	2,525	0.904	1,450	56.0		1,549	120.0	457	58.2	114.4	9.7	50.786					
450A	812239	8195625	Pan Con	174,126	95.9	4.1	23.0	25.6	171.8	3.75	8.11	9,351	3,3359	5,369	135.5		4,661	407.0	1,400	173.0	335.0	25.9	133.23					
450B	812239	8195625	Pan Con	17,929	90.6	9.4	26.1	24.6	300.6	0.35	0.77	904	0.3231	525	24.0		1,156	47.0	220	39.7	109.0	15.0	100.21			twin		
451	812274	8195859	Pan Con	184,777	95.8	4.2	23.1	25.6	199.4	3.99	8.59	9,895	3,5459	5,624	162.1		5,029	441.1	1,515	184.4	355.6	28.1	144.61					
452A	810407	8190286	Pan Con	158,691	95.8	4.2	22.7	25.2	170.3	3.48	7.37	8,518	2,9743	4,859	143.6		4,407	381.1	1,308	162.7	313.3	24.3	125.26					
452B	810407	8190286	Pan Con	30,334	93.8	6.2	24.4	25.3	233.1	0.63	1.36	1,583	0.5715	914	36.6		1,261	74.9	304	45.0	107.0	12.6	79.14			twin		
452A2	810408	8190286	Pan Con	123,058	95.7	4.3	22.8	24.7	135.0	2.73	5.72	5,932	2,3211	3,792	118.1		3,467	297.6	1,002	131.7	268.7	19.8	112.73			duplicate		
Note:																												
TREO:	Total REE Oxides = Sc ₂ O ₃ + La ₂ O ₃ + CeO ₂ + Pr ₆ O ₁₁ + Nd ₂ O ₃ + Sm ₂ O ₃ + Eu ₂ O ₃ + Gd ₂ O ₃ + Y ₂ O ₃ + Tb ₄ O ₇ + Dy ₂ O ₃ + Ho ₂ O ₃ + Er ₂ O ₃ + Tm ₂ O ₃ + Yb ₂ O ₃ + Lu ₂ O ₃ (includes Sc & Y)																											
	NB: Gd & Lu not assayed																											
LREO:	Light REE Oxides = Sc ₂ O ₃ + La ₂ O ₃ + CeO ₂ + Pr ₆ O ₁₁ + Nd ₂ O ₃ + Sm ₂ O ₃ + Eu ₂ O ₃ + Gd ₂ O ₃ (includes Sc)																											
	NB: Gd not assayed																											
HREO:	Total REE Oxides = Y ₂ O ₃ + Tb ₄ O ₇ + Dy ₂ O ₃ + Ho ₂ O ₃ + Er ₂ O ₃ + Tm ₂ O ₃ + Yb ₂ O ₃ + Lu ₂ O ₃ (includes Y)																											
	NB: Lu not assayed																											
CREO:	Critical REE Oxides = Nd ₂ O ₃ + Eu ₂ O ₃ + Y ₂ O ₃ + Tb ₄ O ₇ + Dy ₂ O ₃ (US Dept' Energy Definition)																											
Mag REO:	Magnet Production REE Oxides = Pr ₆ O ₁₁ + Nd ₂ O ₃ + Tb ₄ O ₇ + Dy ₂ O ₃																											

For personal use

