

ASX Announcement | ASX: TNC

3 October 2023

TNC intercepts 6m @ 12.99 g/t Au and 10m @ 2.22% Cu at Wallace North, with multiple high-grade zones

True North Copper Limited (ASX:TNC) (True North, TNC or the Company) is pleased to announce resource extension drilling and Induced Polarisation (IP) survey results at Wallace North, part of its Cloncurry Project in Queensland, identified multiple open zones of high-grade copper and gold mineralisation. Wallace North has a current combined Indicated and Inferred resource of 1.39Mt @ 1.38% Cu and 0.90g/t Au.¹

Highlights:

- Drill results highlighted significant growth potential including:
 - Defining the down plunge continuity of a 100m wide, 250m deep high-grade copper gold shoot open at depth
 - Intersecting the top of an untested shoot, potentially 200m wide and open to depth.
- Significant high-grade copper and gold mineralisation across drillhole results included:

WNR0001

10.0m (8.74m*) @ 2.22% Cu, 1.41g/t Au from 146.00m

WNR0006

- 6.0m (5.05m*) @ 0.43% Cu, 12.99g/t Au from 151.00m
- 4.0m (3.35m*) @ 3.38% Cu, 1.81g/t Au from 88.00m

WNR0002

7.0m (5.55m*) @ 2.14% Cu, 1.13g/t Au from 110.00m

WNR0005

- 5.0m (3.82m*) @ 2.18% Cu, 7.31g/t Au from 182.00m
- Inc. 2.0m (1.53m*) @ 2.89% Cu, 17.08g/t Au from 185.00m

WNR0007

- 3.0m (2.51m*) @ 3.57% Cu, 2.48g/t Au from 109.00m
- 7.0m (5.90m*) @ 3.10% Cu, 1.32g/t Au from 214.00m
- New IP geophysics and historic EM indicate substantial depth extent to the Wallace North system and highlight new targets with similar signatures to recent discoveries of gold-endowed iron-sulphide-copper-gold deposits in the Mt Isa Inlier.
- Further development of Wallace North will include resource restatement, mining and metallurgical studies, downhole
 and ground-based geophysics and follow-up drillhole targeting (with completion expected Q1 2024).
- *= Estimated True Width



Comment

True North Copper's Managing Director, Marty Costello said:

"A successful resource expansion drilling and IP survey program at our fully permitted, 100%-owned, high-grade copper and gold Wallace North Project has identified multiple zones of high-grade copper and gold mineralisation outside the current resource shell, including Hole WNR0001, which included 10m (true width 8.74m) at 2.22% copper and 1.41g/t gold. Additionally, the high-grade gold intercept of WNR0006 was a highlight with 6m (true width of 5.05m) of 0.43% copper and an impressive 12.99g/t gold.

The current Wallace North Resource is 1.39Mt has a copper grade of 1.39% and gold grade of 0.9g/t, but it does not have a Reserve. Thanks to this completed resource expansion drilling and IP surveying, along with our recently concluded advanced grade control drilling program, which included 150 drillholes and more than 9400m of drilling, we can now finalise an updated resource for Wallace North.

Wallace North is an important part of our Cloncurry Hub mining plans. This drilling program confirms there are several highgrade copper and gold zones within the Wallace North approved mining footprint, open at depth and warranting further exploration. More drilling will be undertaken across these zones and the anomalies we identified as part of recent IP surveys.

We are conducting revised metallurgical tests in conjunction with the upcoming technical tasks related to the development of the initial Wallace North Reserve Statement. This testing aims to validate effective extraction and processing methods. The prevalent copper mineralisation in the resource, as observed from our drilling, is chalcopyrite, which typically responds well to standard flotation. Given the gold is intertwined with the copper mineralisation, there is a strong possibility of extracting gold in a concentrated form during ore processing."





Figure 1: Location of the Wallace North Project (Wallace Complex) in relation to TNC's and other projects in the area.

Summary of TNC's Drill Intersections to date

True North Copper has received assay results from eight (8) reverse circulation (RC) drillholes (WNR0001 to WNR0008) completed at its Wallace North Resource. These constitute both infill and extension holes to the 2023 resource¹ (Figure 2 and Figure 3). Significant downhole intercepts are provided in Table 1 and illustrated in plan, long and cross-sections Figure 2, Figure 3, Appendix 1.





Figure 2 Plan view showing the collar location and drill traces of WNR0001 to WNR0008, Copper Block model displayed at > 0.2% Cu. Resource Cutoff at Wallace North 0.3% Cu.



Hole_ID	From (m)	To (m)	Width (m)	ETW (m)	Cu %	Au g/t
WNR0001	146	156	10.00	8.74	1 2.22	2 1.41
inc.	152	155	3.00	2.62	2 4.23	3.15
WNR0002	110	117	7.00	5.5	5 2.14	1.13
WNR0003				No Significant As	says	
WNR0004	139	144	5.00	4.42	2 1.61	0.84
WNR0005	182	187	5.00	3.82	2 2.18	7.31
inc.	185	187	2.00	1.5	2.89	17.08
WNR0006	88	92	4.00	3.3	5 3.38	1.81
inc.	89	90	1.00	0.84	11.00	7.00
WNR0006	151	157	6.00	5.0	5 0.43	12.99
WNR0006	177	180	3.00	2.54	1.61	1.73
WNR0007	109	112	3.00	2.5	3.57	2.48
WNR0007	214	221	7.00	5.90	3.10	1.32
inc.	216	219	3.00	2.53	4.72	2.43
WNR0008	54	58	4.00	3.3	2.77	0.27
WNR0008	230	231	1.00	1.00	2.04	1.06

 Table 1: WNR0001 to WNR0008. Selected copper and gold intercepts. See Table 3. for complete list of intercepts and calculation methods.

Resource infill and extension holes WNR0001 to WNR0008 (totalling 1,838m) were drilled as part of a larger Advanced Grade Control mining study drill program, consisting of 150 holes totalling 9,403m, that targeted the upper 50m of the resource in June and July of 2023. The primary aim of the exploration holes was to extend the base of the existing Wallace North Resource (1.39Mt @ 1.38% Cu and 0.90g/t Au total combined Indicated, and Inferred Resource¹).

WNR0001 to WNR0008 intersected and confirmed that primary copper-gold mineralisation is associated with sulphide infill breccias/veinlets hosted within earlier carbonate veins or brittlely deformed host rocks. Sulphide species include chalcopyrite, pyrrhotite and pyrite indicating the deposit is a structurally controlled, gold rich, iron-sulphide-copper-gold (ISCG) system. Supergene copper mineralisation of copper carbonates, chalcocite, and native copper is observed from 0m to ~50m below surface within the resource.

Several holes targeted the well defined 100m wide by 250 m deep south-westerly plunging high grade Cu-Au shoot below the base of resource at vertical depths between 90.00m and 200.00m below surface (Figure 3). Mineralisation intersected within the shoot is variable in grade and thickness suggesting the shoot may be pinching and swelling with the thickest parts of the shoot interpreted to be localised at the intersections of the main ENE orientated mineralised trend and NNW trending structures. WNR0001 and WNR0002 intersected shallow mineralisation at the base of the resource suggesting the potential for another shoot potentially 200m wide to be developed at depth down-plunge.

One of these NNW structures is also interpreted to have offset the main ENE orientated mineralisation trend between WNR0002 and WNR0003 (Figure 3). Low grade narrow mineralisation intersected in the top of hole WRN0003 suggests the hole has potentially drilled over the top of the mineralised trend.

The orientation of the plunging shoots and increase of gold grades suggests mineralisation may be feeding along subsidiary structures of a regional NW trending fault potentially linked to the TNC's Wallace South Gold Resource (0.27Mt @ 1.8g/t Au total combined Measured, Indicated, and Inferred Resource¹) (Figure 2). The intersections of the plunging shoots and NNW subsidiary structures are conceptual targets for high grade Cu-Au mineralisation in future drilling (Figure 3).





Figure 3: Wallace North Cu%m and Au gm long sections of main structural trend highlighting an open southwest plunging high grade shoot, increasing gold grades with depth and a potential top of a newly developing shoot in the southwest.



Induced Polarisation (IP) Survey Results

Australian Geophysical Services (AGS) completed 1-line for 1.45-line kilometres of 50 m spaced dipole-dipole of Induced Polarisation (IP) over the Wallace North Resource. The line was designed to test IP as an exploration tool for Wallace North style ISCG mineralisation in areas of cover. The line was extended to the north and south of the resource to test two exploration targets. IP responses were subdued from extremely low received signal due to the highly conductive geology in the area.

Coincident with the Wallace North Resource footprint, a +20 mV/v chargeability anomaly was identified coincident with the EM plates historically modelled by CopperChem⁸ that extend from the base resource to more than 1,100m below surface. The depth extents of these plates and the open nature of the shoots identified in drilling to date indicates a significant depth potential at Wallace North. (Figure 4).

Three additional targets were identified along the IP line (Figure 4), a coincident chargeable and conductive body 150 m north of the resource, and two chargeable and conductive bodies to the south.

Target 1 – A broad 50 mV/V chargeability anomaly with coincident conductivity (500 mS/m) is located at the expected depth of supergene/primary copper sulphide preservation below shallow cover. This IP anomaly spatially coincident with electromagnetic (EM) conductor plates (500-8000 S)⁸ that extends from 60m below surface to 700m below surface.

These EM plates are of similar conductivity thickness and depth extents as those plates that were targeted leading to the discovery of the Jericho Iron Sulphide Copper Gold (ISCG) Deposit⁹ (9.8Mt @ 1.8% Cu, 0.4g/t Au, 2.0g/t Ag¹⁰).

Historic shallow drilling over the top of the IP and EM responses returned anomalous copper and gold assays indicating that this zone is more likely potentiation leakage from a concealed Cu-Au mineral system that should be considered a high priority target.

- Target 2 Coincident chargeability (60 mV/V) anomaly located beneath recently mapped & undrilled east-west striking gossanous quartz veins in a similar stratigraphic position as Wallace North just on the other limb of the regional fold. Historic drilling to the south of the mapped veins contains anomalous Au and Cu. Target lies outside of the historic CopperChem EM survey.
- **Target 3** High order 70-90 mV/V chargeability anomaly to the south of historic drilling at the expected level of supergene sulphide/sulphide preservation below the base of cover. Target lies outside of historic CopperChem EM survey.

Next steps are to undertake downhole EM to help target deeper at Wallace North and to extend historic ground-based EM surveys to build a series of prioritised EM plate targets for drill testing along with the designing drillholes for the untested IP/EM targets highlighted above.





Figure 4. Wallace North IP chargeability inversion highlighting chargeability anomalies associated with known mineralisation and EM anomaly plates and untested anomalies considered as potential drill targets.

Wallace North Resource Extension Drillhole Details

WNR0001, WNR0002, WNR0004 and WNR0008 (Appendix 1, Figure 2 and Figure 3 and Figure 7) were designed to test the down-plunge extensions of high-grade shoots targeting approximately 25.00m and 50.00m below existing drillholes. All holes successfully extended mineralisation below the base of historic drilling and along strike and down-dip of hanging wall structures.

Intercept widths appear to be variable with depth indicating the shoots are potentially pinching and swelling with the thickest parts of the shoot interpreted to focus mineralisation at the intersections of the main ENE orientated mineralised trend and NNW trending structures. WNR0001 and WNR0002 intersected shallow mineralisation at the base of the resource that suggests the potential for another shoot potentially 200m wide to be developed at depth down-plunge.

Notably higher gold grades are also observed in recent drilling compared to historic intercepts used in the Wallace North MRE and may have a positive impact on contained metal in future resource estimations.

The orientation of the plunging shoots and increase of gold grades suggests mineralisation may be feeding along subsidiary structures of a regional NW trending fault potentially linked to the TNC's Wallace South Gold Resource (Figure 2). The intersections of the plunging shoots and NNW subsidiary structures are conceptual targets for high grade Cu-Au mineralisation in future drilling and provide significant growth potential (Figure 3).

- WNR0001 intersected 10.0m (8.74m*) @ 2.22% Cu & 1.41g/t Au from 146.00m, 25m below historic drilling (Figure 3, Figure 5, Figure 8).
- WNR0002 intersected 7.0m (5.55m*) @ 2.14% Cu & 1.13g/t Au from 110.00m, 33m below historic drilling. (Figure 3, Figure 9)
- WNR0004 intersected 5.0m (4.42m*) @ 1.61% Cu & 0.84g/t Au from 139.00m, including 3.0m (2.54m*) @ 2.27% Cu & 1.18g/t Au 50m below historic drilling. (Figure 3, Figure 10)



Figure 5: WNR0001; 10.0m (8.74m*) @ 2.22% Cu, 1.41g/t Au from 146.00m

WNR0008 successfully intersected narrow continuation of mineralisation of 1.0m (1.00m*) @ 2.04% Cu, 1.06g/t Au from 230.00m over 100m down-dip of existing drill intercepts (Figure 3, Figure 14). The hole has been PVC cased for DHEM planned for early 2024.

WNR0003 (Figure 3) tested the continuity of mineralisation, west along strike of existing drilling by 80m. Low grade narrow mineralisation was intersected near the top of the hole and may suggest mineralisation is offset by a NNW trending subsidiary structure, and the hole has potentially drilled over the top of the mineralising structural zone.

Wallace North Resource Infill Drillhole Details

WNR0005, WNR0006 and WNR0007 (Appendix 1, Figure 2 and Figure 3) were designed as resource infill holes targeting 25.00m to 50.00m of existing drill intercepts. All holes intersected mineralisation within the intended infill target zones, and will likely increase the confidence of future resource estimates.

WNR0006 intersected a mineralised hanging wall structure reporting a high-grade gold intercept of 6.0m (5.05m*) @ 0.43% Cu, 12.99g/t Au from 151.00m that is a 35m extension of a mineralised hanging wall structure. Another hanging wall structure intersected at 88m returned 4.0m (3.35m*) @ 3.38% Cu, 1.81g/t Au from 88.00m (inc. 2.0m (1.68m*) @ 6.10% Cu, 3.53g/t Au from 89.00m) (Figure 6). At the primary target on the main structure, drilling successfully encountered the target zone, returning 3.0m (2.54m*) @ 1.61% Cu, 1.73g/t Au from 177.00m (Figure 3, Figure 12)).

- WNR0005 (Figure 3, Figure 11) tested within a 50m spacing between existing drill intercepts. The hole intersected 5.0m (3.82m*) @ 2.18% Cu & 7.31g/t Au from 182.00m.
- WNR0007 tested within a 25 m spacing of existing drill intercepts, intersecting 7.0m (5.90m*) @ 3.10% Cu, 1.32g/t Au from 214.00m. (Figure 3, Figure 13).





Figure 6: WNR0006; 4.0m (3.35m*) @ 3.38% Cu, 1.81g/t Au from 88.00m (inc. 2.0m (1.68m*) @ 6.10% Cu, 3.53g/t Au from 89.00m).

Next steps in the Wallace North development include remodelling of the resource domains and recalculation of the resource to include exploration drilling and results received from the Advanced Grade Control Drillholes. This restated resource can be used for pit design, mining and financial analysis for future reserve statements anticipated in Q1 2024.



REFERENCES

- 1. True North Copper. ASX (TNC): Release 16 June 2023, *Prospectus*; True North Copper. ASX (TNC): Release 28 February 2023, *Acquisition of the True North Copper Assets*.
- 2. Evolution Mining Ltd. ASX: (EVN) Release 16 February 2023, Annual Mineral Resources and Ore Reserves Statement
- 3. Glencore PLC. LON: (GLEN) Resources & Reserves Report 31 January 2023, Last retrieved 27 September 2023 https://www.glencore.com/.rest/api/v1/documents/9103f1a33987bb1ca949662011373c42/GLENCORE+Resources+and+Reserves+report+2022.pdf
- AIC Mines Ltd. ASX: (AIC) Release 30 March 2023, Significant Increase in Mineral Resources and Ore Reserves at Eloise Copper Mine
- 5. AIC Mines Ltd. ASX: (AIC) Release 06 February 2023, Jericho Mineral Resource
- 6. Moly Mines Ltd. ASX: (MOL) Release 28 May 2018, Annual General Meeting Presentation
- 7. CuDECO. ASX: (CDU) Release 3 March 2016, Rocklands Feasibility Study
- Hine, K. 2012. Kangaroo Rat FLEM Results. Mitre Geophysics. In. Brown, M. & Overall, D. 2013. EPMs 11675, 13091, 14276, 14295, 14429, 15923 combined annual report for period ended 31 March 2013. Exco Resources Ltd. Open access file retrieved from GSQ Open Data Portal
- Minotaur Exploration Ltd. Technical Workshop Presentation 20-21 March 2019, Jericho Copper-Gold Discovery: What Lurks Beneath the Deep Blue Sea. Last retrieved 27 September 2023 from https://smi.uq.edu.au/files/43680/1903_lsa_D1_08_Little_Jericho.pdf
- 10. AIC Mines Ltd. ASX (AIC) Release 14 July 2023. Jericho Maiden Ore Reserve
- 11. Tombola Gold Ltd, 2022. Tombola Increases the Resource Base upon Completion of the Acquisition of the Gold Projects of True North Copper. ASX announcement dated 16 September 2022.
- 12. Queensland Government. EIS document: Release September 2022, Copper String Project, Coordinator General's evaluation report on the environmental Impact statement.

AUTHORISATION

This announcement has been approved for issue by Marty Costello, Managing Director and the True North Copper Limited Board.

COMPETENT PERSON'S STATEMENT

Mr Daryl Nunn

The information in this announcement includes exploration results from drillholes WNR0001-WNR0008 and an IP geophysical survey at Wallace North. Interpretation of these results is based on information compiled by Mr Daryl Nunn, who is a fulltime employee of Global Ore Discovery who provide geological consulting services to True North Copper Limited. Mr Nunn is a Fellow of the Australian Institute of Geoscientists, (FAIG): #7057. Mr Nunn has sufficient experience relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as a Competent Person as defined in the 2012 Edition of the Australiasian Code for the Reporting of Exploration Results, Mineral Resources, and Ore Reserves (JORC Code). Mr Nunn and Global Ore Discovery hold shares in True North Copper Limited.

DISCLAIMER

This release has been prepared by True North Copper Limited ABN 28 119 421 868 ("TNC" "True North" or the "Company"). The information contained in this release is for information purposes only. This release may not be reproduced, disseminated, quoted or referred to, in whole or in part, without the express consent of TNC.



The information contained in this release is not investment or financial product advice and is not intended to be used as the basis for making an investment decision. Please note that, in providing this release, TNC has not considered the objectives, financial position or needs of any particular recipient. The information contained in this release is not a substitute for detailed investigation or analysis of any particular issue and does not purport to be all of the information that a person would need to make an assessment of the Company or its assets. Current and potential investors should seek independent advice before making any investment decisions in regard to the Company or its activities.

No representation or warranty, express or implied, is made as to the fairness, accuracy, completeness or correctness of the information, opinions and conclusions contained in this news release. To the maximum extent permitted by law, none of TNC, its related bodies corporate, shareholders or respective directors, officers, employees, agents or advisors, nor any other person accepts any liability, including, without limitation, any liability arising out of fault or negligence for any loss arising from the use of information contained in this release.

This release includes "forward looking statements" within the meaning of securities laws of applicable jurisdictions. Forward looking statements can generally be identified by the use of the words "anticipate", "believe", "expect", "project", "forecast", "estimate", "likely", "intend", "should", "could", "may", "target", "plan" "guidance" and other similar expressions. Indications of, and guidance on, future earning or dividends and financial position and performance are also forward-looking statements. Such forward-looking statements are not guarantees of future performance and involve known and unknown risks, uncertainties and other factors, many of which are beyond the control of TNC and its officers, employees, agents or associates, that may cause actual results to differ materially from those expressed or implied in such statement. Actual results, performance or achievements are based. Readers are cautioned not to place undue reliance on forward looking statements and the assumptions on which those statements are based. Readers are cautioned not to place undue reliance on forward looking statements and the results and TNC assumes no obligation to update such information. Specific regard (amongst other things) should be given to the risk factors outlined in this release.

This release is not, and does not constitute, an offer to sell or the solicitation, invitation or recommendation to purchase any securities and neither this release nor anything contained in it forms the basis of any contract or commitment.

JORC AND PREVIOUS DISCLOSURE

The information in this release that relates to Mineral Resource Estimates for the Wallace North Resource is based on information previously disclosed in the Company's 16 June 2023 ASX release "*Prospectus*" available on the Company's website (www.truenorthcopper.com.au) and the ASX website (<u>www.asx.com.au</u>) under the Company's ticker code "TNC".

The information in this release that relates to Mineral Resource Estimates for the Wallace South Resource is based on information previously disclosed in the Company's 28 February 2023 ASX release "Acquisition of the True North Copper Assets" available on the Company's website (www.truenorthcopper.com.au) and the ASX website (<u>www.asx.com.au</u>) under the Company's ticker code "TNC".

The Company confirms that it is not aware of any new information as at the date of this release that materially affects the information included in this release and that all material assumptions and technical parameters underpinning the estimates and results continue to apply and have not materially changed.





APPENDIX 1 CROSS-SECTIONS, PLANS AND INTERCEPT TABLES

Cross-sections, Plans and Intercept Tables

Table 2. Collar and Survey information for WNR0001 to WNR0008 completed at the Wallace North Project.

	Hole ID	Easting (m) MGA2020	Northing (m) MGA2020	RL (m) AHD	Dip	Azimuth MGA2020	Total Depth (m)
	WNR0001	474368.72	7695940.02	188.00	-55.49	142.99	220
	WNR0002	474289.54	7695864.28	188.43	-60.36	143.64	180
(1D)	WNR0003	474208.69	7695791.25	187.89	-56.84	143.53	200
	WNR0004	474401.31	7695961.77	187.23	-64.11	142.78	246
UŊ	WNR0005	474516.39	7696040.50	188.24	-62.3	144.29	210
	WNR0006	474536.97	7696078.58	186.10	-56.26	144.49	223
Ð	WNR0007	474530.99	7696078.66	186.14	-65.46	162.84	260
	WNR0008	474449.20	7696075.02	185.73	-58.54	144.41	299







Table 3. Copper and Gold significant intercepts from holes WNR0001 to WNR0008.

Hole ID	From (m)	To (m)	Downhole Width (m)	ETW (m)	Cu %	Au g/t
	<u> </u>	0.3	3% Cu cut-off gra	ade with 2 m intern	al dilution	
WNR0001	146	156	10.00	8.74	2.22	1.41
WNR0002	4	9	5.00		0.38	0.06
WNR0002	23	25	2.00		3.05	1.52
WNR0002	55	57	2.00		0.89	0.31
WNR0002	64	65	1.00		0.49	0.09
WNR0002	68	69	1.00		1.10	0.11
WNR0002	74	75	1.00		0.70	0.18
WNR0002	79	80	1.00		1.96	0.24
WNR0002	86	87	1.00		1.20	0.15
WNR0002	96	97	1.00		0.51	0.32
WNR0002	110	117	7.00	5.55	2.14	1.13
WNR0002	121	122	1.00		0.31	0.15
WNR0002	128	131	3.00		0.97	0.40
WNR0002	136	139	3.00		0.91	0.40
WNR0003	31	32	1.00		0.35	0.01
WNR0004	139	144	5.00	4.42	1.61	0.84
WNR0005	156	163	7.00		0.80	0.31
WNR0005	168	171	3.00		0.70	0.29
WNR0005	182	187	5.00	3.82	2.18	7.31
WNR0005	198	200	2.00		0.41	0.06
WNR0006	88	92	4.00	3.35	3.38	1.81
WNR0006	147	148	1.00		0.39	3.63
WNR0006	151	157	6.00	5.05	0.43	12.99
WNR0006	177	180	3.00	2.54	1.61	1.73
WNR0007	31	32	1.00		0.60	0.13
WNR0007	91	92	1.00		0.91	0.35
WNR0007	109	112	3.00	2.51	3.57	2.48
WNR0007	214	221	7.00	5.90	3.10	1.32
WNR0008	54	58	4.00	3.37	2.77	0.27
WNR0008	130	131	1.00		0.39	0.08
WNR0008	230	231	1.00	1.00	2.04	1.06
WNR0008	258	259	1.00		1.06	0.24
		1.0	0% Cu cut-off gra	ade with 2 m intern	al dilution	
WNR0001	146	156	10.00	8.74	2.22	1.41
WNR0002	24	25	1.00		5.73	2.81
WNR0002	68	69	1.00		1.10	0.11
WNR0002	79	80	1.00		1.96	0.24
WNR0002	86	87	1.00		1.20	0.15
WNR0002	111	116	5.00	3.96	2.86	1.47
WNR0002	128	129	1.00		1.91	0.91
WNR0002	137	138	1.00		1.63	0.30
WNR0004	139	142	3.00		2.27	1.18
WNR0005	162	163	1.00		1.15	0.18
WNR0005	182	187	5.00	3.82	2.18	7.31
WNR0006	89	91	2.00	1.68	6.10	3.53

Hole ID	From (m)	To (m)	D W	ownhole /idth (m)		ETW (m)	С	u %	Αι	ıg/t
WNR0006	177	179		2.00				2.26		2.53
WNR0007	109	112		3.00		2.51		3.57		2.48
WNR0007	214	221		7.00		5.90		3.10		1.32
WNR0008	54	57		3.00				3.54		0.34
WNR0008	230	231		1.00		1.00		2.04		1.06
WNR0008	258	259		1.00				1.06		0.24
3.0% Cu cı	ut-off grade	with 2 ı	m int	ternal dilutio	on. ^	Selected 3 g/t	Au cut-o	ff with 2 m	n internal	dilution.
WNR0001	152	155		3.00		2.62		4.23		3.15
WNR0002	24	25		1.00				5.73		2.81
WNR0002	113	115		2.00		1.59		4.94		0.95
WNR0004	140	141		1.00				3.60		0.99
WNR0005	185	186		1.00		0.76		3.46		7.75
WNR0005^	185	187		2.00		1.53		2.89		17.08
WNR0006	89	90		1.00		0.84		11.00		7.00
WNR0007	109	110		1.00		0.84		7.56		6.21
WNR0007	216	219		3.00		2.53		4.72		2.43
WNR0008	54	56		2.00				4.64		0.50

Downhole intercepts are calculated at 0.3% Cu, 1% Cu & 3% Cu cutoff with length weighted average maximum consecutive waste below cutoff does not exceed 2m.

No cut-off is applied where gold is reported and is only reported within Cu intersections except where denoted with ^ where a 3g/t Au cutoff with maximum internal dilution of 2m.

All intervals are length weighted averaged.





Figure 8: WNR0001 cross section (30 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 9: WNR0002 cross section (30 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 10: WNR0004 cross section (30 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 11: WNR0005 cross section (40 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 12: WNR0006 cross section (20 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 13: WNR0007 cross section (20 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model





Figure 14: WNR0008 cross section (30 m clipping window) with 0.3% Cu composites and 2023 Cu Resource model









JORC CODE 2012 EDITION - TABLE 1

Section 1 Sampling Techniques and Data

This Table 1 refers to 2023 Exploration Drilling & Induced Polarisation (IP) Survey results completed at the Wallace North

CRITERIA	JORC CODE EXPLANATION	COMMENTARY
CRITERIA Sampling techniques Sampling techniques	 JORC CODE EXPLANATION Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information. 	 COMMENTARY The company conducted an eight-hole infill and resource extension RC drilling program near its Wallace North res of drilling. The drilling was completed by Associated Exploration Drillers Pty Ltd. The program was undertaken to identify down down-dip and down-plunge extents of mineralisation intersected in confidence in the resource. Sample Representivity Most holes are oriented appropriately to give optimal sample representivity, drilled mostly perpendicular to the inter towards the target mineralised horizon/structure; however downhole widths will in most instances not represent to RC drilling techniques returned samples through a fully enclosed cyclone setup. 1m interval RC samples were hori representative 3-4kg sub-sample and collected in a pre-numbered calico bag. The remaining portion of sample (1 RC duplicate sub-samples were rifle split from the bulk bag and are not considered an exact field duplicate of the samples were noted as dry. Assaying All samples are submitted to Australian Laboratory Services (ALS) an ISO certified contract laboratory in Mount Iss be forwarded to other ALS sites (including Townsville or Brisbane) to ensure adequate turnaround times are achie Townsville. Mt Isa sample preparation is via SPL-21 (split sample using riffle splitter - standard splitting procedure) sample. Qc specification of 85% <75.m. Samples greater than 3kg are split to pulverizing and the remainder ret All samples were pulverised and all master pulps selected for return to site and storage. Selection for assaying was guided by the use of a portable XRF instrument (Vanta-series; >500ppm Cu and 500pp veined/faulted lithological units. No pXRF results are reported in this announcement. TNC 2023 IP Survey The company conducted a dipole-dipole induced polarisation (IP) survey at Wallace North and Mount Norma. One for 1.0 line-km were completed between 4 May to 23 Ma
		 The 2012 Fixed Loop Electromagnetic (FLEM) survey was completed for Exco Resources by Outer Rim Exploration survey consisted of five lines for a total of 5.5-line kilometers using a single transmitter loop. EM Geophysics report equipment:

source. The program includes 8 holes for a total of 1,838m

historical exploration/resource drilling, and to increase

rpreted strike and dip of the mineralised body and oriented true widths.

mogenized and collected by a rotary splitter to produce a 15-20kg) is also retained in a green sample bag on drill site. a samples from the cone splitter on the rig. All duplicate sub-

a. Dependent on production capacity, selected batches may eved. Sample preparation varies between ALS Mt Isa and

verized via PUL-32m (Pulverise 500g split to better than 85%

and pulverized via PUL-23 (Pulverise up to 3kg of raw tained).

ppm As), visual estimation of sulphide mineralization and

e line each at Wallace North for 1.45-line km and Mt Norma ophysics report in this release was undertaken using the

n Services over the current Wallace North Prospect. The ort in this release was undertaken using the following



CRITERIA	JORC CODE EXPLANATION	COMMENTARY
		 LandTEM SQUID TEM system using an impulse response (square-wave signal) at 1.25Hz base frequency. Crone eTrans transmitter LandTEM and Smartem 24 receiver
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc). 	 2023 TNC Drilling The drilling was completed using a SCHRAMM 660 drill rig 350psi/1150cfm onboard compressor, 350-500psi/9 (1000psi/1800cfm). Drilling diameter is 5.5 inch RC hammer (face sampling bits are used). Drillhole depths ranged from 180m to 299m. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM) Not applicable
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 2023 TNC Drilling For recent RC drilling no significant recovery issues for samples were observed. Drill chips collected in chip trays are considered a reasonable representation for logging of the entire 1 m interva Best practice methods were used for RC to ensure the return of high-quality samples. As no significant recovery is acceptable limits. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM) Not applicable.
	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography The total length and percentage of the relevant intersections logged. 	 2023 TNC Drilling RC chips were geologically logged in full. All RC holes have been logged by geologists to industry standard for lithology, mineralisation, alteration, and other Logging of RC chips has been completed to the level of detail required to support future Mineral Resource Estimation in this release. Observations were recorded in a field laptop, appropriate to the drilling and sample return method and is qualitative validated through use of excel macros and drillhole validation methods in Micromine Origin 2023. Observations were recorded appropriate to the sample type based on visual field estimates of sulphide content a All chips have been stored in chip trays on 1m intervals. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM) Not applicable.
Sub- sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. 	 2023 TNC Drilling All RC samples are rotary split at the cyclone to create a 1m sample of 3-4 kg. Samples are collected in prenumb cyclone on the drill rig. All samples were noted as dry. RC duplicate sub-samples were rifle split from the bulk bag and are not considered an exact field duplicate of the samples were noted as dry.

900-1150cfm Auxiliary combi and 8V Booster

al. issues were observed, sample bias is assumed to be within

er geological features as appropriate to the style of deposit. ation. However, no Mineral Resource Estimation is reported

and quantitative, based on visual field estimates. Logs were

and sulphide mineral species.

bered calico bags via the rotary splitter underneath the

e samples from the cone splitter on the rig. All duplicate sub-



CRITERIA	JORC CODE EXPLANATION	COMMENTARY
	 Quality control procedures adopted for all sub- sampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	 The remaining sample is retained in green plastic bags at the drill site and laid out in sequence from the top of th A sample is sieved from the reject material and retained in chip trays for geological logging and future reference. All samples are submitted to ALS Mount Isa; dependent on production capacity, selected batches may be forward Brisbane) to ensure adequate turnaround times are achieved. Sample preparation varies between ALS Mt Isa and Townsville. Mt Isa sample preparation is via SPL-21 (split sample using riffle splitter – standard splitting procedure) and pulv passing 75um). Townsville sample preparation is also via SPL-21 (split sample using riffle splitter – standard splitting procedure) sample. QC specification of 85% <75um. Samples greater than 3kg are split to pulverizing and the remainder re All RC samples are submitted to the lab for pulverization however samples are selected for assaying using the Va Cu/As or across lithological units relative to the deposit style e.g. Quartz-carbonate veining and across lithologica Field duplicates were taken from a rifle split from the bulk bag. The comparison of the original cone split, and rifle Au. All duplicates are within expected range, less than 15% difference for Cu while Au variability is under 30% an very low level and therefore are considered acceptable and the materials sampled are representative of the in-sit TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM)
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 Not applicable. 2023 TNC Drilling Samples are dried, crushed and pulverized prior to digestion and assaying as appropriate. ALS is engaged to complete laboratory analysis via ME-ICP49 (Aqua Regia sample digestion based on ME-ICP41s various OR and MI lab client requirements, reporting 11 element full suite Ag, As, Ca, Cu, Fe, Mg, Mo, Pb, S, Co, Z Gold assays are completed via A425. 30g Fire Assay. The Lab utilises industry standard internal quality control measures including the use of internal Standards, Cont QAQC quantities relating to each lab batch are detailed in the Table below. Analytical standards are inserted at a certified reference material ("CRM") of sulphide or oxide material sourced from OREAS with known gold and copp sequence was at the discretion of the logging geologist. Standards were selected to match the anticipated assay sampling sequence. Coarse blanks were inserted at a rate of ~5 for every 100 samples. The location of the blanks in the sampling sequence. Standards, blanks, and duplicates were reviewed for each batch. Most batches as detailed in table below met th duplicates. Seven batches had a slightly lower insertion rate for standards, while 3 of the 21 batches contained I QAQC samples was higher than the ideal insertion rate and deemed adequate for the reporting of exploration res of 15D. Certified standard for gold were all within 3SD of the expected value. Multiple blanks for reported results were also checked against expected values. Where native copper was obser flushes were also requested to ascertain any potential for contamination from previous contamination is not considered material sign the respected value. Multiple blanks for reported results were also checked against expected values. Where native copper was obser flushes were also requested to ascertain any potential for contamination form previous contamination is not considered material 3D. few returned very low order copper contami

he hole to the end of the hole until assay results are received. and stored at the company's offices in Cloncurry. rded to other ALS laboratories (including Townsville or

verized via PUL-32m (Pulverise 500g split to better than 85%

) and pulverized via PUL-23 (Pulverise up to 3kg of raw etained).

anta Series Portable XRF reporting greater than 500ppm al contacts. No pXRF results are reported in this release. le split duplicates have no unexpected high variations in Cu or nd those with the high percent differences in Au are mostly itu material.

s methodology but with upper reporting limits specific to Zn).

trol Blanks and duplicates/repeats.

a minimum rate of 6 for every 100 samples, using 10-60g, per values. The location of the standards in the sampling y grade of the samples on either side of the standard in the

equence was at the discretion of the logging geologist. No his is not considered an issue. ALS internal pulp blanks

ne recommended insertion rate for all standards, blanks, and no field duplicates. However, the overall rate of insertion of sults.

with all returning slightly lower than 3SDs. A sole sample of turned a result of 80 ppm above 3SD which is only half of

e considered adequate for the reporting of exploration

ved in RC Chips, insertion and analysis of laboratory quartz

higher-grade samples (20-60 ppm Cu above 3SD). The

ethods, less cleaning being done prior to doing the quartz ely the cause of the issue.

than 30% difference having higher variability but mostly at rence of 109% likely due to the presence of coarse gold.



CRITERIA	JORC CODE EXPLANATION				COMMI	ENTARY			
						Inse	rtion rate per 100 sa	amples	
		Hole ID	Dispatch No	Batch No	Analytical standards (CRMs)	Coarse Blank	Field duplicates	#orig	#Orig+QC
		WNR0001	335701	TV23174969	8.70	4.35	8.70	23	28
		WNR0001	335801	TV23174977	4.00	8.00	2.00	50	57
		WNR0001, 0002, 0003	335901	TV23175017	6.12	6.12	4.08	49	57
		WNR0003	336001	MI23181196	5.13	5.13	5.13	39	45
		WNR0003	336101	MI23181200	7.89	5.26	5.26	38	45
		WNR0003, 0004	336201	MI23181203	8.16	6.12	2.04	49	57
		WNR0004	336301	MI23181236	5.36	5.36	3.57	56	64
		WNR0004	336401	MI23181242	4.17	6.25	2.08	48	54
		WNR0002, 0006, 0007	336501	TV23191498	9.09	6.06	6.06	33	40
		WNR0002	336601	TV23191500	6.15	3.08	3.08	65	73
		WNR0002	336701	TV23191501	7.41	3.70	3.70	27	31
		WNR0005	336801	TV23191503	7.32	4.88	2.44	41	47
		WNR0005	336901	TV23191504	6.06	6.06	Nil	33	37
		WNR0007	337001	TV23191506	5.41	5.41	2.70	37	42
		WNR0007	337101	TV23191507	4.88	4.88	2.44	41	46
		WNR0006	337201	TV23191508	6.25	6.25	3.13	32	37
		WNR0006	337301	TV23200198	5.88	5.88	1.96	51	58
		WNR0008	337401	TV23200203	9.09	9.09	Nil	11	13
		WNR0008	337501	TV23200207	7.14	7.14	3.57	28	33
		WNR0008	337601	TV23200210	6.56	4.92	3.28	61	70
		WNR0008	337701	TV23200215	4.76	4.76	Nil	21	23

ASX: TNC



CRITERIA	JORC CODE EXPLANATION	COMMENTARY
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	 TNC 2023 IP Survey One line each at Wallace North for 1.45-line km and Mt Norma for 1.0 line-km of dipole-dipole induced polarizatic 2023 by Australian Geophysical Services (AGS). The Mt Norma survey line was oriented ENE (074°) and the Walla Equipment used included a GDD TXV SkVA Transmitter (Tx) and a SMARTem 24 Receiver system (Rx). Receiving electrodes were buried aluminium plates. The survey configuration used for all lines was standard roll-along dipol receiver channels (N level). The IP survey was completed using a Dipole-Dipole (DDIP) configuration. A dipole spacing of 50 m was utilised at Nt Norma and 50 m and 100 m utilised at Wallace North. Data QAQC and analysis was completed by RMAM Geoscience. Raw IP data supplied by AGS was imported into TQIPdb, an IP data quality control and processing software packa, inspected and any noisy decays, bad repeat readings, or readings with very low primary voltage were flagged in th used at any subsequent stage of the processing. 2D inversion modelling was completed on each DDIP line using Res2D produced by Geotomo Software. 2012 Fixed Loop Electromagnetic (FLEM) The 2012 Fixed Loop Electromagnetic (FLEM) survey was completed for Exco Resources over the current Wallace of 5.5 line kilometers using a single transmitter loop. Equipment used included a LandTEM Squid sensor, SMartem receiver, and Crone eTrans transmitter. The single transmitter loop was 700 m x 400 m in size. The receiver lines were oriented NNW to SSE and spaced 50 m. Data quality and subsequent numerical modelling was completed by Mitre Geophysics. 2023 TNC Drilling Field sample logs were collected using laptops and captured in validated excel entries, and uploaded into the com poligital Assay results have been applied to the results. No twin holes have been completed. 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM) No vi
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 2023 TNC Drilling Drill hole collar location of the data samples collected via a Trimble DGPS (MGA2020), accurate to within 10cm. Downhole surveys completed using a Reflex North-seeking Gyro, completed as 30m interval single shots and/or of TNC 2022 IB Survey
		 IP locations were obtained using a Garmin handheld GPS in GDA2020 MGA Zone 54K and local grid.

on survey (DDIP) were completed between 4 May to 23 May, ace North line NNW (346.5°). electrodes were stainless steel plates and transmitter ble-dipole (DDIP) with 50 m receiver dipoles and up to 16 age. Individual chargeability decays from each station were he database. Any readings flagged for low quality are not e North Prospect. The survey consisted of five lines for a total d 150 m apart. Station spacing along lines was 25 m and/or mpany Access Database, validated by company personnel. y personnel.

I.

continuous measurements at end of hole.



	CRITERIA	JORC CODE EXPLANATION	COMMENTARY
	D		 Topography data was integrated into the TQIPdb databases. For Wallace North, Shuttle Radar Topography Missio Explorer portal was utilised.
	a spacing and distribution	Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied.	 2023 TNC Drilling Data spacing is sufficient for the reporting of results. No Mineral Resource or Ore Reserve estimations are being reported. No sample compositing has been applied. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM)
(O)			Not applicable.
	entation of data in relation geological structure	Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. The measures taken to ensure sample security.	 2023 TNC Drilling The drilling orientations were generally in line with the historical drilling data. There are numerous structures which dipping. The drilling orientation is considered appropriate and is expected to have introduce minor bias in interce Estimated True widths are presented in this release with the aim to give a reflection of the mineralised widths. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM) IP & FLEM lines have been oriented as close as possible to right angles to the main mineralisation trends. 2023 TNC Drilling Samples were secured by staff from collection to submittal at ALS Mt Isa. TNC 2023 IP Survey & 2012 Fixed Loop Electromagnetic (FLEM)
(D)			Not applicable.
Aud	lits or reviews	The results of any audits or reviews of sampling techniques and data.	No review or audits have taken place of the data being reported.

on (SRTM) elevation data downloaded from the USGS Earth

ich have been identified to date which are moderately ept width based on the current geological information.



Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section)

CRITERIA	JORC CODE EXPLANATION	COMMENTARY
Mineral tenement and land ten status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 Wallace North (formerly Kangaroo Rat) lies on ML 2695 and ML 90236 and lies approximately 1 k Wallace copper mine. The project is centred at approximately 474534mE 7695886mN (MGA Zon The project is in west central Queensland, Australia, approximately 30km Southeast of Cloncurry. Cloncurry or Mount Isa. The area is well serviced by sealed Barkly Highway from Mount Isa to Clon from Cloncurry to the project area. Existing station and exploration tracks provide good access to the tenements. Movement is very li and wet tracks. The Wallace North deposit is located on Mining Lease - ML2695, that covers an area of 2.136 he covers 318.30 hectares and expires on 31/05/2026 owned by True North Copper Pty Ltd.
Exploration done by other part	 Acknowledgment and appraisal of exploration by other parties. 	 Modern exploration commenced at Wallace North in 1990 by Union Oil Development Company (U Exploration has subsequently been carried out by Ashton Gold Limited (Ashton), Cloncurry Mining (Haddington), and most recently by Exco. In 1990 UODC aimed to define new geological targets for further follow-up work with a focus on get North as a prospective area due to the various small historical workings in the immediate area. Ut holes were drilled for 1,366m. 441 soil samples taken and a 60 m long trench that cut across the Detailed geological mapping at a scale of 1:25,000 was completed over the area in 1991 (Barnes 1992 - 1996 Ashton Gold - After purchasing the project from UODC in early 1992, Ashton Gold cot (NQ core size) for 239.25 metres. 1996 - 2001 Cloncurry Mining Company NL (CMC) and its subsidiary Great Australian Mining Cor exploration work they subsequently conducted was not well documented and there appears to be CMC drilled two RC holes for 102 metres in August 1996 and 24 RAB holes. Prior to CMC going in into including Mount Isa Exploration (MIMEX) and Eagle Mining Corporation (EMC) who drilled 23 I 2001 - 2002 Wedgetail Exploration NL (WTE) made a successful bid for the package of tenement tenement package was transferred to Haddington Gold Pty Ltd (Haddington) in August 2003. 2003 - 2006 Haddington - In 2003 Haddington reviewed the resource and attempted to verify th Haddington also drilled 3 RC holes in the resource area and several RC and RAB holes in the surri 2006 - 2016 Exco - In August 2006 Exco acquired Haddington and incorporated the Wallace Nor of 16 Diamond holes (1,796m) and 74 RC holes (4,030m) over a series of campaigns in 2006, 2(177 metres were also drilled in 2006. Exco was purchased by Washington H Soul Pattinson (WHSP) in late 2012 and later became a wh of Exco a drilling campaign was undertaken at Wallace North to improve data density as a prelude confidence.
Geology	 Deposit type, geological setting and style of mineralisation. 	 The Wallace North project is located in a structurally complex area where mafic volcanic (metabase black shale) rocks of the Toole Creek Volcanics (upper Soldiers Cap Group) are folded about an E-Home Anticline) and cut by a NW-SE-striking fault that is connected to a more substantial, >20 km covered by Quaternary sediments of the Elder Creek drainage system. Wallace North Cu-Au mineralisation is contained within a poorly exposed shear zone that trends E structure is semi-exposed over about 100 m in old workings, however drilling indicates that the st zone appears to demarcate the general contact between a mafic volcanic dominant sequence and the rocks have been mylonitised and variably altered. The main rock types include metadolerite-be propylitic-argillic to silification along fracture and vein salvages (Barnes, 2012). Disseminated to massive, dull to metallic chalcocite mineralisation dominates in the partially oxid dominant Cu species within fresh rock, disseminated or present as small segregations. Gangue m malachite dominant oxide Cu zone is present close to surface. Mineralisation is often seen at the contact between intercalated shale and volcanic lithologies. Pr carbonate veins along basalt/black shale contacts. The series of NW trending structures that inte

km to the north of the Wallace South Au deposit and old ne 54, GDA94 datum).

. Access is by aircraft via an all-weather airstrip into ncurry and then the Flinders and Landsborough Highways

mited during the wet season due to flooded watercourses

ectares and expires on 31/03/2026, and ML90236, that

IODC) when the prospect was known as Wallace. Company (CMC), Haddington Resources Limited

gold and copper mineralisation. They identified Wallace IODC explored the area between 1990 and 1992. 21 RC e shear zone was dug, geologically mapped and sampled. Ps, 2012).

ompleted 8 RC holes for 603 metres and four diamond tails

mpany NL acquired the mining lease in 1996. All the e no Mines Department Reports available for this period. nto liquidation in 2001, several joint ventures were entered RAB holes in the area.

ts which passed into its control in December 2001. The

ne assay results by resampling RC chips still in the field. rounding area.

rth deposit into its Cloncurry Project. Exco completed a total 2007, 2011 and 2012 at Wallace North. 31 aircore holes for

holly owned subsidiary of WHSP. Following WHSP ownership e to re-estimation of the resource to a higher level of

salt) and sedimentary (calcareous siltstone and mudstone, -W-trending, regional-scale anticline (possibly the Mountain n-long, N-S-striking fault. Much of the project area is

ENE-WSW with a steep WNW to vertical dip. The mineralised tructure extends in both directions under cover. The shear a sediment dominant sequence. Within the shear zone, basalt, shale, siltstone and quartzite. Alteration ranges from

lised transitional weathered zone. Chalcopyrite is the ninerals include carbonate, quartz, and pyrite. A minor

imary chalcopyrite mineralisation is associated with quartzrsect/cross-cut the strata at an oblique angle may have



CRITERIA	JORC CODE EXPLANATION	COMMENTARY
		 provided a pathway for the mineralising fluids to cross the stratigraphy. It is likely that the higher g oblique structures intersect the shale/basalt contacts creating small flexures. This is supported by trending structures intersect strata-form mineralisation. Mineralisation comprises two main sub-vertical ENE-WSW approximately parallel tabular zones of mineralisation occur in the footwall and hanging wall, and along strike to the WSW and ENE, which zone(s).
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case. 	 Information on drillholes featured in the announcement are provided in the main body of this announcement are provided in the main body of the provided in the main body of the provided in the
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 Intercept calculations used a cut-off grade of 0.3% Cu. The maximum consecutive waste (below 0. included waste. Significant downhole intercepts are over 1% Cu & 3% Cu, length weighted average. The maximum exceed 3m however there is no limit to included waste. Gold is reported as a length weighted average within the copper intercepts. No metal equivalent values are used. All intervals have been length weighted averaged. All significant new drillhole assay data of a material nature are reported in this release.
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 Both currently reported and historical drillholes have been primarily oriented between [143 - 162 orthogonal intersection of the moderately north-northeast dipping mineralized structures. Confidence in the geometry of main zones mineralisation intersections is good and consequently,
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	 Please refer to the accompanying document for figures and maps.
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	 Representative reporting of low and high grades has been delivered within this report. Intersection lengths and grades are reported as down-hole, length weighted averages. Refer to the list of significant drill hole results in the accompanying report. All significant results us

grade and more consistent mineralisation occurs where y common anomalous Cu/Au grades where the NW

mineralisation. Several additional minor zones of h may constitute faulted offsets of the adjacent main

ouncement, Figure 7, Table 2.

.3% Cu) does not exceed 2m however there is no limit to

consecutive waste (below 1% Cu & 3% Cu) does not

degrees] at moderate dips in order to provide the most

true widths are provided in this release within this zone.

sing the criteria described above.



CRITERIA	JORC CODE EXPLANATION		COMMENTARY
Other substantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	-	Refer to TNC news release dated: 28th February 2023 – Acquisition of True North Copper Assets; Refer to True North Copper. ASX (TNC): Release 16 June 2023, Prospectus
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 		Further work planned includes additional drilling, metallurgy, IP surveys, downhole geophysics and resources and ore reserves.

d other activities associated with definition of mineral