

26 April 2024

HIGH PRIORITY REE CONCESSIONS GRANTED IN BRAZIL

- Goiás state concessions 860164-5/2024 covering 3,262Has have been granted for three years
- The area is a high priority target for rare earth elements (REE) in ionic clays or carbonatites
- Soils and stream sampling program to commence soon

Patagonia Lithium Ltd (ASX:PL3, Patagonia or **Company)** is pleased to advise that it has been granted exploration rights for three years on the two applications it made in the Goais state adjacent to the CMOC niobium mine.

REE Ranking




Figure 1. Ranking of the 5 concession packages granted and applied for REE




Figure 2. The interpreted magnetometry and radiometric data shows the high potential areas in white and the proximity to the Catalão carbonatite deposit. The isovalues 2000 represent the heat intensity from the contact metamorphism depositing the rare earths from fluids.

State	Mineral Tenement	Ranking	Parameters
GO	860.164/2024	1	It is situated within the local anomaly of Uranium and Thorium. This anomaly encompasses the metasomatic zone identified through ternary geophysical interpretation based on MVI, ASA, and DZ, as well as the theoretical model derived from the proportions observed in Araxá - MG. The local anomaly can be divided into two parts. The first of greater magnitude, aligns with the 125 AZ alignment and coincides with the confluence of the drainage network in a topographic low, suggesting a potential accumulation of radioactive minerals rich in Rare Earth Elements. The second anomaly, located to the northwest of the area, also enriched in Uranium and Thorium, sits atop a topographic high. This anomaly may represent an anomalous finitized zone, when associated with the context of the host rock (schist).

Sto	ate	Mineral Tenement	Ranking	Parameters
G	C	860.165/2024	2	It is situated within the regional Uranium and Thorium
				anomaly, bordering the Catalão I carbonatite. The
				anomaly's pattern is concentric to the core of the
				carbonatite. This anomaly encompasses the zones
_ 11				of silicification and metasomatism identified through
				MVI, ASA, and DZ analyses, as well as those derived
				from the theoretical model based on the
				proportions observed in Araxá-MG.
		le 1: Summary of the tar		
	The	Company is securi	ng a field	crew to spend 4-5 days soil and rock chip sampling o
	ma	pping the faults at	a finer sco	ale at 860164-5/2024 for rare earths. GE21, our geold
	COI	nsultants, will identif	y and de	scribe rock outcrops, analysing the local geology o
	cor	relating to the geo	physics w	ork completed. For ionic clays, it will require observ
	and	d describing the we	athering r	mantle that may contain REE. A pan concentrate sur
		=	_	- E-bearing minerals, such as monazite, xenothermite c
		stnasite in ionic clay	•	_
	οu.	on asire in terme etal,	3 (3GP10III	
] [
		·		nan commented "We are now on the ground and c
			_	re earth elements with the first stage being soil samp
	cla	ys and mapping to	sure up o	our drill targets. Being so close to the Catalao rare ed
	de	oosit is exciting in the	at we are	in the right area and the geophysics tells us so. Catc
	I is part of the Alto Paranaíba igneous province in the Goias Province of Brazil. Curren			
	niobium is produced in the complex as a by-product of the Chapadão phospha			
	mine. Monazite, the most common rare earth mineral identified in the mine feed, occ			
	as Ce-rich and La-rich varieties that can be easily distinguished. This is what we will			
	targeting."			
	131	9° · · · · 9•		
	۸	thorized for release	by the Pe	ard of the Company
	ΑU	inonsed for release	Dy III C DO	ard of the Company.
	_			
		further information	please co	ontact:
		lip Thomas		
		cutive Chairman		
	Pat	agonia Lithium Ltd		
	M: -	+61 433 747 380		
	E: <u>p</u>	hil@patagonialithiur	<u>m.com.au</u>	

Table 1: Summary of the target areas

Our socials - twitter@pataLithium, Instagram, facebook, pinterest and youtube

Competent Person Statement

The information in this announcement that relates to exploration results is based on, and fairly represents information compiled by Phillip Thomas, MAIG FAusIMM, Technical Adviser of Patagonia Lithium Ltd and is Executive Chairman, who is a Fellow of the Australasian Institute of Mining and Metallurgy. Mr Thomas has sufficient experience relevant to the style of mineralisation and type of deposit under consideration, and to the activity which he has undertaken, to qualify as a Competent Person as defined in the 2012 Edition of the Joint Ore Reserves Committee (JORC) Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr Thomas consents to the inclusion in this announcement of the matters based on this information in the form and context in which it appears.

About Patagonia Lithium Ltd

Patagonia Lithium has two major lithium brine projects – Formentera/Cilon in Salar de Jama, Jujuy province and Tomas III at Incahuasi Salar in Salta Province of northern Argentina in the declared lithium triangle. It has also applied **for 41,746 Has** of concessions exploring for **ionic REE clays**, **Niobium**, **and lithium in pegmatites**. Four exploration concession packages have been applied for. 830178/2024 has been granted.

Since listing on 31 March 2023, recharge water analysis, surface sampling and MT geophysics have been completed in preparation of an upcoming drill program at Formentera, where the first well JAM 24-01 has been completed with MT Geophysics at Tomas III showing low resistivity and very prospective. In July 2023, a 13 hole drill program was submitted for approval which was granted in January 2024. Samples as **high as 1,100ppm lithium** (2 June 2023 announcement) were recorded at Formentera and resistivity values as low as 0.3Ω .m were recorded during the MT Geophysics survey at Formentera making the project highly prospective. The Company confirms it is not aware of any new information or data that materially affects the information in this announcement.

JORC Code, 2012 Edition – Table 1 report Patagonia Lithium Ltd ASX:PL3 Goias State applications 830164/2024 and 830165/2024

Section 1 Sampling Techniques and Data

(Criteria in this section apply to all succeeding sections.)

Criteria	JORC Code explanation	Commentary
Sampling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) 	 There was no sampling as the application concession 830164/165 is still waiting to be granted. Publicly available radiometric data was acquired from the bureau of mineral resources in the state of Goias, Brazil. The geophysics that measure Uranium, Thorium and Potassium were derived from satellite data accessing the Data from CPPLL, Codemge/Codemig, Metago, and others projects publicly available. Acquisition and processing of LANDSAT, Sentinel 1, ASTER scenes, pre-processing, spectral analysis and evaluation/prioritization of results and the evaluation and processing of geophysical data was undertaken. Public data from technical papers, the Catalao REE deposit and references on field sampling, drilling, geological lithologies and distances from source were collated.

Criteria	JORC Code explanation	Commentary
	may warrant disclosure of detailed information.	
Drilling techniques	 Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face- sampling bit or other type, whether core is oriented and if so, by what method, etc). 	No drilling was undertaken.
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 No sampling was undertaken. The geophysics data analysed that included radiometric, magnetic and gravity data is publicly available.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	No logging was undertaken but the Artificial Intelligence model did reference sampling ratios of elements and distances from deposits of occurrences of rare earths. See sample of table below for REE. Araxa is a closeby deposit. Carbonatte

Criteria	JORC Code explanation	Commentary
Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all subsampling stages to maximise representivity of samples. Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the material being sampled. 	Not applicable as no sampling undertaken.
Quality of assay data and laboratory tests		Raw data from the magnetic surveys was reprocessed into 1D inversions.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage 	Not applicable as no sampling undertaken.

Criteria	JORC Code explanation	Commentary
	(physical and electronic) protocols.Discuss any adjustment to assay data.	
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 	 Accuracy of the data is between 50-150m with data obtained at 400-600m intervals. Gravity data is more unreliable and thus was given a lower ranking.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 	400-600m spacing depending on the satellite data used.
Orientation of data in relation to geological structure		Orientation was perpendicular to earth surface.
Sample security	The measures taken to ensure sample security.	Not applicable as no sampling undertaken.
Audits or reviews	 The results of any audits or reviews of sampling techniques and data. 	Not applicable as no sampling undertaken.

Section 2 Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section.)

Criteria	JORC Code explanation	Commentary
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings. The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area. 	 Mining concession 830.164/2024 and 830165/2024 are still pending being granted in the state of Goais, Brazil – the concessions when granted will be 100% owned by Patagonia Lithium subsidiary PL3 Mineracao Brazil Ltda. The licence when granted is for a 3 year period unless it is renewed for a further period. It has been referenced for lithium exploration. Both concessions cover a total of 3,262 Has.
Exploration done by other parties	Acknowledgment and appraisal of exploration by other parties.	 No exploration has been undertaken on this concession application. Adjacent to 830164/2024 is the CMOC Niobium mine. This is a private operation and information is not readily available on drill core data.
Geology	Deposit type, geological setting and style of mineralisation.	 The first target zone, of greatest importance, is the metasomatic zone. The second, an anomaly of Thorium and Uranium located within a structure aligned to the 125-degree Azimuth, is characterized by a topographic low that may be associated with the accumulation of radioactive minerals (possibly Monazites?) and potentially, Rare Earth Elements. The third zone, the second anomaly situated northwest of the area, also enriched in Uranium and Thorium, is located at the summit of a topographic elevation. This anomaly may represent an igneous body with chemical characteristics similar to carbonatite, albeit smaller, not identified in the MVI magnetic geophysics data. The Catalão I alkaline—carbonatite—phoscorite complex (ferro niobium mine adjacent) contains both fresh rock and residual (weathering-related) niobium mineralization. The fresh rock niobium deposit consists of two plug-shaped orebodies named Mine II and East Area, respectively emplaced in carbonatite and phlogopitite. Together, these orebodies

Criteria	JORC Code explanation	Commentary
		contain 29 Mt at 1.22 wt.% Nb2O5 (measured and indicated). In closer detail, the orebodies consist of dyke swarms of pyrochlore-bearing, olivine-free phoscorite-series rocks (nelsonite) that can be either apatite-rich (P2 unit) or magnetite-rich (P3 unit). Dolomite carbonatite (DC) is intimately related with nelsonite. Natropyrochlore and calciopyrochlore are the most abundant niobium phases in the fresh rock deposit. Pyrochlore supergroup chemistry shows a compositional trend from Ca–Na dominant pyrochlores toward Ba-enriched kenopyrochlore in fresh rock and the dominance of Ba-rich kenopyrochlore in the residual deposit. Carbonates associated with Ba-, Sr-enriched pyrochlore show higher δ18OSMOW than expected for carbonates crystallizing from mantle-derived magmas. We interpret both the δ18OSMOW and pyrochlore chemistry variations from the original composition as evidence of interaction with low-temperature fluids which, albeit not responsible for the mineralization, modified its magmatic isotopic features. The origin of the Catalão I niobium deposit is related to carbonatite magmatism but the process that generated such niobium-rich rocks is still being determined and might be related to crystal accumulation and/or emplacement of a phosphate–iron-oxide magma.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: easting and northing of the drill hole collar elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar dip and azimuth of the hole down hole length and interception depth hole length. If the exclusion of this information is justified on the basis that the 	 The main geophysical data coming from georeferenced PDFs, highlighted by the correlation between samples is the F parameter, followed by the thorium-uranium ratio. There is a high correlation between Kd potassium factor and Thorium.

Criteria	JORC Code explanation	Commentary
	information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.	
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent values should be clearly stated. 	 Not applicable – 1D inversion was used to better define the fenitization in the radiometric and magnetic surveys.
Relationship between mineralisation widths and intercept lengths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	Not Applicable as no drilling was undertaken.
Diagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	Not Applicable as no drilling was undertaken.
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	Not Applicable as no drilling was undertaken.
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	See above for detailed geophysical results - Carbonatites and alkaline-silicate rocks are the most important sources of rare earth elements (REE) and niobium (Nb). Cooling and crystallizing carbonatitic and alkaline melts expel multiple pulses of alkali-rich aqueous fluids which metasomatize the surrounding country rocks, forming fenites during a process called fenitization. We are exploring for these rocks. These alkalis and volatiles are original constituents of the magma

Criteria	JORC Code explanation	Commentary
		 that are not recorded in the carbonatite rock, and therefore fenites are a key focus of a carbonatite system and our exploration efforts. RGB 3,2,10 – ratio 4,12 – PCA band 8,3 were used to identify lithium minerals. Sentinel-2 imagery (low resolution – pixel 32m) yielded poor results so we will use Hi Res spectral.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 We intend to commence soil sampling and rock chip sampling as soon other the exploration concessions are granted 830164/2024 and 830165/2024.