



Strategic Expansion of Kalahari Copper Belt Portfolio with Applications Lodged for Key Botswana Licences

New Prospecting Licences sit adjacent to the Damara Copper Project in Namibia, where drilling has commenced recently

Perth, Western Australia – 29th January 2025 – Noronex Limited (**Noronex** or the **Company**) (**ASX: NRX**) is pleased to advise that it has lodged two strategically located Prospecting Licence Applications in Botswana, adjacent to its Damara Copper Project in Namibia.

Highlights

- RC drill rig has mobilised to test a number of Basement targets in the Damara Copper Project.
- Noronex has applied for two 100%-owned Prospecting Licences in Botswana adjacent to this drilling.

Noronex Chief Geologist Bruce Hooper commented:

“With the drill rig mobilising to test prospective new targets in Namibia at our Damara Project, we are planning for success and have applied for the ground adjacent to this drilling in Botswana to cover further geophysical targets.

Applying the Central African Copper Belt’s basement deposit models in both Namibia and Botswana could represent a major breakthrough for the potential of the Kalahari Copper Belt.

We await the results of the drilling with high expectations.”

Botswana Applications

The northern margin of the Kalahari Copper Belt in Namibia and Botswana is covered by shallow Kalahari sands and has never been drill tested. Modelling shows significant similarities with the basement-hosted deposits in the Central African Copper Belt in Zambia and Congo.

Noronex has lodged applications for two Prospecting Licences in Botswana with the Department of Mines to cover extensive parts of this prospective region. The applications, made under a proposed 100%-owned subsidiary of Noronex, have been accepted and are being assessed. The Licences cover nearly 1,500 square kilometres of previously unexplored terrane. Based on extrapolation, the area is expected to be covered by between 10 and 80m of Kalahari sands.

The applications under Senyetse Resources (Pty) Ltd are PL000030/2025-APP for 721.87 square kilometres and PL000032/2025-APP for 745.40 square kilometres. A new subsidiary, Tilodi Metals Botswana Proprietary Limited, has been set up in-country.




Figure 1: Regional aeromagnetic image of the Kalahari Copper Belt in Namibia with the current Noronex projects showing Fiesta in the west and a number of magnetic complexes in the north in the Damara project.

The Otjiuapahuri Prospect in Namibia lies on the Namibia-Botswana border in an isolated region of the Hoveka Traditional Authority. A camp has been set up and drilling has commenced, intersecting 70m of the Kalahari sand as expected.

The magnetic interpretation shows a complex magnetic signature with a number of reverse polarity bullseye circular features. Interpretation of the recent gravity survey has been very informative, although it is unclear what the basement features are geologically as no drilling has ever been completed in this region.

It is considered there are both high magnetic-dense stratigraphic units but also Intrusive complexes. There is a high probability that part of the complexity in the signatures is due to alteration through movement of hydrothermal fluids. This could be associated with mineralisation.

In Botswana similar extensions of the belt are expected from government survey interpretations.

– ENDS –

Authorised by the Board of Directors of Noronex Limited

For further information, contact the Company at info@noronex.com.au or on (08) 6555 2950

Investor inquiries:
Bruce Hooper/James Thompson

Media inquiries:
Nicholas Read
Read Corporate
M: 0419 929 046

About Noronex Limited

Noronex is an ASX-listed copper company with advanced projects in the Kalahari Copper Belt, Namibia, and in Ontario, Canada, that have seen over 180,000m of historical drilling. The Company currently has a JORC 2012 Resource of 10Mt @ 1.3% Cu at its Witvlei Project¹.

The Company plans to use modern technology and exploration techniques to generate new targets at the projects and grow the current Resource base.

Competent Person Statement – Exploration Results

The information in this report that relates to Exploration Results is based on information compiled by Mr Bruce Hooper who is a Registered Professional Geoscientist (RPGeo) of The Australian Institute of Geoscientists. Mr Hooper is a consultant to Noronex Ltd and has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity which he is undertaking to qualify as Competent Person as defined in the 2012 Edition of the Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves. Mr Hooper consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

Any information contained in this report that relates to a Mineral Resources has been extracted from a previously released announcement dated 8/03/2021 ("Announcement"). The Company confirms that it is not aware of any new information or data that materially affects the information included in the Announcement, and that all material assumptions and technical parameters underpinning the estimates in the Announcement continue to apply and have not materially changed.

¹ Refer to ASX Announcement dated 8 March 2021.

APPENDIX 1: JORC COMPLIANT EXPLORATION REPORT

The following information is provided in accordance with Table 1 of Appendix 5A of the JORC Code 2012 – Section 1 (Sampling Techniques and Data), Section 2 (Reporting of Exploration Results).

JORC Code 2012 Edition – Table 1

Section 1 - Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	<i>Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</i>	<p>The historical Fiesta Project Drilling was completed between 2009 and 2016 and limited information is available on the nature and quality of the sampling.</p> <p>Current drilling at the Fiesta prospect. Drill samples are collected from below ~80m on 1m intervals from the cyclone of the RC drill rig with two 1-2 kg samples (original and duplicate) sub-samples collected in calico bags via a cone splitter on the rig.</p> <p>Samples are tested by pXRF and those over 1000 ppm Cu are assayed in the laboratory at 1m intervals, Samples below 1000ppm Cu are spear composited to 3m composites.</p> <p>All samples are prepared and analysed at ActLabs for 43 elements</p>
	<i>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</i>	All drilling RC samples were weighed, split in a cone splitter on the rig and composited on site
	<i>Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information.</i>	<p>Reverse Circulation drilling was used to generate 1m samples</p> <p>The Kalahari Sands are up to 100m thick over the prospect area and can provide difficulties in drilling with steel casing being required. No samples are collected prior to casing.</p> <p>Oxide mineralisation is noted to ~120m depth.</p>
Drilling techniques	<i>Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (e.g. core diameter, triple or standard tube, depth of</i>	Reverse Circulation (RC) drilling completed at Fiesta in 2024 by Hammerstein Drilling Namibia using 'best practice' to achieve maximum sample recovery and quality.

Criteria	JORC Code explanation	Commentary
	<i>diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</i>	
Drill sample recovery	<i>Method of recording and assessing core and chip sample recoveries and results assessed.</i>	Weights were collected from the complete sample collected every metre to manage recovery, the majority of samples were collected dry.
	<i>Measures taken to maximise sample recovery and ensure representative nature of the samples.</i>	Diligent control was maintained on the rig on sample recovery and all smaller samples recorded.
	<i>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</i>	No relationship to sample size has been noticed.
Logging	<i>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</i>	Samples were logged by qualified geologists and recorded in LogChief software.
	<i>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</i>	Logging is quantitatively recorded for every metre on oxidation, lithology and mineralisation that is stored in a MaxGeo Datashed database.
	<i>The total length and percentage of the relevant intersections logged.</i>	Reported in table in release.
Sub-sampling techniques and sample preparation	<i>If core, whether cut or sawn and whether quarter, half or all core taken.</i>	No diamond drilling was completed.
	<i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i>	Samples were split by a cone splitter on the cyclone and then composited by spearing where required. The majority of samples were collected dry.
	<i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i>	Samples were weighed, fine crushing of entire sample to 70% -2mm, split off 250 and pulverise split to better than 85% passing 75 microns. Samples were prepared at the ActLabs laboratory in Windhoek.
	<i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i>	Quality control procedures are in place with repeats, blanks inserted in the field.
	<i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i>	Quality control procedures are in place with 1 in 20 blanks and standards. Field duplicates were collected at 1 in 20 frequency

Criteria	JORC Code explanation	Commentary
	<i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i>	No information is available.
Quality of assay data and laboratory tests	<i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i>	Samples are analysed by ActLabs Canada for UT 4-Noronex and overlimit by ME-OG62 49 elements by a 4 acid digestion.
	<i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i>	No drilling data from field-portable pXRF tools are reported.
	<i>Nature of quality control procedures adopted (e.g. standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i>	Blanks and repeats are inserted at 1 in 20 sample intervals. Field duplicates are inserted at 1 in 20. Standards from Zambian Sedimentary Copper deposits of appropriate grades are inserted at 1 in 20.
Verification of sampling and assaying	<i>The verification of significant intersections by either independent or alternative company personnel.</i>	Sampling is overseen and managed by standard procedures.
	<i>The use of twinned holes.</i>	No holes have been twinned.
	<i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i>	Database is verified and managed by RockSolid Australia.
	<i>Discuss any adjustment to assay data.</i>	No adjustments have been made.
Location of data points	<i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i>	Hole locations are located using a hand held GPS
	<i>Specification of the grid system used.</i>	Coordinates are reported in WGS 84 UTM Zone 34S.
	<i>Quality and adequacy of topographic control.</i>	The Project area has a relatively flat relief, minor collar variations were applied.
Data spacing and distribution	<i>Data spacing for reporting of Exploration Results.</i>	Drillhole spacing is variable. Orientation was varied to cross interpreted sedimentary dips.

Criteria	JORC Code explanation	Commentary
	<i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.</i>	It is considered that drilling is insufficient to establish continuity of mineralisation and grade consistent for an Inferred Mineral Resource.
	<i>Whether sample compositing has been applied.</i>	Samples were composited to 3m if no visible mineralisation was reported.
<i>Orientation of data in relation to geological structure</i>	<i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i>	Variable hole orientations give some indication mineralisation is sub-vertical.
	<i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i>	True widths are not known at this time however a wireframe has been created between mineralised intercepts. Intercepts is interpreted to be 40 % of true thickness.
<i>Sample security</i>	<i>The measures taken to ensure sample security.</i>	Samples were delivered direct to the laboratory supervised by geologist.
<i>Audits or reviews</i>	<i>The results of any audits or reviews of sampling techniques and data.</i>	No audits completed.

Section 2 Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
<i>Mineral tenement and land tenure status</i>	<p><i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></p> <p><i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></p>	<p>The Humpback project consists of EPL 8656,8655, 8664, 8671 and 8672. The tenements were applied for by Noronex Exploration and Mining Ltd on 1st November 2021 and are granted until 17th November 2025. Gravity surveys were also completed in the Damara Duplex Project of EPL 8964 and 8965 that are granted until 16th March 2027</p> <p>Noronex Exploration and Mining Ltd holds a 100% legal and beneficial interest.</p> <p>Environmental Clearance Certificate were issued by the Minister of Environment and Tourism on 19 December 2022 in respect of exploration activities which clearance is to be valid for a period of three years</p> <p>Land access agreements signed for the Fiesta and Fortuna farms.</p> <p>Approval for the EPL's and exploration work has been supported by chiefs in the Hoveka Traditional Authority.</p> <p>There are no overriding royalties other than from the state, no special indigenous interests, historical sites or other registered settings are known in the region of the reported results.</p>

Criteria	JORC Code explanation	Commentary
		<p>Two new Prospecting Licenses applications have been submitted to the Botswana Ministry of Mines The applications under Senyetse Resources (Pty) Ltd are PL000030/2025-APP for 721.87 square kilometres and PL000032/2025-APP for 745.40 square kilometres. A new subsidiary Tilodi Metals Botswana Proprietary Limited has been set up in the country.</p> <p>The licenses have not been granted and no environmental or local authority discussions have taken part.</p>
<i>Exploration done by other parties</i>	<i>Acknowledgment and appraisal of exploration by other parties.</i>	<p>Significant exploration has been completed on the project by EISEB Prospecting and Mining (Pty) Ltd. A Joint Venture with Cupric Canyon PLC was very active over the project area for a number of years.</p> <p>Exploration was completed between 2009 and 2016 and over 120 holes have been drilled in the Fiesta-Fortuna district.</p> <p>An Access database with drilling and assay information is available and a number of reports.</p>
<i>Geology</i>	<i>Deposit type, geological setting and style of mineralisation.</i>	<p>The Humpback Project is located within a north easterly trending belt of Mesoproterozoic sediments, the Kalahari Copper Belt. Stratigraphy displays typical characteristics of a sedimentary copper system, including a basal sequence of bimodal volcanics overlain by red-bed sediments, mixed reduced marine siliciclastic and carbonate rocks..</p> <p>Copper mineralisation occurs throughout the belt along, and above, the main redox contact between the Ngwako Pan and D’Kar Formations. Mineralisation is largely epigenetic and primarily related to basin inversion during a prolonged mineralising event during the Damara (Pan-African) orogeny. Mineralisation is concentrated on major reactivated structures above basement highs where basinal fluids are concentrated in reductant traps during basin inversion.</p> <p>Chalcocite and chalcopyrite are the dominant copper-bearing mineral at the Fiesta Project, with other copper sulphide mineralisation. Chrysocolla and malachite are observed as the main minerals in the oxide ore in the district.</p>

Criteria	JORC Code explanation	Commentary
		<p>The mineralisation is stratiform and occurs in a sub-parallel lode that can be modelled over 3 km's..</p> <p>The Damara Duplex on the northern margin of the Copper Belt contains volcanic units and interpreted gneissic, amphibolite and marble basement of the Damara suture zone. A number of covered magmatic complexes have never been drilled and their composition is unknown.</p>
<i>Drill hole Information</i>	<p><i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i></p> <p><i>easting and northing of the drill hole collar</i></p> <p><i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i></p> <p><i>dip and azimuth of the hole</i></p> <p><i>down hole length and interception depth</i></p> <p><i>hole length.</i></p> <p><i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></p>	Exploration results when reported are based on a compilation of current drilling and historical drilling.
<i>Data aggregation methods</i>	<p><i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (e.g. cutting of high grades) and cut-off grades are usually Material and should be stated.</i></p> <p><i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></p> <p><i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></p>	<p>Intervals when reported are reported based on a 0.3 % Cu cut-off and include up to 6m waste below the cut-off. Results reported are greater than 0.3m% Copper.</p> <p>The prices used to calculate CuEq are based on US\$8,400/t copper, and US\$24/oz. Recoveries of 93% Cu and 86% Ag, Payability of 97% Cu and 90% Ag, TC/RC of 0.2 and 0.3US/lb, Namibian payabilities are based upon the Motheo feasibility studies.</p>
<i>Relationship between mineralization widths and intercept lengths</i>	<p><i>These relationships are particularly important in the reporting of Exploration Results.</i></p> <p><i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i></p> <p><i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (e.g. 'down hole length, true width not known').</i></p>	<p>Due to RC drilling and no visual review possible of the drillcore it is not clear on true thickness downhole.</p> <p>Fiesta true thickness has been estimated by building a wireframe of Zone 1 over 3.5 km strike, intercepts are between 40 and 60% of drilled widths so an estimated 50% has been extrapolated across the drilling.</p>

Criteria	JORC Code explanation	Commentary
<i>Diagrams</i>	<i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i>	Regional and Fiesta Drilling Plan.
<i>Balanced reporting</i>	<i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i>	All intervals below transported cover were assayed and reported.
<i>Other substantive exploration data</i>	<i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i>	<p>Results from gravity surveys completed during 2024 is reported in this release.</p> <p>The gravity survey was completed by Geophysics LDA a local Namibian geophysical contractor based in Swakopmund, Namibia between August and October 2024. Data was collected using 2 Scintrex CG5 gravity meters and a Emlid and Leica differential GPS in RTK mode. Three new base stations were established and gravity readings were corrected for drift corrections of under 0.01mGal</p> <p>Gravity readings were collected on either an 800 x 200m grid with infill lines at 400m x 100m or on 800m x 100m lines. Repeated values were collected for quality control..</p>
<i>Further work</i>	<i>The nature and scale of planned further work (e.g. tests for lateral extensions or depth extensions or large-scale step-out drilling).</i>	A program of further work is being planned to follow up the anomalous results
	<i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i>	A diagram is provided in the body of the report for future targets in the area.