

ASX Announcement

Rogozna Gold and Base Metals Project, Serbia - Drilling Update

KOTLOVI GROWS WITH HIGH-GRADE GOLD INTERSECTIONS

New high-grade drill intercepts at the emerging Kotlovi discovery expand the known mineralisation and reinforce
the exceptional growth potential at Rogozna

Highlights:



- o ZRSD25206
 - **34.9m @ 2.2g/t Au from 324.2m, including:**
 - 14.0m @ 4.1g/t Au from 328.2m.
- o ZRSD25200A
 - 14.0m @ 1.4g/t Au from 318.1m, including:
 - 6.0m @ 2.8g/t Au from 318.1m; and
 - 24.8m @ 0.7g/t Au from 352.1.
- o **ZRSD25215A**
 - 10.9m @ 0.6g/t Au from 347.8m; and
 - 18.0m @ 0.8g/t Au from 516.3m, including:
 - 6.0m @ 1.5 g/t Au from 516.3m.

Mineralisation has now been defined along ~300m of NNW-SSE strike and remains open in all directions.

Drilling continues with seven rigs operating across the Rogozna Project, with assay results pending for multiple holes and further results expected to be released in coming weeks.

Strickland remains well-funded, with cash and liquids at 30 September 2025 totalling \$41.8 million.

Introduction

Strickland Metals Limited (ASX: STK) (**Strickland** or the **Company**) is pleased to report significant new drilling results from the Kotlovi Prospect, an emerging new discovery within its 100%-owned ~7.4Moz AuEq Rogozna Gold and Base Metals Project¹ in Serbia (Figure 1).

Strickland's Managing Director, Paul L'Herpiniere, said: "Kotlovi is continuing to shape up as an important new discovery at Rogozna, with the potential to make a significant contribution to the project's overall growth trajectory. These latest drill results have further expanded the known mineralisation, which now extends over a 300m strike length.

Several holes have now returned thick zones of strong mineralisation, with the mineralised zone still open in all directions offering further significant upside. Given its strategic location just 350 metres from the 1.28Moz AuEq Medenovac Deposit and the growing scale of the mineralisation, Kotlovi looks like it will feature prominently in our ongoing drilling and development plans."

-

¹ Refer to "Table 1: Rogozna JORC Inferred Mineral Resource Estimates" at the end of this release for further details regarding the Rogozna Resource.






Figure 1. Rogozna Project – Geology, Deposits and Prospects.

Exploration Update

Exploration drill-holes ZRSD25200A and ZRSD25206 were designed to test the up-dip extension of the mineralisation defined in the discovery holes ZRSD24158/ZRSD24163² and follow-up of extensive gold mineralisation encountered in ZRSD25189³, which was completed at Kotlovi in 2024 and 2025 respectively.

Drill-hole ZRSD25215A was designed to test the northern strike extent of the mineralisation at Kotlovi, representing a step-out of 150m from the discovery hole ZRSD24158.

 $^{^2\}mbox{Refer}$ to ASX announcement dated 11 November 2024.

³Refer to ASX announcement dated 6 August 2025.



ZRSD25200A

Significant intersections include:

- 14.0m @ 1.4g/t Au, 0.1% Zn & 1.9g/t Ag (1.5g/t AuEq⁴) from 318.1m, including:
 - o 6.0m @ 2.8g/t Au & 0.9g/t Ag (2.8g/t AuEq⁴) from 318.1m; and
- 24.8m @ 0.7g/t Au & 0.6g/t Ag (0.7g/t AuEq⁴) from 352.1; and
- 3.6m @ 1.9g/t Au & 2.6g/t Ag (1.9g/t AuEq⁴) from 407.6m.

ZRSD25206

Significant intersections include:

- 34.9m @ 2.2g/t Au & 2.4g/t Ag (2.3g/t AuEq⁴) from 324.2m, including:
 - 14.0m @ 4.1g/t Au & 2.4g/t Ag (4.2g/t AuEq⁴) from 328.2m.

ZRSD25215A

Significant intersections include:

- 10.9m @ 0.6g/t Au & 0.6g/t Ag (0.6g/t AuEq⁴) from 347.8m; and
- 18.0m @ 0.8g/t Au & 7.1g/t Ag (1.1g/t AuEq⁴) from 516.3m, including:
 - o 6.0m @ 1.5g/t Au, 0.2 % Cu, 0.1 % Pb, 0.1 % Zn & 18.8g/t Ag (2.1g/t AuEq⁴) from 516.3m.




Figure 2. Plan view map of the Kotlovi-Medenovac area, showing drill-hole intercepts, gold-arsenic soil geochemical response and section line for holes reported on in this announcement.

 $^{^4}$ For Kotlovi AuEq grade is based on metal prices of gold (US\$2,250/oz), copper (US\$10,000/t), silver (US\$25/oz), lead (US\$2,200) and zinc (US\$3,000/t) and overall metallurgical recoveries of 80% for these metals. These estimates are based on Strickland's interpretation of potential long term commodity prices and their interpretation of initial metallurgical test work and use the following formula: Au Equivalent (g/t) = Au (g/t) + 1.38 x Cu(%) + 0.011 x Ag (g/t) + 0.304 x Pb(%) + 0.413 x Zn(%). It is the Company's opinion that all the elements included in the metal equivalents calculations have a reasonable potential to be recovered and sold.






Figure 3. Kotlovi cross-section view along A-B, showing results for ZRSD25206 in relation to previously reported drill intercepts.

Mineralisation Styles and Controls

Gold mineralisation at Kotlovi has a strong, steeply dipping NNW to SSE structural control and occurs near the base of volcanics in proximity to the contact with the Kotlovi stock, a large quartz-diorite intrusion that separates Kotlovi from the neighbouring 1.28Moz AuEq Medenovac Deposit.

In drill-hole ZRSD25200A, mineralisation includes both endoskarn hosted in chlorite-clay altered, quartz-diorite (Figure 4) in addition to more typical green garnet-skarn hosted gold mineralisation, with both styles being characterised by disseminated pyrite and arsenopyrite.

The high-grade gold zones in ZRSD25206 are hosted in fault gouge and brecciated andesite (Figure 5) that is intruded by chloritized and clay altered quartz-diorite with disseminated pyrite.

The mineralised intercept in ZRSD25215A is hosted by green garnet-skarn at the contact with overlying andesite and contains disseminated pyrite and chalcopyrite throughout the intersection.

Importantly, the drill-defined mineralisation at Kotlovi remains open in all directions.






Figure 4. Core photograph of ZRSD25200A from 318.1m to 320.1 m of chloritized quartz-diorite with disseminated pyrite and carbonate cavities -6.0g/t Au.



Figure 5. Core photograph of ZRSD25206 from 347.3m to 348m of cement-supported polymictic (andesite, limestone) breccia with disseminated to semi-massive pyrite –13.5g/t Au.



Next Steps

Seven rigs continue drilling across the Rogozna Project, with four rigs focused on the gap zone of Gradina and three rigs dedicated to discovery drilling across the project.

Assays remain outstanding for multiple holes, with further results expected to be released over coming weeks.

This release has been authorised by the Company's Managing Director Mr Paul L'Herpiniere.

Ends —

For further information, please contact:

Paul L'Herpiniere

Managing Director

Phone: +61 (8) 6317 9875 info@stricklandmetals.com.au stricklandmetals.com.au

Media Inquiries:

Nicholas Read – Read Corporate Phone: +61 (8) 9388 1474 info@readcorporate.com.au

Competent Person's Statement

The information in this report that relates to Exploration Results for its Rogozna Project is based on information compiled or reviewed by Mr Paul L'Herpiniere who is the Managing Director of Strickland Metals Limited and is a current Member of the Australian Institute of Mining and Metallurgy (AusIMM). Mr Paul L'Herpiniere has sufficient experience, which is relevant to the style of mineralisation and types of deposit under consideration and to the activities undertaken, to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code of Reporting of Exploration Results, Mineral Resources and Ore Reserves". Mr L'Herpiniere consents to the inclusion in the report of the matters based on the information in the form and context in which it appears.

The information in this announcement that relates to Mineral Resources has been extracted from various Strickland ASX announcements and are available to view on the Company's website at www.stricklandmetals.com.au or through the ASX website at www.asx.com.au (using ticker code "STK"). The Company confirms that it is not aware of any new information or data that materially affects the information included in the original market announcement. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcement and that all material assumptions and technical parameters underpinning the Mineral Resource Estimates in the relevant market announcement continue to apply and have not materially changed.

Forward-Looking Statements

This announcement may contain certain forward-looking statements, guidance, forecasts, estimates, prospects, projections or statements in relation to future matters that may involve risks or uncertainties and may involve significant items of subjective judgement and assumptions of future events that may or may not eventuate (Forward-Looking Statements). Forward-Looking Statements can generally be identified by the use of forward-looking words such as "anticipate", "estimates", "will", "should", "could", "may", "expects", "plans", "forecast", "target" or similar expressions and may include, without limitation, statements regarding plans, strategies and objectives of management, anticipated production and expected costs. Indications of, and guidance on future earnings, cash flows, costs, financial position and performance are also Forward Looking Statements.

Persons reading this announcement are cautioned that such statements are only predictions, and that actual future results or performance may be materially different. Forward-Looking Statements, opinions and estimates included in this announcement are based on assumptions and contingencies which are subject to change, without notice, as are statements about market and industry



trends, which are based on interpretation of current market conditions. Forward-Looking Statements are provided as a general guide only and should not be relied on as a guarantee of future performance.

No representation or warranty, express or implied, is made by Strickland that any Forward-Looking Statement will be achieved or proved to be correct. Further, Strickland disclaims any intent or obligation to update or revise any Forward-Looking Statement whether as a result of new information, estimates or options, future events or results or otherwise, unless required to do so by law.



Table 1: Rogozna JORC Inferred Mineral Resource Estimates

Prospect	Tonnes (Mt)	AuEq (g/t)	Au (g/t)	Cu (%)	Ag (g/t)	Pb (%)	Zn (%)	AuEq (Moz)	Au (Moz)	Cu (kt)	Ag (Moz)	Pb (kt)	Zn (kt)
Medenovac (February 2025) ^A	21	1.9	0.77	0.27	6.3	0.11	1.54	1.28	0.52	57	4.3	23	320
Shanac (March 2025) ^A	150	1.1	0.64	0.12	5.8	0.24	0.34	5.30	3.09	180	28.0	360	510
Copper Canyon (October 2021) ^B	28	0.9	0.40	0.30	-	-	-	0.81	0.36	84	-	-	-
Total ^c	199	1.2	0.62	0.16	5.0	0.19	0.41	7.40	3.97	320	32.2	380	830

Table Notes:

- A. For Medenovac (February 2025) and Shanac (March 2025) AuEq grade is based on metal prices of gold (US\$2,250/oz), copper (US\$10,000/t), silver (US\$25/oz), lead (US\$2,200) and zinc (US\$3,000/t) and overall metallurgical recoveries of 80% for these metals. These estimates are based on Strickland's interpretation of potential long term commodity prices and their interpretation of initial metallurgical test work and use the following formula: Au Equivalent (g/t) = Au (g/t) + 1.38 x Cu(%) + 0.011 x Ag (g/t) + 0.304 x Pb(%) + 0.413 x Zn(%). It is the Company's opinion that all the elements included in the metal equivalents calculations have a reasonable potential to be recovered and sold. A 1.0 g/t AuEq cut-off has been used for the Medenovac Resource Estimate. A 0.60 g/t AuEq cut-off has been used for the Shanac estimate.
- B. For Copper Canyon (October 2021) AuEq grade based on metal prices of gold (US\$1,750/oz), copper (US\$10,000/t), and metallurgical recoveries of 80% for both metals. These estimates are based on the Company's assumed potential commodity prices and recovery results from initial and ongoing metallurgical test work and use the following formula for Copper Canyon: AuEq (g/t) = Au (g/t) + 1.55 x Cu (%). It is the Company's opinion that all the elements included in the metal equivalents calculations have a reasonable potential to be recovered and sold. A 0.4g/t AuEq cut-off has been used for the Copper Canyon Resource Estimate.
- C. Rounding errors are apparent in the summation of total resources.

Please refer to the Company's ASX announcements dated:

- 27 March 2025 titled: "Shanac Resource Increases to 5.30Moz AuEq, Taking Rogozna to 7.40Moz AuEq" for full details regarding the Shanac Mineral resource Estimate;
 - 19 February 2025 titled: "Rogozna Resource Increases by 23% to 6.69Moz AuEq" for full details regarding the Medenovac Mineral Resource Estimate; and
- 17 April 2024 titled: "Acquisition of the 5.4Moz Au Eq Rogozna Gold Project" for full details regarding the Copper Canyon Mineral Resource Estimate.



Appendix A - Significant Intercepts

Table 2 – Kotlovi Significant Intercepts

		Collar	Coordinates	(m)	Depth	Orientation	Downh	ole Inter	val (m)			Gr	ade		
	Hole ID	Easting	Northing	RL	(m)	Azi/Dip (degrees)	From	То	Length	Au (g/t)	Cu (%)	Pb (%)	Zn (%)	Ag (g/t)	AuEq (g/t)*
	ZRSD25200A						318.1	332.1	14.0	1.4	0.0	0.0	0.1	1.9	1.5
	including						318.1	324.1	6.0	2.8	0.0	0.0	0.0	0.9	2.8
5	including	469,132	4,770,128	1,119	545	65/-55	318.1	320.1	2.0	6.0	0.0	0.0	0.0	1.6	6.0
	and						352.1	376.9	24.8	0.7	0.0	0.0	0.0	0.6	0.7
7	and						407.6	411.1	3.6	1.9	0.0	0.0	0.0	2.6	1.9
	ZRSD25206						324.2	359.1	34.9	2.2	0.0	0.0	0.0	2.4	2.3
	including	469,129	4,770,128	1,119	463	80/-60	328.2	342.2	14.0	4.1	0.0	0.0	0.0	2.4	4.2
Y	and						347.3	348.0	0.7	13.5	0.0	0.0	0.0	2.6	13.5
	ZRSD25215A						347.8	358.7	10.9	0.6	0.0	0.0	0.0	0.6	0.6
	and	460 425	4 770 400	4 000	650	270/70	516.3	534.3	18.0	0.8	0.0	0.0	0.0	7.1	1.1
	including	469,435	4,770,400	1,090	650	270/-70	516.3	522.3	6.0	1.5	0.2	0.1	0.1	18.8	2.1
	including						516.3	518.3	2.0	1.8	0.1	0.1	0.1	40.5	2.7

^{*}For Kotlovi AuEq grade is based on metal prices of gold (US\$2,250/oz), copper (US\$10,000/t), silver (US\$25/oz), lead (US\$2,200) and zinc (US\$3,000/t) and overall metallurgical recoveries of 80% for these metals. These estimates are based on Strickland's interpretation of potential long term commodity prices and their interpretation of initial metallurgical test work and use the following formula: Au Equivalent (g/t) = Au (g/t) + 1.38 x Cu(%) + 0.011 x Ag (g/t) + 0.304 x Pb(%) + 0.413 x Zn(%). It is the Company's opinion that all the elements included in the metal equivalents calculations have a reasonable potential to be recovered and sold.



Appendix B – JORC Table 1 – Kotlovi

Section 1 Sampling Techniques and Data

	Criteria	JORC Code explanation	Commentary
	Sampling techniques	 Nature and quality of sampling (e.g. cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done this would be relatively simple (e.g. 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (e.g. submarine nodules) may warrant disclosure of detailed information. 	 Zlatna Reka Resources (ZRR) The Kotlovi drilling database comprises data from diamond drilling completed by ZRR including 6 holes for a total of 3,996m of drilling. Drilling and sampling utilised appropriate, industry standard methods and was closely supervised by company geologists. The core was halved with a diamond saw to provide assay samples. Drilling utilised triple tube core barrels. Core recovery measurements confirm the representivity of the sampling. Sample lengths range from around 0.1m to rarely greater than 10.0m, with around 90% of the combined drilling having sample lengths of 1.0m to 3.0m. Most sample lengths are 2m. ZRR samples were submitted to ALS in Bor, Serbia for sample preparation, with pulverised samples transported to ALS in Rosia Montana, Romania for analysis for gold by fire assay, and ALS Ireland for ICP analysis by four-acid digest for attributes including copper. Previous Explorers (Euromax and Eldorado Gold)
7	\cup		No previous drilling has been undertaken over the Kotlovi prospect area.
	Drilling techniques	• Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).	 All drilling was by diamond core at PQ, HQ and NQ diameters (122.6, 96.0mm and 75.7mm hole diameter). ZRR utilised triple tube core barrels with core oriented by an "Ace Core Tool" electronic tool.
12021	Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures taken to maximise sample recovery and ensure representative nature of the samples. 	Sample recovery was maximised by use of appropriate drilling techniques including use of triple tube core drilling.



Criteria	JORC Code explanation	Commentary
	 Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 Recovered core lengths average 99% recovery with little variability between drilling phases consistent with the author's experience of high-quality diamond drilling.
		 There is no notable relationship between core recovery and gold and copper grades. Available information demonstrates that sample bias due to preferential loss/gain of fine/coarse material has not occurred.
Logging	Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.	 Drilling and sampling utilised appropriate, industry standard methods and was closely supervised by company geologists. The core was halved with a diamond saw to provide assay samples. ZRR utilised triple tube core barrels.
	Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc.) photography.	Core recovery measurements confirm the representivity of the sampling.
	The total length and percentage of the relevant intersections logged.	
Sub-sampling	If core, whether cut or sawn and whether quarter, half or all core taken.	Zlatna Reka Resources (ZRR)
techniques and sample preparation	If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.	 Field-sampling employed appropriate methods and was supervised by company geologists.
	For all sample types, the nature, quality and appropriateness of the sample preparation technique.	 Core was halved for assaying with a diamond saw with sample lengths ranging from around 0.1m to rarely greater than 10m, with around 90% of
	 Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples. 	the combined drilling having sample lengths of 1.0m to 3.0m, with most samples being 2.0m in length.
	 Measures taken to ensure that the sampling is representative of the in-situ material collected, including for instance results for field duplicate/second- half sampling. 	 Available information indicates that, at the current stage of project assessment, the sample preparation is appropriate for the mineralisation style.
	Whether sample sizes are appropriate to the grain size of the material being sampled.	 Available information indicates that sample sizes are appropriate to the grain size of the material being sampled.
	•••••	 Routine monitoring of laboratory performance included submission of coarse blanks and reference standards for all drilling phases.



	Criteria	ORC Code explanation	Co	ommentary
			•	Sample preparation of ZRR samples comprised oven drying, crushing to 70% passing 2 mm, with 1 Kg rotary split sub-samples pulverised to 85% passing 75 microns.
			Pr	revious Explorers (Euromax and Eldorado Gold)
			•	Routine monitoring of laboratory performance included submission of coarse blanks and reference standards for all drilling phases. Field duplicates supplied for Euromax and Eldorado drilling and provide an indication of the repeatability of field sampling for these drilling phases.
	15)		•	Preparation of Eldorado samples submitted to ALS comprised oven drying, crushing to 70% passing 2 mm, with sub-samples pulverised to 85% passing 75 microns.
	Quality of	The nature, quality and appropriateness o	, , ,	latna Reka Resources (ZRR)
	assay data and laboratory	procedures used and whether the technique	•	ZRR samples were assayed for Au and Base Metals by fire assay and ICP with
	tests	 For geophysical tools, spectrometers, hand parameters used in determining the analysis 		four acid digest respectively. No analytical measurements from geophysical tools inform the Exploration Results.
		 Mature of quality control procedures adopted (e.g. standards, blackers, external laboratory checks) and whether acceptable level accuracy (ie lack of bias) and precision have been established. 	=	Monitoring of laboratory performance included submission of coarse blanks
			whether acceptable levels of	and reference standards for all drilling phases. Field duplicate assays provide an indication of the repeatability of field sampling. Analyses of coarse duplicates of crushed samples collected for ZRR's drilling at an average frequency of around 1 duplicate per 20 primary samples support the repeatability and reliability of sample preparation.
			•	Acceptable levels of accuracy and precision have been established for attributes included in the Exploration Results.
			Pr	revious Explorers
			•	Monitoring of laboratory performance included submission of coarse blanks and reference standards for all drilling phases. Field duplicate assays provide an indication of the repeatability of field sampling for Euromax and Eldorado drilling. Acceptable levels of accuracy and precision have been established for attributes included in the Exploration Results.
	(D)			

(



Criteria	JORC Code explanation	Com	mentary
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols. Discuss any adjustment to assay data. 	• 	No twinned holes have been drilled at Kotlovi. For ZRR drilling, sampling and geological information was entered directlinto electronic logging templates which were imported into ZRR's maste acQuire database. Assay results were merged directly into the database from digital files provided by ALS. No assay results were adjusted.
Location of data points	 Accuracy and quality of surveys used to locate drill holes (collar and downhole surveys), trenches, mine workings and other locations used in Mineral Resource estimation. Specification of the grid system used. Quality and adequacy of topographic control. 		Drill collars were defined World Geodetic System 1984 (WGS84), Sector 34 coordinates derived from differential global positioning system (GPS surveys using the Gaus-Kruger projection and Hermanskogel datustransformed to WGS84 Universal Transverse Mercator (UTM) coordinate Holes were generally downhole surveyed by magnetic single shot surveys ogyro tools.
		•	Elevations of ZRR holes commonly significantly differ from the DTM. Hole paths and surface topography have been located with sufficient confidence.
Data spacing and distribution	 Data spacing for reporting of Exploration Results. Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied. Whether sample compositing has been applied. 		Kotlovi drilling is at an exploration stage and no systematic drilling has been undertaken. The holes were planned to intersect various potenti mineralisation trends observed from the surface soil geochemical dataset
Orientation of data in relation to geological structure	 Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type. If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material. 	! -	Kotlovi drilling is at an early stage and variably orientated. These are exploratory holes and were planned to intersect trends in the sogeochemistry set and our current understanding of controlling structure True widths are estimated to be between 0.5 and 1 of apparent width. The drilling orientations provide un-biased sampling of the mineralisation.



Criteria	JORC Code explanation	Commentary
Sample security	The measures taken to ensure sample security.	 ZRR diamond core was delivered to the core shed by company personnel. Core-cutting and sampling was supervised by company geologists. Samples collected in canvas bags were sealed on wooden pallets by heavy duty plastic wrapping for transportation to the assay laboratory by courier. No third parties were permitted un-supervised access to the samples prior to delivery to the sample preparation laboratory.
		The general consistency of results between sampling phases provides additional confidence in the general reliability of the data.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	No audits of sampling techniques and data were conducted.

Section 2: Reporting of Exploration Results

(Criteria listed in the preceding section also apply to this section)

Criteria	JORC Code explanation	Со	mmentary
Mineral tenement and land tenure status	• Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.	•	The Rogozna Project is contained within four exploration licenses, Šanac na Rogozni, Zlatni Kamen, Leča and Pajsi Potok with a combined area of approximately 184 km ² . The exploration licenses are 100% owned by ZRR, a wholly owned Serbian subsidiary of Betoota Holdings (Betoota).
	• The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.	•	The Kotlovi Prospect is located within the Sanac na Rogozni exploration license.
		•	In Serbia, exploration licenses are granted for an eight year term comprising periods of three years, three years and two years, with renewal documents needing to be submitted to Serbian authorities after each period.
D D		•	In September 2023 the Šanac na Rogozni license was renewed for its second 3-year exploration period, with the potential for further extension of an additional two years.
		•	There are no known impediments to obtaining a licence to operate in the area.



Criteria	JORC Code explanation	Commentary
		 Pursuant to a royalty agreement between Betoota and Franco Nevada, Franco Nevada will receive a 2% net smelter return (NSR) on gold and 1.5% NSR on all other metals extracted from the Šanac na Rogozni License. ZRR has a royalty agreement with Mineral Grupa d.o.o, whereby Mineral Grupa d.o.o. is entitled to a 0.5% NSR on all metals produced from the Zlatni Kamen License.
Exploration done by other	Acknowledgment and appraisal of exploration by other parties.	The Kotlovi exploration datasets include data from Euromax and Eldorado Gold and Zlatna Reka Resources.
parties		 Available information indicates the data from previous explorers are adequately reliable.
Geology	Deposit type, geological setting and style of mineralisation.	 Rogozna lies within the Serbian Cenozoic igneous province of the Alpine-Himalayan orogenic and metallogenic system which geographically overlaps the Serbo-Macedonian Magmatic and Metallogenic Belt. The Project is situated at the western branch of the Vardar Zone West Belt at the border of two major tectonic units, the Drina- Ivanjica thrust sheet and the Vardar Zone West Belt separated by a large fault zone in NW- SE direction, which is considered to play a significant role in controlling the Oligocene - Miocene magmatism and the mineralisation in the area.
		• Basement rocks comprise serpentinites, directly overlain by a Cretaceous succession of marls, limestones and sandy-clays, which are in turn overlain by andesitic pyroclastics related to an earlier stage of Cenozoic volcanism. All of these units are affected by later Cenozoic magmatism represented by quartz-latitic to trachytic dykes and stocks, which intrude all older units and give rise to the formation of extensive skarn alteration at the contact between the limestones and intrusions. The skarns are exposed in the southern part of the project, including Copper Canyon where there has been block uplifting and subsequent erosion of the andesitic pyroclastics.
(2) 15		 Rogozna mineralisation, including Kotlovi, represents a large scale magmatic hydrothermal system which hosts a skarn based Au-Cu +/- Zn, Ag and Pb mineralised system. Most of the mineralisation is associated with retrograde skarn development in spatial association with quartz latite dykes.



Criteria	JORC Code explanation	Cor	mmentary
			Distal, higher-grade skarn hosted mineralisation occurs at Gradina, Gradina North, and Copper Canyon South projects, and at Medenovac there is also lower tenor mineralisation that is developed in the overlying andesition volcanic rocks. Cu generally occurs as chalcopyrite in association with pyrrhotite and pyrite, and less commonly with sphalerite and galena.
Drill hole Information	 A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes: 	•	Appropriate information is included in the body of this report (see Appendi A).
	o easting and northing of the drill hole collar		
	 elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar 		
	o dip and azimuth of the hole		
	 down hole length and interception depth 		
	o hole length.		
	• If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.		
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. 	•	Significant drill hole results are reported on a length weighted basis, a cutoff grades of >0.5g/t AuEq. No upper cuts were applied. Higher-grade intercepts are reported at cutoff grades of >1.5g/t AuEq.
	 Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail. 	•	In reporting of Exploration Results for Kotlovi Au equivalent grades are based on metal prices of Au (\$US2,250/oz), Cu (\$US10,000/t), Au (\$US25/oz), Pb (\$US2,200/t), Zn (\$US3,000/t), and metallurgical recoveries of 80% for all metals. These estimates are based on ZRR's assumed potential
	The assumptions used for any reporting of metal equivalent values should be clearly stated.		commodity prices and recovery results from initial and ongoing metallurgical test work and give the following formula: AuEq (g/t) =Au (g/t $+ 1.38 \times Cu(\%) + 0.011 \times Ag (g/t) +0.304 \times Pb(\%) +0.413 \times Zn(\%)$.
		•	In the Company's opinion all elements included in the metal equivalen



Criteria	JORC Code explanation	Commentary
		calculation have a reasonable potential to be recovered and sold. These estimates are based on current commodity prices and the Company's interpretation of initial metallurgical testwork results.
Relationship Detween mineralisation widths and ntercept engths	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known'). 	 Kotlovi drilling includes a range of orientations, with ratios of true mineralisation widths to down-hole widths ranging from less than half to around 1.
iagrams	 Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	Appropriate diagrams are included in the report.
Balanced eporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results. 	Appropriate information is included in the body of the report.
Other ubstantive exploration data	 Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances. 	 Preliminary metallurgical test work completed for all deposits from 2020 to 2022 included test work aimed at analysis of bulk samples, grade variability analysis, comminution characterisation, Cu and Zn concentrate analysis, gravity gold recovery and bulk sulphide floatation defined projects. This work suggested amenability to conventional processing with flotation recoveries for the relevant metals generally in the range of 78 to 86% for
		the currently defined deposits. Immersion density measurements were performed on core samples from all modern Rogozna drill phases at an average of around one sample per 6 m.
9		 Geological, mapping, soil and rock chip sampling, and geophysical surveys by previous workers including magnetic and gravity surveys aid ZRR's planning of exploratory drilling.



Criteria	JORC Code explanation	Commentary
		 Geochemical survey data shows strong gold and pathfinder element anomalism at Kotlovi. Anomalous soil geochemical values after levelling the geochemical data using mapped lithology and using ZScore analysis, are ZScore of >1 for the multielement data indicates strong anomalism, >0.5 is moderate anomalism and >0.2 is slightly anomalous.
		• The Kotlovi geochemical survey involved soil samples taken on roughly 100m-spaced, East-West-orientated lines, with individual samples collected along 100m intervals on each line. Soils samples were collected from the "B" horizon, at roughly 30cm depth. The samples were sieved to -1mm size fraction and assayed by fire assay for gold and ICP with four acid digest for all other elements.
Further work	 The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling). Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Planned future work at Kotlovi includes further diamond drilling, with both infill and extensional drilling designed to demonstrate continuity of mineralisation and define the mineralised footprint and geological controls.